RLC-HydroG

Hydrogeological Assessment Smiths Falls Compost Site 3514 Highway 43, Smiths Falls, Ontario



RLC-HydroG – Hydrogeological Services Ottawa, Ontario July 8, 2025

Table of Contents

1	INTR 1.1	ODUCTION	
	1.2	Scope of Work	
2		DESCRIPTION	2
	2.2	Zoning	4
	2.3	Land Use	4
	2.4	Topography	5
	2.5	Hydrology	5
3	MET 3.1	HODOLOGYPre-Consultation	
	3.2	Background Information	8
	3.3	Test Pits	8
	3.4	Boreholes and Monitoring Wells	8
	3.5	Surface Water Sampling	9
	3.6	Elevation Survey	10
	3.7	Groundwater Elevation Monitoring	10
	3.8	Groundwater Sampling	10
4		LOGY	
	4.1	Surficial Geology	
	4.2	Terrain Analysis	
	4.3	Bedrock Geology	13
5	HYD 5.1	ROGEOLOGY	
	5.2	Closest Water Supply Wells	17
	5.3	Potential Sources of Contamination.	18
	5.4	Hydrogeological Sensitivity	18
	5.5	Water Budget	19
6	IMP/ 6.1	ACT ASSESSMENTSoil Impacts	
	6.2	Surface Water Impacts	24

	6.3	Groundwater Impacts	25
	6.4	Natural Functions of the Ecosystem	27
	6.5	Mitigation	27
7	MON	IITORING PLAN	28
	7.1	Surface Water Monitoring	28
	7.2	Groundwater Monitoring	29
	7.3	Reporting	30
8	CON	TINGENCY PLAN	31
	8.1	Trigger Mechanisms	31
9	CON	CLUSIONS	31
1(DMMENDATIONS	
1:	L LIMI	TING CONDITIONS	33
12	2 REFE	RENCES	34

ATTACHMENT A Legal Survey

ATTACHMENT B Zoning Map

ATTACHMENT C Elevation Survey

ATTACHMENT D SLT Borehole Logs

ATTACHMENT E Town of Smiths Falls IPZ

ATTACHMENT F Water Well Records

ATTACHMENT G Laboratory Certificate of Analysis – TP2-9

ATTACHMENT H Laboratory Certificate of Analysis – Borehole Soils

ATTACHMENT I Laboratory Certificate of Analysis – Surface Water

ATTACHMENT J Laboratory Certificate of Analysis – Overburden Groundwater

ATTACHMENT K Spill Response Plan



July 8, 2025

Project Number: 25022

Vanessa Bernicky
Town of Smiths Falls
77 Beckwith Street North
PO Box 695
Smiths Falls, Ontario K7A 2B8
Email: vbernicky@smithsfalls.ca

Re: Hydrogeological Assessment

Smiths Falls Compost Site

3514 Highway 43, Smiths Falls, Ontario

1 INTRODUCTION

RLC-HydroG was retained by St. Lawrence Testing & Inspection Co. Ltd. (SLT) on behalf of the Town of Smiths Falls to conduct a hydrogeological assessment for the Smiths Falls Compost Site located at 3514 Highway 43, Smiths Falls, Ontario. The location of the site is indicated in Figure 1. The Smiths Falls Compost Site has been in operations since 1993.

The site is operated under Provisional Certificate of Approval A450106. The Town of Smiths Falls is currently in the process of obtaining an amendment to the Environmental Compliance Approval (ECA) for the Compost Site.

1.1 Objectives

The objectives of the hydrogeological assessment were determined based on consultation with the Town of Smiths Falls, and MECP technical information requirements for compost sites (MECP, 2013) including the assessment of:

- Physical conditions at the site (outdoor composting operation on a granular base).
- Water use conditions in the area.
- Surface water hydrology and quality.
- Terrain analysis, soil quality, and geology.
- Hydrogeology including water table elevations and groundwater flow directions.
- Overburden groundwater quality.
- Identification of water supply wells, water takings, and other water uses.
- Distance to nearest water supply wells.
- Regulatory requirements.
- Municipal zoning.
- Conservation authority requirements.
- Potential impacts to soils, groundwater, surface water and water users.
- Monitoring and contingency plans to detect and mitigate impacts.

Figure 1: Site Location



1.2 Scope of Work

The following scope of work was developed in consultation with SLT and the Town of Smiths Falls:

- Pre-consultation with RVCA.
- Desktop study including a review of background information (water well records, geological databases, hydrology information, topography, known water uses).
- Review of previous site investigation reports by SLT.
- Site Visit
- Traverse the site and view surrounding areas.
- Inspect new overburden monitoring wells.
- Measure groundwater elevations at monitoring wells.
- Conduct an elevation survey to establish well reference elevations.

2 SITE DESCRIPTION

The civic address of the Smiths Falls Compost Site is 3514 Highway 43, Smiths Falls, Ontario. The site occurs on Parts of Concession 5 & 6, Lots 1 & 2, Geographic Township of North Elmsley, Township of Drummond

- North Elmsley, Ontario. The Compost Site has an area of 1.5 hectares. A Plan of Survey by Callon Dietz Group (2025) is included in Attachment A. The site occurs within the County of Lanark and falls under the jurisdiction of the Rideau Valley Conservation Authority (RVCA).

2.1 Compost Site

The Compost Site includes a cleared area (approximately 80 m by 70 m) with a gravel pad (approximately 60 m by 40 m). The gravel pad was installed in 1993 and consists of a 0.3 m thick layer of compacted Granular B gravel overlain by 0.1 m thick layer of compacted stone dust. The Compost Site is accessed by a roadway (gravel and tarmac). The areas surrounding the clearing are forested. The site layout is indicated in Figure 2. Access to the site is controlled by a gate at Highway 43 that is locked when the site is not in operation. A stormwater management pond is located to the immediate northeast of the clearing/pad area.

Cleared areas to the southeast of the Compost Site were previously used for snow storage. This activity ended in 2023.

SCALE

Stomwater pond

Compost
Site
Site
Site
NMV2

MWZ

MWS

MWS

Cemetery

Figure 2: Site Layout

The Smiths Falls Compost Site receives leaf and garden waste from the residents of Smiths Falls and Drummond - North Elmsley Township. Brush and trees are deposited at a cleared area that is approximately 200 m east of the Compost Site (see Figure 2). Leaf and garden waste is handled, stored and processed at the Compost Site. A loader is used to handle the leaf and garden waste. Machinery and equipment is stored, serviced and refueled at offsite locations. The leaf and garden waste are screened onsite by local contractors. The screening process is monitored by Town of Smiths Falls staff to ensure the equipment is in good working condition and is properly maintained. The screened compost is sampled and tested by the Town of Smiths Falls. Approved compost is used by Town of Smiths Falls staff, Town of Smiths Falls Parks department, and residents of Smiths Falls and Drummond - North Elmsley Township.

Excess screened materials are removed from the site and deposited at a local waste transfer station (Glenview Iron and Metal Ltd. (GIM) at 3954 Highway 43 West, Smiths Falls, ON, K7A 5A5).

In Ontario, a compost site is a waste disposal site and requires an Environmental Compliance Approval (ECA) under Ontario Regulation 347.

2.2 Zoning

Zoning at the Compost Site is 'Waste Disposal'. The surrounding lands are zoned 'Institutional'. Hillcrest Cemetery occurs to the south of the Compost Site and is owned by the Town of Smiths Falls. Zoning information for the site and surrounding areas is included in Attachment B (Drummond - North Elmsley Zoning Map).

2.3 Land Use

Land use at the site includes compost handling and processing. There is no agricultural or livestock related use. Surrounding land uses within 700 m of the Compost Site includes:

- North:
 - Forest / undeveloped land
 - Agricultural land (grazing / crops)
 - o Carroll Road
 - o Railway line
 - Wetlands
- East:
 - o Forest / undeveloped land
 - Wetlands
 - Carroll Road
 - Site access roadway
- West:
 - Forest / undeveloped land
 - Wetland
 - Residential properties (north of Highway 43)

- South:
 - o Forest / undeveloped land
 - Wetland
 - Residential properties
 - Hillcrest Cemetery
 - Commercial use (storage locker facility)

2.4 Topography

The site and surrounding areas are undulating. Onsite elevations range from approximately 128.6 m asl (at the top of berms to the north and south of the compost site cleared area) to approximately 123.4 m asl (at the eastern corner of the Compost Site). An analysis of the terrain at the site was conducted using 'laser imaging, detection, and ranging' (LIDAR) data. Digital terrain model data was obtained from the Government of Canada Open Maps website (Government of Canada, 2025). A colour shaded digital terrain model image of the site and surrounding areas is provided in Figure 3.

TCC VAR TO THE PROPERTY OF THE

Figure 3: Topography – Colour shaded LIDAR DTM

2.5 Hydrology

The site occurs in the Edmonds Dam - Rideau River Watershed. Onsite drainage is by infiltration and overland flow to the east towards eastern portion of The Swale Wetland which is a provincial significant wetland (PSW). The Swale Wetland occurs to the east and west of the site. The western portion of The Swale Wetland drains to the east via an unnamed creek that occurs approximately 190 m to the southeast

of the Compost Site. Wetlands and boundaries from the RVCA online geographic information system (GIS) are shown in Figure 4 (RVCA Geoportal, 2025). Areas of unregulated wetland occur at the margins of the PSW. Parts of the unregulated wetlands extend onto the eastern and southern corners of the site. The closest surface water feature is The Swale Wetland. At its closest point, the PSW portion of The Swale Wetland is approximately 35 m south of the southern corner of the site. Regulation setback boundaries associated with The Swale Wetland are all outside of the Compost Site boundary. Drainage directions at the site are indicated in Figure 4.

It is noted that the Compost Site is in an intake protection zone (IPZ-3 with a score of 8 – see Section 5). The intake for the Town of Smiths Falls water supply system is located at the Rideau River at a point that is approximately 2.3 km southeast of the site.



Figure 4: RVCA GeoPortal - Wetlands and Regulation Boundaries

Surface water flow directions of creeks and rivers in the areas surrounding the site are indicated on Figure 5. The Swale Wetland drains to the south towards the Rideau River at a point which is approximately 1.6 km southeast of the site.




Figure 5: Surface Water Drainage

3 METHODOLOGY

3.1 Pre-Consultation

A pre-consultation meeting with RVCA was conducted on July 2, 2025. RLC-HydroG presented the scope of work for the hydrogeological assessment including: a desktop analysis of geoscience and hydrology information; site traverse and observation of surrounding areas and surface water features; groundwater elevation monitoring; survey of well reference elevations; the integration of findings from recent drilling and installation of monitoring wells; and recent groundwater sampling by SLT. RCVA appreciated the opportunity to comment on the hydrogeological assessment and provided clarification regarding the suitability of the site with respect to the Mississippi Rideau Source Protection Plan (2014 as amended) (see Section 5 for further details).

3.2 Background Information

A review of available background information was conducted including:

- MECP water well records.
- MECP permit to take water (PTTW) database.
- Topographic data.
- RVCA online geographic information system (GIS).
- Ontario Geological Survey (OGS) databases.
- The Ontario Source Protection Atlas.
- Previous site investigation reports by SLT including:
- SLT, 2024a. Proposed Snow Dump Site, Smiths Falls, ON, Environmental Soil Assessment, Report No.24C049 (March 19, 2024).
- SLT, 2024b. Smiths Fall Compost Site, Smiths Falls, ON, Environmental Soil Assessment, Report No.24C265 (December 30, 2024).
- SLT, 2025a. Smiths Fall Compost Site, Smiths Falls, ON, Creek Water Assessment, Report No.25C050 (April 4, 2025).
- SLT, 2025b. Property Located at the Smiths Falls Compost Site, 3514 Lanark County Road 43, Smiths Falls, ON, Environmental Assessment, Report 25C163 (July 4, 2025).

3.3 Test Pits

Five (5) shallow test pits (TP1-1 to TP1-5) were excavated to the southeast of the Compost Site by SLT on March 7, 2024 (SLT, 2024a). None of the test pits were excavated at the Compost Site.

Ten (10) test pits (TP2-1 to TP2-10) were excavated by SLT on December 12, 2024 (SLT, 2024b). Most of the test pits were located to the southeast of the Compost Site. One test pit (TP2-9) was located at the Compost Site. The location of TP2-9 is indicated in Figure 2. Soil samples were submitted to the Bureau Veritas Mississauga laboratory for analysis of benzene, toluene, ethylbenzene, and xylenes (BTEX), petroleum hydrocarbons (PHCs, F1 to F4), metals, inorganics, and polycyclic aromatic hydrocarbons (PAHs).

3.4 Boreholes and Monitoring Wells

Seven (7) boreholes were drilled at the site by Eastern Ontario Diamond Drilling under the supervision of SLT on June 24 and 25, 2025. Two boreholes are located at the Compost Site (BH1 and BH7) and one borehole is located between the Compost Site and the nearby unnamed creek (MW2). All boreholes were drilled to refusal. A summary and discussion of the drilling and stratigraphy are included in Section 6.1 of this report. Soil samples were submitted to the Bureau Veritas Mississauga laboratory for analysis of benzene, toluene, ethylbenzene, and xylenes (BTEX), petroleum hydrocarbons (PHCs, F1 to F4), metals (including chromium XI, and mercury), and polycyclic aromatic hydrocarbons (PAHs).


Monitoring wells were installed at all seven (7) borehole locations (MW1 to MW7). Monitoring well locations are indicated in Figure 2. Protective casings were installed at all monitoring wells except for MW5.

3.5 Surface Water Sampling

Four (4) surface water samples (S1 to S4) were collected in locations to the southeast of the Compost Site by Town of Smiths Falls staff on March 25, 2025 (SLT, 2025a). Surface water sample locations are indicated in Figure 6. Findings of the surface water sampling program are presented in Section 6.2 of this report.

The surface water samples were submitted to the Bureau Veritas Mississauga laboratory for analysis of BTEX, PHCs (F1 to F4), metals (including chromium XI, and mercury), and PAHs.

Figure 6: Surface Water Sampling Locations



3.6 Elevation Survey

A survey of monitoring well reference elevations was conducted by RLC-HydroG on June 27, 2025. Ground surface (GS), top of riser (TOR), and top of protective casing (TOC) elevations were surveyed at seven (7) monitoring well locations using a Topcon RL-H5B laser level. Elevation control points s for the survey were established using LIDAR data from the Canada Open Maps website. Three LIDAR control points were used to enhance survey accuracy. Elevation survey data is provided in Attachment C.

3.7 Groundwater Elevation Monitoring

Groundwater elevation monitoring was conducted by RLC-HydroG on June 27, 2025. The depth to water at each monitoring well was measured using an electronic water level tape. Groundwater elevation data is summarized and discussed in Section 5 of this report.

3.8 Groundwater Sampling

SLT conducted groundwater sampling at six monitoring wells (MW1, MW2, MW3, MW4, MW6, and MW7) on June 26, 2025 (SLT, 2025b). Dedicated 5/8 inch (16 mm) tubing and inertial lift foot valves were installed at each monitoring well location. The available water column at MW5 was insufficient for sampling. Each well was purged prior to sampling by removal of three well bore volumes.

Samples were collected in laboratory prepared bottles with preservatives. Samples were delivered to the Bureau Veritas Mississauga laboratory for analysis of BTEX, PHCs (F1 to F4), metals (including chromium XI, and mercury), and PAHs. Overburden groundwater quality results are summarized and discussed in Section 6.3 of this report.

4 GEOLOGY

4.1 Surficial Geology

Surficial geology information from the Ontario Geological Survey (OGS) was obtained from the OGS Earth website (OGS, 2025). The database indicates the site is in an area of till (stone-poor, sandy silt to silty sand) on Paleozoic terrain. The Compost Site occurs in an area of till which extends to the north of the site. This till area is surrounded by organic deposits (peat, muck, marl) associated with the nearby wetlands. Areas of till occur to the south of the site (at the cemetery, and at the storage facility and north of Saumure Circle), and thin drift occurs at Saumure Circle. Surficial geology at the site and surrounding areas is shown in Figure 7.

These descriptions are generally consistent with the findings of the water well records search, test pitting, and recent boreholes by SLT.

Bedrock-drift complax in Patenzois terrain

Till

Griganic Deposits

Fine-loadured glacionarine deposits - all and city, minor set of one deposits - all and city, minor set of one in Patenzois terrain

Till -allone-poor, sendy all to only peat, mack, mark

Patenzois terrain

Griganic Deposits

Till -allone-poor, sendy all to only peat, mack, mark

Patenzois terrain

Till

Griganic Deposits

Figure 7: Surficial Geology

4.2 Terrain Analysis

SCALE

Seven boreholes (BH1 to BH7) were drilled on and near the Compost Site on June 24 and 25, 2025. The locations of the monitoring wells that were installed at each borehole location are indicated in Figure 2. Borehole stratigraphy and observations are summarized in graphical logs provided by SLT (see Attachment D). The boreholes were drilled to provide confirmation of soil conditions in the overburden unit. A summary of borehole information is provided in Table 1.

Table 1: Borehole Stratigraphy and Well Screen Intervals

686 m

BH1	Description					
	Moist, brown, loose SILTY SAND - gravelly and compact					
0.00 to 4.03 m	below 0.9 m / very moist and dense below 2.4 m / most and					
	dense below 3.0 m					
	Auger hole terminated at refusal at 4.03 m					
	A monitoring well was installed (MW1) with well screen from					
	0.91 to 4.03 m bgs					

BH2	Description
0.00 to 0.77 m	TOPSOIL
0.77 to 2.44 m	Moist, brown, dense SILTY SAND with gravel / loose below
0.77 to 2.44 iii	15 m / dense below 2.3 m
	Auger hole terminated at refusal at 2.44 m
	A monitoring well was installed (MW2) with well screen from
	0.91 to 2.44 m bgs

вн3	Description
0.00 to 0.75 m	TOPSOIL
0.75 to 4.37 m	Moist, brown, loose SILTY SAND / becoming compact below 0.8 m with silt zone and gravelly / moist and dense below 2.3 m
	Auger hole terminated at refusal at 4.37 m
	A monitoring well was installed (MW3) with well screen from
	0.91 to 4.37 m bgs

BH4	Description
0.00 to 1.25 m	TOPSOIL
1.25 to 1.98 m	Moist, brown, loose SILT & SAND with clay
1 00 to 4 20 m	Moist, brown, compact SILTY SAND / becoming brown grey,
1.98 to 4.29 m	very moist
	Auger hole terminated at refusal at 4.29 m
	A monitoring well was installed (MW4) with well screen from
	0.91 to 4.29 m bgs

BH5	Description
0.00 to 0.61 m	TOPSOIL with gravel
0.61 to 2.64 m	Moist, black then brown, compact SILTY SAND with gravel /
0.61 (0 2.64 111	black from 1.5 to 1.8 m / very moist and dense below 2.4 m
	Auger hole terminated at refusal at 2.64 m
	A monitoring well was installed (MW5) with well screen from
	0.91 to 2.64 m bgs

вн6	Description
	Moist, black, compact SILT & SAND / with no gravel from 0.8
0.00 to 3.07 m	to 2.1 m / brown and loose below 0.8 m / becoming compact
	with gravel below 2.3 m
	Auger hole terminated at refusal at 3.07 m
	A monitoring well was installed (MW6) with well screen from
	0.91 to 3.07 m bgs

BH7	Description
0.00 to 0.18 m	TOPSOIL
0.18 to 2.36 m	Moist, brown, compact SILTY SAND / with gravel below 1.5 m
	Auger hole terminated at refusal at 2.36 m
	A monitoring well was installed (MW7) with well screen from
	0.91 to 2.36 m bgs

In general, the overburden at the site includes a discontinuous thin layer of topsoil (at BH2, BH3, BH4, BH5, and BH7) underlain by 'silty sand' or 'silt and sand'. Refusal was encountered at depths from 2.36 m (at BH7) to 4.37 m (at BH3) which is assumed to be at fractured bedrock.

4.3 Bedrock Geology

Geological mapping information from the OGS Earth website (OGS, 2024) shows that the site is located in an area where the Lower Ordovician March Formation is the uppermost bedrock unit. The March formation occurs at the bottom of the Beekmantown Group. The bedrock lithology is described as sandstone, dolomitic sandstone, and dolostone. The site is not located in an area of known, inferred, or potential karst.

5 HYDROGEOLOGY

An unconfined water table was encountered in the overburden unit. Drainage and infiltration within the overburden unit is expected to be influenced by topography. Groundwater elevations at seven monitoring (MW1 to MW7) wells are shown in Figure 8. Overburden groundwater flow is inferred to be to the east at the Compost Site, towards unregulated wetlands and The Swale Wetland. To the southeast of the unnamed creek overburden groundwater flow is inferred to be to the northwest toward the unnamed creek. The overburden unit is not used as a water supply aquifer in the area, so the 'first receiving aquifer' is the bedrock aquifer.

On June 27, 2025 the depth to groundwater at the Compost Site monitoring wells was 1.49 m below ground surface (bgs) at MW1 and 0.92 m bgs at MW7. A summary of monitoring well information and groundwater elevations is provided in Table 2.

Table 2: Overburden Groundwater Elevations (June 27, 2025)

	Ground Surface		Top of Riser		27-Jun-25		
Monitoring Well ID	Elevation (m asl)	Stickup (m)	Reference Elevation (m asl)	Well Depth (m bgs)	Depth to Water (m btor)	Water Level Elevation (m asl)	
MW1	125.83	1.02	126.85	5.11	2.51	124.34	
MW2	124.21	0.76	124.97	3.19	2.38	122.59	
MW3	123.70	0.99	124.69	5.12	1.80	122.89	
MW4	123.88	0.96	124.84	5.28	1.97	122.87	
MW5	124.86	1.02	125.88	3.65	3.34	122.54	
MW6	124.86	1.06	125.92	4.13	3.15	122.77	
MW7	124.85	1.13	125.97	3.50	2.04	123.93	
m asl = metres	above sea level						
m btor = metre	s below top of rise	r	m bgs = metres below	2			



Figure 8: Overburden Groundwater Elevations (June 27, 2025) and Flow Directions

The primary water supply aquifer in the area occurs within the horizontally bedded carbonaceous sedimentary bedrock. The bedrock aquifer has water bearing fracture zones (i.e., horizontal bedding plane fractures) that occur between sedimentary layers of bedrock. Permeability is controlled by fractures. The primary porosity (i.e. the 'primary fracture network') is associated with the horizontal bedding plane fractures. A secondary porosity is associated with subvertical fracturing.

On a regional scale recharge to the bedrock aquifer is by infiltration in low lying areas, and discharge is to lakes, rivers, and streams. At the site, the direction of groundwater flow in the upper fractured bedrock unit is assumed to be to the south towards the Rideau River. The direction of groundwater flow in the deep bedrock unit is also assumed to be to the to the south (towards the St Lawrence River).

Information from the Ontario Source Protection Atlas, (MECP, 2025) provides the following information:

- The site is not located within a wellhead protection area (WHPA). It is noted that the Compost Site is approximately 1.3 km southwest of the Kemptville WHPA.
- The site is located within an intake protection zone (IPZ-3 with score of 8).
- The site is not within an issue contributing area (ICA).
- The site is not within a significant groundwater recharge area (SGRA).
- The site is in an area where a highly vulnerable aquifer occurs (HVA with a score of 6).

The Mississippi Rideau Source Water Protection Plan (MVCA and RVCA, 2014 as revised) includes specific requirements associated with the ranking IPZ-3 with score of 8. A map showing the Smiths Falls IPZ is included in Attachment E. RVCA confirmed during pre-consultation that the Mississippi Rideau Source Protection Plan does not prohibit waste disposal site activities within the IPZ unless there is a threat associated with transfer processing of hazardous waste and/or liquid industrial waste.

The Town of Smiths Falls Comprehensive Zoning By-law (2022) indicates that a waste disposal site is prohibited in the 'IPZ-8' zone unless is has been "demonstrated to the satisfaction of the Corporation and/or RMO that the Use does not represent a significant threat to drinking water." The findings of this report show that there is no significant threat to drinking water as impacts to soil and overburden groundwater are limited and localised, and the source of potable groundwater in the area (the bedrock aquifer) is unlikely to be adversely affected by the Compost Site.

5.1 Water Well Records

A review of the MECP Water Well Information System database (WWIS - MECP, 2025) was conducted. 27 water well records were identified within an approximately 700 m radius of the site. Individual well records are provided in Attachment F. The well record locations are shown in Figure 9. Please note that the well record locations are based on MECP database coordinates which are subject to varying degrees of error. A summary of relevant information from the water well records is provided in Table 3.

All of the records are for drilled wells completed in the bedrock aquifer. The wells range in depth from 11 to 50 m and have an average depth of 32 m. 21 of the well records indicate fresh water was encountered. Three of the records indicate the water was not tested.

25 of the well records have indications that an adequate quantity of water (for a four-bedroom residence) is available based on yield testing conducted at the time of drilling (i.e. yields of 18 L/min or greater). Two well records indicate the yield was marginal (<16 L/min). Taken collectively the well record information shows that the drilled wells in the area can provide a suitable water supply.

Figure 9: Water Well Records



A review of the MECP Permit to Take Water (PTTW) database was carried out within a 5 km radius of the site. PTTW information was obtained from the MECP online GIS system (MECP, 2025). One PTTW was identified. PTTW #5545-9FUPKX is held by the Town of Smiths Falls for 'municipal water supply' and permits taking of up to 18,100,000 L/day of surface water. No other water taking permits were identified in the search area.

Table 3: Water Well Records Summary

WELL RECORDS SUMMARY									
Well Record Number	Year Drilled	Depth to Bedrock (m)	Overburden Material	Total Depth (m)	Casing Depth (m)	Depth to Water Bearing Zone(s) (m)	Static Water Level (m)	Recommended Pumping Rate (L/min)	Comments
3501528	1961	5.5	clay	24.4	6.7	12.2 / 23.8	3.0	23	fresh
3501530	1951	1.5	soil	15.5	1.5	15.2	6.1	15	fresh
3501531	1957	6.1	clay and gravel	45.7	7.9	43.3 - 45.7	0.9	23	fresh
3501534	1956	4.9	old well	14.6	1.2	12.2 - 14.6	5.5	23	fresh
3501535	1962	0.6	earth	11.6	4.6	9.1	5.5	18	fresh
3501570	1957	0.0	bedrock at surface	11.3	2.4	10.7	5.5	68	fresh
3501572	1962	0.9	sandy loam	39.3	5.5	39.3	5.5	27	fresh
3502306	1968	0.0	bedrock at surface	38.1	?	38.1	2.1	45	
3502360	1968	0.6	sand and fill	22.9	6.4	22.3	5.5	27	fresh
3502529	1969	0.0	bedrock at surface	21.9	7.9	20.1	2.4	45	fresh
3502774	1970	1.2	soil	26.2	7.6	24.4	7.9	23	
3502775	1970	1.2	soil	22.3	7.6	21.3	9.1	23	fresh
3502776	1970	0.9	soil	18.3	7.6	16.8	7.9	23	fresh
3502849	1971	0.6	soil	25.3	7.6		10.7	23	
3503752	1974	4.3	clay and gravel	41.5	7.6	10.7 / 27.4 / 40.5	0.6	45	fresh
3504372	1976	1.2	soil and stones	48.2	7.6	46.6	6.1	27	fresh
3504376	1976	0.9	fill	41.8	7.6	40.2	4.6	91	fresh
3504601	1976	0.6	sand and fill	30.5	7.6	25.0	5.5	9	fresh
3504698	1977	0.6	soil	37.8	7.6	36.0	9.1	36	fresh
3505025	1978	3.4	clay	43.9	6.7	41.8	3.0	41	fresh
3505040	1978	0.0	bedrock at surface	39.3	6.1	38.1	3.0	23	fresh
3505850	1980	?	old well	34.1	?	33.5	6.1	23	fresh
3506496	1982	0.0	bedrock at surface	34.7	6.1	34.1	6.1	23	fresh
3508204	1987	4.3	clay and stones / gravel	21.3	6.7	19.8	0.6	91	fresh
3509649	1990	8.5	clay and gravel	48.2	10.1	44.2 / 46.3	2.4	55	fresh
3513519	2001	1.5	sandy soil	50.3	6.7	49.1	12.8	455	not tested
3513956	2002	0.6	rocky earth	43.0	6.7	41.5	7.6	227	not tested
7378471	2020	1.5	sand	45.1	6.7	42.1	5.2	91	not tested

5.2 Closest Water Supply Wells

The section of Highway 43 to the west of William Street West is not serviced by a municipal water supply system, so all properties in the study area (~700 m radius around the site) are assumed to be serviced by private drilled wells and individual wastewater treatment systems. All of the well records in the study area indicate drilled wells with casing that extends into bedrock.

The closest water supply well is at 3618 Highway 43 (see Figure 9). A well record corresponding to this location was not identified by the well records search. The configuration of the well is not known. This well is approximately 350-400 m south of the Compost Site and is located to the south of the unnamed creek that connects the western and eastern portions of The Swale Wetland. No significant impacts to the 3618 Highway 43 well are anticipated from activities at the Compost Site. The well is located to the south of a hydraulic boundary (the unnamed creek) with respect to the overburden unit. The direction of

overburden groundwater flow at the 3618 Highway 43 development envelope is assumed to be to the north based on topographic data. The direction of flow in the upper bedrock aquifer is assumed to the to the south towards the Rideau River. The risk of impacts to the 3618 Highway 43 well from the Compost Site is low if the well is a drilled well accessing the bedrock aquifer and has casing that extends several metres into the bedrock unit. Further investigation of the configuration of the 3618 Highway 43 well is warranted.

The next closest water supply well appears to be the well at 114 Saumure Circle (well record #3504601). This well is approximately 560 m west-southwest of the site and is located to the west of the eastern portion of The Swale Wetland. The well has steel casing extending approximately 7 m into the bedrock unit. No impacts to the well are anticipated from activities at the Compost Site.

The closest water supply well to the north of the site (#3508204) is approximately 860 m north of the Compost Site. The well has steel casing extending approximately 2.4 m into the bedrock unit No impacts to the well are anticipated from activities at the Compost Site, and the risk of impacts is considered to be extremely low.

5.3 Potential Sources of Contamination

For compost sites that accept only leaf and yard waste (in paper bags), the risk of contamination is relatively low. Potential contaminants include:

- Nutrients (nitrate, ammonia, phosphorus, and potassium).
- Organics (dissolved organic carbon (DOC)).
- Trace metals (typically iron, manganese, copper, and zinc).
- Debris including plastics, paint chips, pressure-treated wood, dyed mulch (phthalates, phenols, metals, chromated copper arsenate).
- Vehicular traffic and machinery use at the site including a loader, and contractor screening equipment (BTEX, and PHCs). All vehicles and machinery are stored, refueled, and serviced offsite.

The site is used during summer months only, so no road salt use is indicated.

5.4 Hydrogeological Sensitivity

The site is not within an area of 'known, potential, or inferred karst' as determined by the OGS Karst map layer (OGS, 2025).

The water well records show that the overburden thickness within approximately 700 m of the subject property varies from 0 to 8.5 m and has an average thickness of 1.9 m. The overburden material is described in well records as sand, clay, gravel, rocks/stones, and fill.

Recent drilling by SLT at seven (7) boreholes included two boreholes that was drilled at the Compost Site (BH1 and BH7). The boreholes encountered silty sand to a depth of 4.03 m at BH1, and a depth of 2.36 m at BH7.

Based on an overburden thickness of less than 2 m, the subject site is considered to be hydrogeologically sensitive due to the presence of thin permeable soils.

5.5 Water Budget

A water budget describes the relationship between the inputs and outputs of a water system. The water budget is defined as:

$$P = E + I + R + \Delta S$$

Where:

P = total precipitation

E = evaporation

I = infiltration

R = runoff

 ΔS = change in storage.

Precipitation and Temperature

The Drummond Centre Climate Station is located approximately 21 km northwest of the site. Temperature and precipitation 'Normals' for the period from 1981 to 2020 are presented in Figure 10 (Environment Canada, 2025).

The precipitation and temperature patterns affect overburden groundwater elevations and storage, surface water levels and flow, and vegetation growth.




Figure 10: Drummond Centre Temperature and Precipitation (1981 to 2020)

Evaporation and Water Surplus

For this study output from an Environment Canada Engineering Climate Services water balance model was used. The model is described in an Environment Canada information sheet by K. Johnstone and P.Y.T. Louie titled 'Water Balance Tabulations for Canadian Climate Stations. Hydrometeorology Division, Canadian Climate Centre, Atmospheric Environment Service'. The model is based on the methodology of Thornthwaite and Mather (1957) with Canada specific modifications and uses decades of meteorological

data from the nearest weather station up to 2023. The Environment Canada water balance output sheet that was used for this report is provided in Table 4.

Table 4: Environment Canada Climatic Water Balance Model – Drummond Centre

Drummo	Drummond Centre WATER BUDGET MEANS FOR THE PERIOD 1985-2023									DC20492	
DI GIIIIIO	ila cellere		WATE	IN DODG	321 1127	AND TOK		LINIOD .	1505 2	.025	DCZOTJZ
LAT	44.85	WA	TER HO	LDING	CAPAC	ITY	75 MM	HE	AT IND	EX	36.54
LON	G 78.13	LO	WER ZO	NE			45 MM	Α.		• • • • •	1.077
DATE	TEMP (C)	PCPN	RAIN	MELT	PE	AE	DEF	SURP	SNOW	SOTI	ACC P
	()			6 A 14 TO 1							
31- 1	-9.2	69	18	23	1	1	0	41	58	74	304
28- 2	-8.0	57	16	30	1	1	0	44	70	75	360
31- 3	-1.9	61	33	77	8	8	0	102	21	75	420
30- 4	6.1	77	72	26	33	33	0	66	0	74	498
31- 5	13.3	75	75	0	81	81	0	10	0	58	574
30- 6	18.0	95	95	0	114	105	-9	10	0	38	670
31- 7	20.5	90	90	0	133	108	-25	2	0	17	760
31- 8	19.4	85	85	0	116	84	-32	2	0	17	846
30- 9	15.0	89	89	0	76	71	-6	5	0	31	935
31-10	8.4	86	85	1	37	37	0	17	0	62	86
30-11	1.6	74	59	11	11	11	0	47	5	74	160
31-12	-5.3	73	29	19	2	2	0	44	31	75	234
AVE	6.5 TTL	930	746	187	613	542	-72	390			
Drummo	nd Centre		STAN	DARD [DEVIAT:	IONS FO	R THE	PERIOD	1985-	2023	DC20492
DATE	TEMP (C)	PCPN	RAIN	MELT	PE	AE	DEF	SURP	SNOW	SOIL	ACC P
31- 1	3.1	26	23	23	1	1	0	38	31	5	51
28- 2	2.7	21	15	25	1	1	0	33	43	0	59
31- 3	2.4	28	22	32	5	5	0	36	42	0	67
30- 4	1.6	40	39	43	8	8	0	55	0	4	88
31- 5	1.6	30	30	0	10	10	0	17	0	22	98
30- 6	1.2	46	46	0	8	19	20	23	0	31	115
31- 7	1.3	37	37	0	9	30	33	8	0	23	126
31- 8	1.2	45	45	0	8	28	31	9	0	26	140
30- 9	1.4	41	41	0	8	13	12	17	0	27	133
31-10	1.5	34	35	4	7	7	1	26	0	19	34
30-11	1.8	28	27	10	4	4	0	33	9	6	47
31-12	3.1	26	21	15	2	2	0	26	29	0	46

The Environment Canada Water Balance model indicates:

Total annual precipitation (PCPN)
 Potential evaporation (PE)
 Water surplus (SURP)
 390 mm/year

Infiltration and Runoff

An infiltration factor was calculated using MECP guidelines (MOEE, 1995 and MOE, 2008). The infiltration factor is the sum of topographic, soil, and cover (i.e. vegetation) factors. The site occurs within an undulating terrain so a topographic infiltration factor of 0.2 is applicable. Undisturbed soil at the site includes a 2.4 to 4 m layer of silty sand. A soil infiltration factor of 0.4 (open sandy loam) is applicable. 60% of the compost site is cleared and the rest of the site is forested. A cover (i.e. vegetation) infiltration factor of 0.14 was calculated. The combined infiltration factor (topography + soil + cover) is 0.74.

Infiltration is calculated by multiplying the combined infiltration factor by the water surplus. The available infiltration at the site is estimated to be 288.6 mm/year.

As discussed in Section 2.5 (Hydrology) drainage at the site is by infiltration and runoff to the onsite stormwater pond. Runoff typically occurs during the spring melt season and immediately after high rainfall events.

Storage is assumed to be stable. Runoff is calculated by subtracting evapotranspiration and infiltration from total precipitation. The water budget for pre and post-development conditions at the site is provided in Table 5.

Table 5: Water Budget (Pre- and Post Development)

Pre-Development Conditions			Post-Development Conditions				
Site			Site				
Area of Compost Site	15,000	square metres	Area of Compost Site	15,000	square metres		
	1.50	hectares		1.50	hectares		
Precipitation			Precipitation				
Total Precipitation (DRUMMOND CENTRE)	930	mm/year	Total Precipitation (DRUMMOND CENTRE)	930	mm/year		
	0.93	m/year		0.93	m/year		
Volume of precipitation	13,950	cubic metres/year	Volume of precipitation	13,950	cubic metres/year		
Evaporation			Evaporation				
Potential Evapotranspiration (PE)	613.0	mm/yr	Potential Evapotranspiration (PE)	613.0	mm/yr		
	0.613	m/year		0.613	m/year		
	9,195	cubic metres / year		9,195	cubic metres / year		
Water Surplus			Water Surplus				
Water Holding Capacity	75	mm	Water Holding Capacity	75	mm		
EC Water Surplus (DRUMMOND CENTRE - 1985-2023)	390	mm/year	EC Water Surplus (DRUMMOND CENTRE - 1985-2023)	390	mm/year		
Water Surplus	0.39	m/year	Water Surplus	0.39	m/year		
Infiltration			Infiltration				
Infiltration Factors			Infiltration Factors				
Topography	0.2	undulating	Topography	0.2	undulating		
Soil	0.4	sand	Soil	0.2	sand / compacted gravel		
Area of woodland	5,700	square metres	Area of woodland	5,700	square metres		
Area of cleared land	9,300	square metres	Area of cleared land	9,300	square metres		
woodland	0.2	100%	woodland	0.2	40%		
cleared	0.1	0%	cleared	0.1	60%		
Cover	0.20	woodland	Cover	0.14	woodland and cleared		
Total	0.80		Total	0.54			
Factored Water Surplus (water available for infiltration)	312.0	mm/yr	Factored Water Surplus (water available for infiltration)	210.6	mm/yr		
	0.312	m/year		0.211	m/year		
	4,680	cubic metres / year		3,159	cubic metres / year		
Runoff	5.0	mm/yr	Runoff	106.4	mm/yr		
	0.005	m/year		0.106	m/year		
	75	cubic metres / year		1,596	cubic metres / year		

The water budget analysis shows that runoff associated with the pre-development condition is estimated to be approximately 75 m³/year. Runoff associated with current site conditions (post-development) is estimated to be approximately 1,596 m³/year. The change in runoff is due to clearing and installation of compacted fill and accounts for approximately 11% of the water in the system. The net change in runoff is mitigated as most of the runoff from the pad is captured by the onsite stormwater pond, where it infiltrates. Runoff that is not directed to the stormwater pond is to the site's vegetated buffers where infiltration and evapotranspiration occur.

6 IMPACT ASSESSMENT

6.1 Soil Impacts

Five (5) shallow test pits (TP1-1 to TP1-5) were excavated to the southeast of the Compost Site by SLT on March 7, 2024 (SLT, 2024a). None of the test pits were excavated at the Compost Site.

Ten (10) test pits (TP2-1 to TP2-10) were excavated by SLT on December 12, 2024 (SLT, 2024b). Most of the test pits were located to the southeast of the Compost Site. One test pit (TP2-9) was located at the Compost Site. The soil samples were submitted for laboratory analysis of BTEX, PHCs, metals, inorganics, and PAHs.

The analytical results from test pit soil samples were compared to O.Reg. 153, Table 2 site condition standards (commercial land use, coarse textured soil, potable groundwater condition). The analytical results for the sample from TP2-9 were below the selected criteria. The relevant pages from the laboratory certificate of analysis are provided in Attachment G (see SLT, 2024b for the full certificate of analysis). It should be noted that soil exceedances were identified at five of the nine test pit locations to the southeast of the Compost Site (SLT, 2024b). Exceedances are noted for PHCs, metals, and PAH parameters. These exceedances are thought to be associated with previous snow storage activities at the clearings to the southeast of the Compost Site. Snow storage activities ended in 2023.

Seven boreholes (BH1 to BH7) were drilled on June 24 and 25, 2025 (SLT, 2025b). Borehole locations are indicated in Figure 2. Analytical results from borehole soil samples from B H1, BH2, and BH7 are compared to O.Reg 153 Table 2 site condition standards (institutional and commercial land use, coarse texture soil, potable groundwater condition) in Table 6 of this report. The laboratory certificate of analysis is provided in Attachment H. The analytical results for borehole soil samples from BH1, BH2, and BH7 were all below the applicable criteria.

It is noted that soil samples BH1-S1, BH2-S3, and BH7-S13 had detectable concentrations of one or more PAH parameters, and that soil sample BH2-S3 had detectable concentrations of PHC F3 and F4, all at levels that are well below the applicable criteria.

Table 6: Borehole Soil Geochemistry

PARAMETER	Units	Reporting Limit	O.Reg 153 limits (Table 2 * Institutional Land Use)	O.Reg 153 limits (Table 2 ** Commercial Land Use)	BH1-S1 (0.0 to 1.37 m bgs)	BH1-S2 (1.52 to 3.66 m bgs)	BH2-S3 (0.0 to 2.13 m bgs)	BH7-S12 (0.0 to 1.37 m bgs)	BH7-S13 (1.52 to 2.59 m bgs)	BH7-S13 (DUP)
Metals	1				ı			1		
Antimony	ug/g	0.2	7.5	40	<0.2	<0.2	0.25	<0.2	<0.2	<0.2
Arsenic	ug/g	1	18	18	1.9	<1	2.4	1.3	1.8	1.7
Barium	ug/g	0.5	390	670	65	52	62	97	100	100
Beryllium	ug/g	0.2	4	8	0.26	<0.2	0.22	<0.2	0.22	0.21
Boron	ug/g	5	120	120	<5	<5	<5	<5	6.2	5.9
Cadmium	ug/g	0.1	1.2	1.9	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
Chromium	ug/g	1	160	160	11	8.5	12	9.7	10	10
Chromium IV	ug/g	0.18	8	8	<0.18	<0.18	<0.18	<0.18	<0.18	NA
Cobalt	ug/g	0.1	22	80	4.6	3.6	3.1	4.4	4.5	4.5
Copper	ug/g	0.5	140	230	9.7	7.6	12	9.1	12	12
Lead	ug/g	1	120	120	7.7	3.0	17	4.4	13	14
Mercury	ug/g	0.05	0.27	3.9	<0.05	<0.05	0.056	<0.05	<0.05	< 0.05
Molybdenum	ug/g	0.5	6.9	40	<0.5	<0.5	1.4	<0.5	<0.5	<0.5
Nickel	ug/g	0.5	100	270	7.6	5.3	7.5	7.5	8.1	7.9
Selenium	ug/g	0.5	2.4	5.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Silver	ug/g	0.2	20	40	<0.2	<0.2	<0.2	<0.2	<0.2	< 0.2
Thallium	ug/g	0.05	1	3.3	0.074	0.052	0.07	0.065	0.075	0.082
Uranium	ug/g	0.05	23	33	0.45	0.41	0.4	0.45	0.44	0.46
Vanadium	ug/g	5	86	86	24	18	16	10	19	19
Zinc	ug/g	5	340	340	19	11	29	15	32	32
Polycyclic Aromatics Hydr	ocarbon	s (PAHs)			:	•				
Acenaphthene	ug/g	0.005	7.9	21	<0.005	< 0.005	0.007	<0.005	< 0.005	NA
Acenaphthylene	ug/g	0.005	0.15	0.15	<0.005	<0.005	< 0.005	<0.005	< 0.005	NA
Anthracene	ug/g	0.005	0.67	0.67	<0.005	<0.005	0.02	<0.005	<0.005	NA
Benz[a]anthracene	ug/g	0.005	0.5	0.96	<0.005	<0.005	0.053	<0.005	0.0092	NA
Benzo[a]pyrene	ug/g	0.005	0.3	0.3	<0.005	<0.005	0.052	<0.005	0.019	NA
Benzo[b,j]fluoranthene	ug/g	0.005	0.78	0.96	<0.005	<0.005	0.079	<0.005	0.033	NA
Benzo(g,h,i)perylene	ug/g	0.005	6.6	9.6	0.0064	<0.005	0.035	<0.005	0.017	NA
Benzo[k]fluoranthene	ug/g	0.005	0.78	0.96	<0.005	<0.005	0.025	<0.005	0.01	NA
Chrysene	ug/g	0.005	7	9.6	<0.005	<0.005	0.052	<0.005	0.012	NA
Dibenz[a,h]anthracene	ug/g	0.005	0.1	0.1	<0.005	<0.005	0.0091	<0.005	<0.005	NA
Fluoranthene	ug/g	0.005	0.69	9.6	<0.005	<0.005	0.13	<0.005	0.016	NA
Fluorene	ug/g	0.005	62	62	<0.005	<0.005	0.0093	<0.005	<0.005	NA
Indeno[1,2,3-cd]pyrene	ug/g	0.005	0.38	0.76	<0.005	<0.005	0.036	<0.005	<0.005	NA
Methlynaphthalene-1	ug/g	0.005	0.99	30	<0.005	<0.005	0.0084	<0.005	<0.005	NA
Methlynaphthalene-2	ug/g	0.005	0.99	30	<0.005	<0.005	0.0092	<0.005	<0.005	NA
Naphthalene	ug/g	0.005	0.6	9.6	<0.005	<0.005	0.011	<0.005	<0.005	NA
Phenanthrene	ug/g	0.005	6.2	12	<0.005	<0.005	0.13	<0.005	<0.005	NA
Pyrene	ug/g	0.005	78	96	<0.005	<0.005	0.095	<0.005	0.012	NA
Benzene, Toluene, Ethylb	•				0.000	0.000	3.000	0.000	3.012	
Benzene	ug/g	0.02	0.21	0.32	<0.02	<0.02	<0.02	<0.02	<0.02	NA
Toluene	ug/g	0.02	2.3	6.4	<0.02	<0.02	<0.02	<0.02	<0.02	NA
Ethylbenzene	ug/g	0.02	1.1	1.1	<0.02	<0.02	<0.02	<0.02	<0.02	NA
Xylenes	ug/g	0.02	3.1	26	<0.02	<0.02	<0.02	<0.02	<0.02	NA
Petroleum Hydrocarbons		0.04	5.1		\U.U4	\U.U4	₹0.04	\U.U4	\U.U4	11/7
F1	1	10	55	55	<10	<10	<10	<10	<10	NA
F2	ug/g	7	98		<7	<7	<7	<7	<7	
	ug/g			230						NA NA
F3	ug/g	50	300	1700	<50	<50	87	<50	<50	NA
F4	ug/g	50	2800	3300	<50	<50	30	<50	<50	NA
Bold and shaded = result exceed Ontario Regulation 153/04 (as a		neards of City C	ndition Call Control	Mater and Co. Proc. 1	Ctondo-d- f : !!	Under Dark 2011	of the Fault :	stal Dectarti:	t /inctituation - 11	luco*
Ontario Regulation 153/04 (as ai commercial land use**, coarse t				water and Sediment S	otanuarus for Use	onuer Part XV.1 (or the Environmer	itai Protection Ac	ı (ırısırıudonai iand	use-,
NA = not analysed		NC - no criteria	,		ND = non-detect	able		bgs = below gro	und surface	

6.2 Surface Water Impacts

Surface water features on or near the subject site include:

- Unregulated wetlands onsite and bordering nearby PSW.
- A stormwater pond at the site that receives surface water runoff from the compost site clearing /pad area.
- An unnamed creek that occurs approximately 190 m to the south of the site.

The site has been operating since 1993. The surface water regime in the vicinity of the site is stable and no changes have occurred since 1992, and no significant changes are anticipated in the future.

Table 7: Surface Water Geochemistry (March 25, 2025)

PARAMETER	Units	Reporting Limit	PWQO	S1	S1 (DUP)	S2	S3	S4	
Metals									
Antimony	ug/L	0.5	20	<0.5	<0.5	<0.5	<0.5	<0.5	
Arsenic	ug/L	1	100	<1	<1	<1	<1	<1	
Barium	ug/L	2	NC	47	48	51	55	41	
Beryllium	ug/L	0.4	11/1100	<0.4	< 0.4	< 0.4	< 0.4	< 0.4	
Boron	ug/L	10	200	<10	<10	<10	<10	<10	
Cadmium	ug/L	0.09	200	< 0.09	< 0.09	< 0.09	< 0.09	< 0.09	
Chromium	ug/L	5	8.9	<5	<5	<5	<5	<5	
Chromium IV	ug/L	0.5	1	<0.5	<0.5	<0.5	<0.5	<0.5	
Cobalt	ug/L	0.5	0.9	<0.5	<0.5	< 0.5	<0.5	<0.5	
Copper	ug/L	0.9	5	1.0	1.0	1.1	<0.9	<0.9	
Lead	ug/L	0.5	1/3/5	<0.5	<0.5	<0.5	<0.5	<0.5	
Mercury	ug/L	0.1	0.2	<0.1	NA	< 0.1	<0.1	<0.1	
Molybdenum	ug/L	0.5	40	<0.5	<0.5	<0.5	<0.5	<0.5	
Nickel	ug/L	1	25	<1	<1	<1	<1	<1	
Selenium	ug/L	2	100	<2	<2	<2	<2	<2	
Silver	ug/L	0.09	0.1	< 0.09	< 0.09	< 0.09	< 0.09	< 0.09	
Sodium	ug/L	100	NC	8100	8000	7300	7500	23000	
Thallium	ug/L	0.05	0.3	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	
Uranium	ug/L	0.1	5	0.14	0.14	0.17	0.16	0.16	
Vanadium	ug/L	0.5	6	<0.5	<0.5	< 0.5	<0.5	<0.5	
Zinc	ug/L	5	30	8.8	13	8.2	6.3	5.5	
Polycyclic Aroma	tics Hydro	carbons (PAH	s)						
18 parameters te	sted as pe	r O.Reg. 153	various	ND	NA	ND	ND	ND	
Benzene, Toluene	e, Ethylber	nzene, and Xy	lenes (BTEX)						
BTEX parameters	ug/L	various	various	ND	NA	ND	ND	ND	
Petroleum Hydro	carbons (F	PHCs)							
F1 to F4	ug/L	various	various	ND	NA	ND	ND	ND	
Bold and shaded = res	ult exceeds I	imit							
Provincial Water Qual	ity Objectives	(PWQO), MOEE	, 1994. Water M	anagement, Po	olicies, Guideline	es, Provincial V	ater Quality O	bjectives.	
NA = not analysed	NC - no criteria ND = non-detectable								

Surface water sampling was conducted on March 25, 2025 (SLT, 2025a). Four (4) surface water samples (S1 to S4) were collected in locations to the southeast of the Compost Site by Town of Smiths Falls staff. Surface water sample locations are indicated in Figure 2. Analytical results from the surface water samples are compared to the applicable surface water quality standards (Ontario Provincial Water Quality Objectives (PWQO)) in Table 7 of this report. The laboratory certificate of analysis is provided in Attachment I. The analytical results for all surface water samples were below the PWQO limits. The results for PAHs and PHCs were all non-detectable.

It is noted that low level concentrations of copper, uranium and zinc were detected in one or more of the samples, all at levels that are well below the PWQO limits. Barium and sodium were also detected at low concentrations in all four samples.

6.3 Groundwater Impacts

SLT conducted groundwater sampling at six monitoring wells (MW1, MW2, MW3, MW4, MW6, and MW7) on June 26, 2025. Samples were submitted for laboratory analysis of BTEX, PHCs (F1 to F4), metals (including chromium XI, and mercury), and PAHs.

Analytical results from the groundwater samples from MW1, MW2, and MW7 are compared to the limits provided in O.Reg. 153, Table 2 site condition standards (all types of property use, coarse textures soils) in Table 8 of this report. The laboratory certificate of analysis is provided in Attachment J. The analytical results for groundwater samples from MW1, MW2, and MW7 were all below the applicable Table 2 Site Condition Standards.

It is noted that the groundwater samples from MW1 and MW7 had detectable concentrations of one or more PAH parameters, and that the sample from MW2 had detectable concentrations of benzene and toluene, all at levels that are well below the applicable Table 2 Site Condition Standards.

The results were also compared to the Ontario Drinking Water Standards (MECP – ODWS, 2003, as amended) in Table 8 of this report. There were no exceedances of the ODWS health limits. The concentration of sodium at MW2 exceeded the ODWSOG (MECP, 2003, as amended) aesthetic objective (AO) limit.

Table 8: Groundwater Geochemistry (June 26, 2025)

PARAMETER	Units	Reporting Limit	O.Reg 153 limits (Table 2 *)	ODWS***	MW1	MW2	MW7	
				Sample Date		26-Jun-25		
Metals				, ,				
Antimony	ug/L	0.5	6	6	<0.5	<0.5	<0.5	
Arsenic	ug/L	1	25	10	<1	1.9	<1	
Barium	ug/L	2	1,000	1,000	150	350	340	
Beryllium	ug/L	0.4	4	NC	<0.4	<0.4	<0.4	
Boron	ug/L	10	5,000	5,000	21	56	40	
Cadmium	ug/L	0.09	2.7	5	<0.09	<0.09	< 0.09	
Chromium	ug/L	5	50	50	<5	<5	<5	
Chromium IV	ug/L	0.5	25	NC	<0.5	<0.5	<0.5	
Cobalt	ug/L	0.5	3.8	NC	2.4	2.2	<0.5	
Copper	ug/L	0.9	87	1,000 ^{AO}	<0.9	3.4	3.3	
Lead	ug/L	0.5	10	10	<0.5	<0.5	<0.5	
Mercury	ug/L	0.1	0.29	1	<0.1	<0.1	<0.1	
Molybdenum	ug/L	0.5	70	NC	2.6	13	2	
Nickel	ug/L	1	100	NC	2.4	3.2	<1	
Selenium	ug/L	2	10	50	<2	<2	<2	
Silver	ug/L	0.09	1.5	NC	<0.09	<0.09	<0.09	
Sodium	ug/L	100	NC	200,000 ^{AO}	17,000	300,000	7,800	
Thallium	ug/L	0.05	2	NC	<0.05	<0.05	<0.05	
Uranium	ug/L	0.1	20	20	0.7	2.6	2.8	
Vanadium	ug/L	0.5	6.2	NC	<0.5	4.2	0.59	
Zinc	ug/L	5	1,100	5,000 ^{AO}	<5	<5	6.1	
Polycyclic Aroma	tics Hydro	carbons (PAI	ls)	<u> </u>				
Fluoranthene	ug/L	0.05	0.41	NC	0.052	ND	ND	
Phenanthrene	ug/L	0.03	1	NC	0.18	ND	0.064	
Pyrene	ug/L	0.05	4.1	NC	0.073	ND	ND	
15 other PAH par	remeters	various	various	various	ND	ND	ND	
Benzene, Toluen	e, Ethylbe	nzene, and X	ylenes (BTEX)					
Benzene	ug/L	0.2	5	1	<0.2	0.40	<0.2	
Toluene	ug/L	0.2	24	60	<0.2	0.33	<0.2	
Ethylbenzene	ug/L	0.2	2.4	140	<0.2	<0.2	<0.2	
Xylenes	ug/L	0.4	300	90	<0.4	<0.4	<0.4	
Petroleum Hydro		PHCs)						
F1 to F4	ug/L	various	various	NC	ND	ND	ND	
Bold and shaded = res	sult exceeds	health limit						
Bold = result exceeds	s ODWSOG a	esthetic obcetive	e (AO) limit	AO = Aesthetic Objec	tive			
Protection Act (Table	2, all types of	f property use, co						
* Ontario Regulation : Protection Act (Table *** Ontario Ministry (153/04 (as ar 2, all types of of Environmen	mended), Record f property use, co nt Conservation a	s of Site Condition. Soil, G	round Water and Sedim	nent Standards for U			

^{***} Ontario Ministry of Environment Conservation and Parks (MECP) (MOE, 2003, Revised 2006 as amended). Technical Support Document for Ontario Drinking Water Standards, Objectives and Guidelines (ODWSOG) as amended/revised under Ontario Regulation 169/03, 2021.

NA = not analysed NC - no criteria ND = non-detectable

6.4 Natural Functions of the Ecosystem

The Compost Site is located in a forested area between two portions of the provincially significant Swale Wetland. Unregulated wetlands extend onto the edges of the Compost Site in two places.

Composting activities have the potential to affect adjacent ecological features through the leaching of nutrients and organic compounds. Elevated concentrations of nutrients (typically nitrate, ammonia, phosphorus, and potassium) and biochemical oxygen demand (BOD) are expected in surface water and/or shallow groundwater. Leaching of trace metals, phthalates, and phenolic compounds may also occur, though these are typically of low concentrations in leaf and yard waste.

Analytical results from one test pit soil sample (TP2-9) collected at the Compost Site did not exceed the applicable Table 2 site condition standards. Groundwater sample analytical results from monitoring wells located on and near the Compost Site (MW1, MW2, and MW7) did not exceed the applicable Table 2 site condition standards. These results suggest that impacts to soil and groundwater are minimal under current operating conditions.

The PSW setbacks are intended to provide a protective buffer to preserve the natural functions of adjacent wetland ecosystems. The Compost Site is located outside of the regulated PSW setback areas, as shown on Figure 4, and all composting activities are confined to a topographically elevated area away from the mapped wetland features.

Stormwater generated on the site is directed to an on-site stormwater management pond, which facilitates sedimentation and infiltration. The site has been in operation since 1993. Based on site observations and aerial imagery, there is no evidence of ecological impacts to the downgradient PSW such as algal blooms, or stressed vegetation.

Given the current site configuration, existing management practices, and monitoring results, there is no indication that the natural function of the adjacent PSW has been adversely affected by site operations. Adverse effects are unlikely to occur in the future if the site continues to be carefully managed in accordance with best practices.

6.5 Mitigation

The following mitigation measures have been identified:

- Supervision of onsite equipment use. Leaf and garden waste is screened onsite by local contractors. The screening process is monitored by Town of Smiths Falls staff to ensure the equipment is in good working condition and is properly maintained.
- This risk of contamination from vehicular traffic and heavy equipment (a loader operated by the Town of Smiths Falls, and contractor screening equipment) can be mitigated by implementation of a site specific spill response plan (see Attachment K).
- Diligent site management and operational controls will help to prevent detrimental impacts.

- Monitoring of surface water quality at the established surface water stations will identify any significant impacts if they do occur. Surface water monitoring details are provided in Section 7.1.
- Monitoring of groundwater at selected monitoring wells will identify any significant impacts if they do occur. Groundwater monitoring details are provided in Section 7.2.

7 MONITORING PLAN

The following is a summary of the locations, monitoring requirements, analytical requirements, and reporting schedule.

The methods and protocols for sampling, analysis and recording shall conform, in order of precedence, to the methods and protocols specified in:

- MECP 'Protocol for the Sampling and Analysis of Industrial/Municipal Wastewater' (August 1994), ISBN 0-7778-18880-9, as amended.
- The publication 'Standard methods for the Examination of Water and Wastewater' (22nd edition) as amended.

7.1 Surface Water Monitoring

Surface water monitoring stations

- S1
- S2
- S3
- S4

Surface water monitoring

- At all locations conduct surface water monitoring including measurement of:
- Field parameters (pH, conductivity, TDS, and temperature) to be measured using a calibrated multimeter instrument.
- Depth and width of channel.
- Flow condition (low / moderate / high)

Surface water sampling

- Surface water samples are to be collected at each surface water station (S1, S2, S3, and S4).
- Surface water samples to be collected according to standard industry practices by suitably trained personnel (i.e. nitrile gloves, laboratory supplied bottles with preservatives, temperature control, samples submitted within holding times, and strict chain-of-custody protocols).
- Laboratory analysis of surface water samples
- Samples to be submitted to a CALA registered environmental laboratory under strict chain-of custody protocols.

- Samples to be submitted for laboratory analysis of:
 - Hardness
 - Alkalinity as CaCO3
 - Electrical conductivity
 - Ha o
 - Total oil and grease
 - o Total ammonia
 - (un-ionized ammonia to be calculated according to Provincial Water Quality Objectives (PWQO) methodology (MOEE, 1994).
 - Nitrate
 - Nitrite
 - o Total Phosphorus
 - o Potassium
 - o Iron
 - Manganese
 - o Copper
 - o Zinc
 - o DOC
 - Phthalates
 - o Phenols

Schedule

Surface water monitoring and sampling to be conducted once per year in July.

7.2 Groundwater Monitoring

Groundwater monitoring network

- MW1
- MW2
- MW7

Groundwater monitoring

- At all locations conduct groundwater elevation monitoring including measurement of:
- The distance from reference point (top of riser) to water in each well using an electronic water level tape.
- Field parameters (pH, conductivity, TDS, and temperature) to be measured using a calibrated multimeter instrument.

Groundwater sampling

- Groundwater samples are to be collected at each monitoring well.
- Groundwater samples to be collected according to standard industry practices by suitably trained personnel (i.e. nitrile gloves, laboratory supplied bottles with preservatives, temperature control, samples submitted within holding times).

- Field parameters (pH, electrical conductivity, temperature) to be measured using a calibrated multimeter instrument at the time of sampling.
- Laboratory analysis of groundwater samples
- Samples to be submitted to a Canadian Association For Laboratory Accreditation (CALA) registered environmental laboratory under chain-of custody protocols.
- Samples to be submitted for analysis of:
 - Hardness
 - Alkalinity as CaCO3
 - Electrical conductivity
 - Hq o
 - Chloride
 - Nitrate
 - Nitrite
 - o Total Phosphorus
 - Potassium
 - o Iron
 - Manganese
 - o Copper
 - o Zinc
 - o DOC
 - Phthalates
 - Phenols
 - o Sodium
 - o Total oil and grease

Schedule

 Groundwater monitoring and sampling to be conducted at all monitoring wells once per year in July.

7.3 Reporting

An annual water monitoring report to be prepared by a suitable qualified person (environmental geoscientist with P.Geo. or P.Eng. qualification). The annual water monitoring report should include:

- A description of all surface water and groundwater monitoring locations.
- Methodology.
- Results (tabulated and plotted) including a comparison of analytical results with applicable limits.
- Discussion of results.
- Conclusions and recommendations.

Schedule

The annual monitoring report to be submitted to MECP before November 30 of each year.

8 CONTINGENCY PLAN

8.1 Trigger Mechanisms

The following trigger mechanisms will be used:

- A complaint is received.
- Surface water analytical results exceeding PWQO limits.
- Groundwater analytical results at MW1, MW2, or MW7 exceeding the applicable site conditions standards (O.Reg. 153 Table 2 site condition standards, commercial land use, coarse texture soil, for a potable groundwater condition.
- Any indication that the natural environment is being degraded.

The following contingency actions will be taken if triggered:

- If any complaints are received, or if any adverse effects are identified an investigation regarding adverse effects will be conducted immediately.
- The Town of Smiths Falls will retain a qualified person (Ontario licensed environmental geoscientist/engineer with QP_{ESA} designation) to define and supervise the investigation. The qualified person will provide an action plan to ensure safe management as soon as possible.
- If significant impacts to the environment and/or potable water users is identified, the MECP will be informed.
- If a neighbouring property owner within 500 m of the site reports a well water quality issue, the
 Town of Smiths Falls will investigate the nature of the concern and determine if it is potentially
 associated with the Compost Site. If the Compost Site is confirmed to be the probable cause of
 the issue the Town of Smiths Falls will inform MECP, investigate the issue, and a provide an action
 plan for safe management.

9 CONCLUSIONS

- The location of the Compost Site is suitable for use as a compost facility and is compliant with source protection plan, and Zoning By-law requirements.
- There is no significant threat to drinking water as existing impacts to soil and overburden groundwater are limited and localised. The primary source of potable groundwater in the area is the bedrock aquifer, which is unlikely to be adversely affected by the Compost Site.
- Investigations at the site and surrounding areas (test pitting, drilling, monitoring wells, and surface
 water sampling) are generally sufficient to characterise potential impacts associated with
 activities at the Compost Site.
- The site has been active since 1993 and has not caused any significant impacts. The local surface water regime is stable and is unlikely to change.
- The closest water supply wells are unlikely to adversely affected by the Compost Site.

RLC-HydroG

• There is no indication that the natural function of the adjacent PSW has been adversely affected by Compost Site operations. Adverse effects are unlikely to occur in the future if the site continues to be carefully managed in accordance with best practices.

10 RECOMMENDATIONS

- A spill response plan (see Attachment K) for the Compost Site should be implemented.
- The monitoring plan presented in this report (Section 7) should be conducted on an annual basis.
- The contingency plan presented in this report (Section 8) should be used to ensure appropriate actions will be taken if any indications of adverse effects are identified.
- Further information should be obtained regarding the closest water supply well at 3618 Highway 43. The well owner should be interviewed, and the depth of the well should be determined (if possible). The well should be inspected to assess general compliance with Ontario Regulation 903 construction requirements. If the well is not a drilled bedrock well with casing that extends into the bedrock unit, the well should be sampled, and the sample should be submitted for analysis if the list of parameters identified in Section 7.2 of this report.

In summary, it is RLC-HydroG's professional opinion that the site is suitable for use as a Compost Site. The hydrogeological recommendations contained in this report, if followed, will ensure that operation of the Compost Site will be safe and sustainable in the long term, and will not cause any adverse effects to the environment.

RLC-HydroG – Hydrogeological Services

Russell Laird Chown, P.Geo. $\mathsf{QP}_{\mathsf{ESA}}$

Senior Hydrogeologist

Filename: SLT-TOSF - Smiths Falls Compost Site - FINAL - 8jul25

11 LIMITING CONDITIONS

This report has been prepared by **RLC-HydroG** exclusively for the use of the named clients: **St. Lawrence Testing & Inspection Co. Ltd.** and the **Town of Smiths Falls**. No other party may rely on or reproduce this report, in whole or in part, without the prior written consent of RLC-HydroG. RLC-HydroG will consider reasonable requests to authorize use by third parties; however, any unauthorized use of this report is at the sole risk of the user.

This report presents the site conditions and observations as documented by RLC-HydroG during the site investigation and is based on information available at the time of the work. The conclusions and recommendations expressed herein are professional opinions based on the scope of work, project objectives, available data, and the limiting conditions stated in this report.

RLC-HydroG has relied in good faith on information provided by third parties and assumes such information to be accurate and complete. This information has not been independently verified unless specifically stated. RLC-HydroG accepts no liability for errors, omissions, or inaccuracies resulting from inaccurate or incomplete information provided by others.

The findings of this report apply only to the site conditions observed at the specific locations and on the dates noted. Unless otherwise indicated, they should not be extrapolated to other areas, times, or environmental conditions beyond the scope of investigation. Similarly, conclusions related to analytical testing are limited to the parameters analyzed by the laboratories retained for this project.

This report does not constitute legal advice and should not be interpreted as such. RLC-HydroG offers no assurance or certification of compliance with environmental laws, regulations, or policies, which remain the responsibility of the client or regulatory authorities.


Any use of this report by parties other than the client is entirely at their own risk. RLC-HydroG disclaims any responsibility or liability for damages or losses incurred by third parties as a result of decisions made or actions taken based on this report.

12 REFERENCES

- Callon Dietz Group, 2025. **Plan of Survey**.
- Corporation of the Town of Smiths Falls (2022). Comprehensive Zoning By-law (August 22, 2022).
- Environment Canada, 2023. Canadian Climate Normals and Averages.
- Government of Canada, 2025. Open Maps, High Resolution Digital Elevation Model (HRDEM),
 CanElevation Series. Digital terrain model (DTM) LIDAR data acquired in 2022.
- Government of Ontario, 2004, as amended. Ontario Regulation 153/04, Records of Site Condition. Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act.
- Government of Ontario, 1990. R.R.O. 1990, as amended, Ontario Regulation 347: General Waste Management.
- Rideau Valley Conservation Authority (RVCA), 2025. Online Geographic Information System (GIS).
- Mississippi Valley Conservation Authority and Rideau Valley Conservation Authority (MVCA and RVCA), 2014 as revised. Mississippi Rideau Source Protection Plan.
- Ontario GeoHub, 2023. Ontario Watershed Boundaries (OWB) GIS portal.
- Ontario Geological Survey (OGS), OGS Earth website, 2025. Various authors. Surficial Geology, Paleozoic Geology, and Karst layers.
- Ontario Ministry of Environment, 2013. **Checklist for Technical Requirements** for a Complete Environmental Compliance Approval Submission.
- Ontario Ministry of Environment Conservation and Parks (MECP), 2025. Water Well Information System (WWIS).
- Ontario Ministry of Environment Conservation and Parks (MECP), 2015. Water Supply Wells: Requirements and Best Practices.
- Ontario Ministry of Environment Conservation and Parks (MECP), 2025. Permits to Take Water (PTTW) online GIS.
- Ontario Ministry of Environment Conservation and Parks (MECP), 2025. **Ontario Source Protection Information Atlas**.
- Ontario Ministry of Environment Conservation and Parks (MECP) (MOE, 2003, Revised 2006 as amended). Technical Support Document for Ontario Drinking Water Standards, Objectives and Guidelines (ODWSOG) as amended/revised under Ontario Regulation 169/03, 2021.
- Ontario Ministry of Environment and Energy (MOEE), 1994. Provincial Water Quality Objectives (PWQO), Water Management, Policies, Guidelines, Provincial Water Quality Objectives (July, 1994).
- Ontario Ministry of Environment and Energy (MOEE), 1995. Hydrogeological Technical Information Requirements for Land Development Applications.
- Ontario Ministry of Environment (MOE), 2008. Design Guidelines for Sewage Works.
- Ontario Safe Drinking Water Act, 2002 as amended. S.O. 2002, c. 32

- Ontario Water Resources Act, 1990. Revised Statute of Ontario (R.S.O.), Ontario Regulation 903, 1990, Wells.
- St. Lawrence Testing & Inspection Co. Ltd. (SLT), 2024a. Proposed Snow Dump Site, Smiths Falls, ON, Environmental Soil Assessment, Report No.24C049 (March 19, 2024).
- St. Lawrence Testing & Inspection Co. Ltd. (SLT), 2024b. **Smiths Fall Compost Site**, Smiths Falls, ON, **Environmental Soil Assessment**, Report No.24C265 (December 30, 2024).
- St. Lawrence Testing & Inspection Co. Ltd. (SLT), 2025a. Smiths Fall Compost Site, Smiths Falls, ON, Creek Water Assessment, Report No.25C050 (April 4, 2025).
- St. Lawrence Testing & Inspection Co. Ltd. (SLT), 2025b. Property Located at the Smiths Falls Compost Site, 3514 Lanark County Road 43, Smiths Falls, ON, Environmental Assessment, Report 25C163 (July 4, 2025).
- Thornthwaite, and Mather, 1957: Instructions and tables for computing potential evaporation and the water balance. Publications in Climatology, Volume 10(3), Laboratory of Climatology.

ATTACHMENT A Legal Survey



PLAN OF SURVEY OF PART OF LOTS 1 AND 2 CONCESSION 6

IN THE GEOGRAPHIC TOWNSHIP OF NORTH ELMSLEY TOWNSHIP OF DRUMMOND/NORTH ELMSLEY

COUNTY OF LÁNARK SCALE 1:750

(SCALE IN METRES)

GEORGE N. BRACKEN ONTARIO LAND SURVEYOR

LEGEND:

DENOTES SURVEY MONUMENT SET SURVEY MONUMENT FOUND

SIB STANDARD IRON BAR SSIB SHORT STANDARD IRON BAR IRON BAR

RIB ROUND IRON BAR CC CUT CROSS

OU ORIGIN UNKNOWN ORP OBSERVED REFERENCE POINT

WIT WITNESS MEASURED SET

1054 GEORGE BRACKEN O.L.S.

BEARING NOTE

KEY PLAN

P.I.N. 05235

2163(LT)

BEARINGS ARE UTM GRID, DERIVED FROM OBSERVED REFERENCE POINTS A & B, BY REAL TIME NETWORK (RTN) OBSERVATIONS, UTM ZONE 18, CENTRAL MERIDIAN 75'00'00"W, NAD83 (CSRS)

DISTANCES ARE GROUND AND CAN BE CONVERTED TO GRID BY MULTIPLYING BY THE COMBINED SCALE FACTOR OF 0.999669

DISTANCES AND COORDINATES SHOWN ON THIS PLAN ARE IN METRES AND CAN BE CONVERTED TO FEET BY DIVIDING BY 0.3048

SURVEYOR'S CERTIFICATE

I CERTIFY THAT:

- (1) THIS SURVEY AND PLAN ARE CORRECT AND IN ACCORDANCE WITH THE SURVEYS ACT, THE SURVEYORS ACT AND LAND TITLES ACT, AND THE REGULATIONS MADE UNDER THEM.
- (2) THE SURVEY WAS COMPLETED ON THE 17TH DAY OF APRIL, 2025

GEORGE N. BRACKEN

9001


THIS PLAN OF SURVEY RELATES TO AOLS PLAN SUBMISSION FORM NUMBER V-96306

Callon Dietz INCORPORATED

ONTARIO LAND SURVEYORS CARLETON PLACE LONDON NORTH BAY

requests@callondietz.com callondietz com DRAWN BY: RW FILE No: 25-27301 PLAN No: X-4027

ATTACHMENT B
Zoning Map



ATTACHMENT C
Elevation Survey

•	alls Compost Site - 27jun25			
Bench Mark				masl
CONTROL POINT A	Elev at centre of roadway in front of white-blue shed at compost site	f	LIDAR ->	126.58
Setup level	STN-0	me	easurement	masl
	Elevation of laser level (1st setup)		1.344	127.924
MW7	G	c	3.078	124.846
IVIVV /				
	TO		5 cm above TOR	126.022
	TO		1.952	125.972
MW1		S	2.098	125.826
	ТО		1.002	126.922
	ТО	R	1.077	126.847
Move level				
	BS to BH1-TOR (***above***		0.196	126.651
	FS to TP-	A	1.901	124.750
Move level				
	BS to TP-A		0.836	125.586
MW3			1.887	123.699
	TO		0.852	124.734
	ТО	R	0.898	124.688
Move level	STN-C			
	BS to MW3-TOR		1.037	125.725
MW2	G	S	1.514	124.211
	TO	С	0.682	125.043
	ТО	R	0.753	124.972
Move level	STN-D			
	BS to MW3-TOR		1.027	125.715
	FS to TP-B		1.311	124.404
CONTROL POINT B	Centre of bridge		1.782	123.933
Move level				
	BS to TP-B		1.920	126.324
MW4		S	2.444	123.880
	TO		1.445	124.879
	TO		1.487	124.837
MW5		S	1.464	124.860
IVIVV		C no casing	1.404	124.000
	TO		0.443	125.881
	FS to TP-C	<u>κ</u>	1.234	125.090
Mayalayal			1.254	125.090
Move level			0.000	125.986
	BS to TP-C		0.896	
and anoth TD	BS to MW5-TOR		0.104	125.882
need another TP	FS to TP-D		1.372	124.614
Move level			. =	100.00=
	BS to TP-D		1.711	126.325
MW6			1.466	124.859
	ТО		0.336	125.989
	ТО	R	0.403	125.922
CONTROL POINT C	Centre of tarmac road adjacent to		1.876	124.449
	centre of access to MW6			
	ID		GS	TOR
	MW1		125.83	126.85
	MW2		124.21	124.97
	MW3		123.70	124.69
	MW4		123.88	124.84
		1		
	MW5		124.86	125.88
	MW5 MW6		124.86 124.86	125.88 125.92

ATTACHMENT D
SLT Borehole Logs

	C,		St. Lawrence & Inspection (Tes Co.	stin Ltc	g .k		(OFF	FIC.	E B	C)	R	E	ŀ	-1	O														
١,	e len	т Т	own of Smiths Falls																RE BO	PO RE	RT HO	NO LE	NC		<u>25</u> 0	<u>ا ز</u>	<u>6.</u>	<u> </u>			_	
١.			Compost Site																CA	SII	٧G		Η	F	Αı	Ja	eı	^				ı
	DATE	OF BO	RING June 24, 2025	[DATE OF	WL R	EADIN	G	June	26,	2025	<u>;</u>						_	DA	TU	Μ.						_		_		_	_
			SOIL PROFILE				S	AMPI	LES													_								_		
	NO			101	3 NS	NOI		83	ERY	.UE	LABORATORY TESTS PERFORMED			1	LA	В				T	ES	T					R	ES	ULT	S		
DEPTH	ELEVATION	DEPTH	SOIL DESCRIPTION	STRAT. PLOT	WATER CONDITIONS	CONDITION	ΤΥΡΕ	NUMBER	RECOVERY	N - VALUE	LABO TE PERF					W	ΑT		COI VP	NTE	NT		AT W	TER	BE		LIM WL					
_				<u> </u>										DY	NA	MIC	PE	NET	RAT	ION	TES	ST &	BLO	ws	PEF	FO	OT.	k	C			\dashv
0-			G'11 G 1		-	/	 -				<u> </u>	0	П	П		Π	20	Ή	П	Π	П	1	î	П	П		ı	î	П	Π	ПÎ	0
			Silty Sand Brown, moist, loose,			$ \setminus $																										H
-			becoming gravelly and compact below 0.9 m,			X	SS	1	30	6		-																				H
			and very moist and									T					П				T		П						\prod	\prod		A
			dense below 2.4 m and moist and dense																													Н
1_			below 3.0 m			\mathbb{W}	SS	2	40	17		-	\parallel	4	4	\parallel	H	₩	\parallel	igwedge	+	4	\Vdash	-	\prod	1	\parallel	Щ	H	$\!$	Ш	A
						lΛ	00	_	40	17																						A
				ŀ		\sim												$\ $														П
						K 7						Ħ	H		\parallel	$\dagger \dagger$	Ħ	$\dagger \dagger$	\dagger	$\dagger \dagger$	\parallel	Н	\dagger	\dagger	Ħ	H		Ħ	#	$\dagger \dagger$	Ш	П
-						IV																										口
2				1		Δ	SS	3	75	14			Ц		Ц	Ц	Ц	\coprod	\parallel	\coprod	Ц	Щ	\parallel		\coprod	\prod	\coprod	Ш	Щ	Ц	Ш	目
						\Box																										Н
							ĺ																									Н
<u> </u>						\mathbb{W}			ļ			4	\downarrow	4	\parallel	H	${f H}$	$\!$	+	\coprod	\parallel	Щ	\parallel	₩-	+	₩	\parallel	₩	H	₩	H	A
						lΛ	SS	4	65	36																						H
						\sim	¥ .																									H
-3-	1						+	-		 :		H	\dagger	\dagger	H	$\dagger \dagger$	Ħ	$\dagger \dagger$	\parallel	Ħ	T	+	H	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	\dagger	\dagger	\prod	$\dagger \dagger$	Ħ	月
	1					$ \setminus $		_																								H
	1					ΙX	SS	5	75 :	45										Ш				\coprod		\coprod		\parallel	Ш	\coprod	Щ	Н
_	1						1					П																				Н
																																Н
4]		-	<u> </u>	ļ			<u> </u>	H	\downarrow	\coprod	\coprod	\coprod	H	\coprod	\parallel	\downarrow	+	\parallel	H	₩	$\!$	H	H	╫	H	$\!$	#	Н
	$\frac{1}{4}$. 03	Auger refusal																													A
	1		 Well Installed																													H
-	1		Screen: 4.03 to 0.91 r	h		-	+-	-	 	 	1	\parallel	+	#	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	+	+	\dagger	\dagger	\parallel	\parallel	\parallel	$\dagger \dagger$	$\dagger \dagger$	\dagger	$\parallel \parallel$	$\dagger \dagger$	#	口
	-		Sand: 4.03 to 0.61 m Hole Plug: 0.61 to su:	nfaq	æ																											日
F	1		+ + ug. 0.01 00 5u.																										Ш		\prod	H
-5-	1							Т] '	П					П					\prod	\prod	\prod		\prod						H
	1		,																													H
	1							<u> </u>		<u> </u>				Щ	Ц	Ţ	Ц	Ш			Ц	Ц	Ц	Ц		Ц	Ш	Ц	Ш		Ш	П
	1											<i>'</i>	41	rEÑ	IDI:	X																
F	-																															
-	-			1	1	1	1			1	1																					

.

	7		St. Lawrence ' & Inspection (Tes Co.	stin Ltc	9 J.	•	(OFF	FIC	E B	OREHOLE RECORD
												REPORT NO. <u>25C163</u> BOREHOLE NO. <u>2</u>
			COHDOSE SILE									CASING FIF AUGER
	DATE	0F B0	RING June 24, 2025	[ATE OF	WL R				26,	2025	DATUM
			SOIL PROFILE	_	,		S	AMPI	LES			LAB TEST RESULTS
_	NO	_		10,	R ONS	NOL	.	EB	ERY	LUE	LABORATORY TESTS PERFORMED	LAD 1201 III20210
DEPTH	ELEVATION	DEPTH	SOIL DESCRIPTION	STRAT. PLOT	WATER CONDITIONS	TIONO	TYPE	NUMB	RECOVERY	N - VALUE	PER	WATER CONTENT & ATTERBERG LIMITS. WP WL
	Е			S	8	Ľ						DYNAMIC PENETRATION TEST BLOWS PER FOOTK
0-			75 mm Mongoil		<u> </u>	\	ļ					0 20 40 60 60
			75 mm Topsoil Silty Sand			$ \setminus $						
_			Brown, moist, dense, with gravel, becoming			ΙŇ	SS	1	50	57		
-			loose below 1.5 m and									
			dense below 2.3 m				1					
1 -						\forall	SS	2	40	40		
						$ \wedge $			10	40		
<u> </u>						\setminus	1					
						I X	SS	3	10	8		
2						\mathbb{A}	\vdash		-		1	
F	Ļ								ļ			
-	2.	. 44	Auger refusal									
	}		Well Installed Screen: 2.44 to 0.91									
-3-	}		Sand: 2.44 to 0.61 m			-	 			<u> </u>		
			Hole Plug: 0.61 m to	sur:	flace							
E]						<u> </u>		<u> </u>		1	
	}											
	1											
-4	1					-	<u> </u>	\vdash	 		1	
							_	<u> </u>	ļ	ļ	1	
	1											
	1											
-5	1						+			†		
	1											
	1					_	_		 	 	4	APPENDIX
	1											AFFENDIA
	1											

Γ		fl	St. Lawrence ' & Inspection (Tes Co.	tin Ltc	9 J.		(OFF	-IC	E B	()	R	R I	Εŀ	Η	(
İ			own of Smiths Falls																1	REI BO	PO RF	RT HO	NO LF	NO	_ <u></u>).	<u> </u>	<u>ان</u> 3	10	3_		_		-	
			Compost Site																. (CA:	SIN	١G		H	\mathbf{F}	A	ЦC	æ	r				_	
L	DATE	E OF BO	RING June 24, 2025	[ATE OF	WL R				26,	2025	_							_	DA	TU	M .	_	_									-	_
			SOIL PROFILE	·	,		S	AMPI	LES												_		-							.,	т	ii		
	_			10	ည္	z		~	≿	וַגַ	LABORATORY TESTS PERFORMED				L/	λB					ſ	ES	1					F	RES	υί	.iS	,		
ОЕРТН	ELEVATION	ОЕРТН	SOIL DESCRIPTION	STRAT. PLOT	WATER CONDITIONS	CONDITION	TYPE	NUMBER	RECOVERY	N - VALUE	ABORA TES ERFO	_				٧	۷A	TEI			ITE	NT				BE			MIT	S.		-		-
ă	EE	ä		STR	N S	8		N	RE	ž	-								W	P —			_	₩ 				W	L -					İ
-	╁											<u>۔</u>		DY	YN/	MI		ENI	ETR	ATI	ON	TE	ST 4	BL0	ws	PE	R FO		60	К			A	0
Ю-	\vdash		75 mm Topsoil			\ /						Ň	T	П			T	Ĭ	П	T			T		Π		П	\prod	Ï	T	П	П	Ĭ	Ĭ
F	1		Silty Sand			V	SS	1	35	2											$\ $													╛
F-	-		Brown, moist, loose, becoming compact belo	W		[ادر	Ľ]							\prod										\prod						
<u> </u>	1		0.8 m with wet zone										T					\prod																
	1		and gravel and gravelly, moist and																															
1.	1		dense below 2.3 m			\mathbb{H}	CC	_	25	11		H	4	\parallel	\parallel	\mathbb{H}	+	H	\downarrow	+	\prod	#	\parallel	\parallel	H	#	$\!$	$\dashv \mid$	\parallel	H	H	H	#	-
	1						SS	2	25	1																								
	1					 	ļ																											
-										 		H	\dagger	\dagger	\dagger	Т	+	H	t	\parallel	1	+	H	\parallel	\parallel	$\dagger \dagger$	$\dagger \dagger$	\dagger	\parallel	$\dagger \dagger$	Ħ	$\dagger \dagger$	1	
	-					IV	SS	2	50	15																								
2]					lΛ	33	٦	30					Ц									Ц		\coprod	\coprod	\coprod			Щ	Ш	Ц	Ц	
_	1													П																				H
	1						À																											-
	_					\mathbb{W}	SS		1.00	11		H	\parallel	\prod	\downarrow		\parallel	H	4	\prod	\downarrow	4	H	\coprod	\coprod	\coprod	\coprod	\downarrow	4	Щ	\coprod	Щ	\parallel	
E	_					$ \Lambda$	55	4	100	41																								Ē
	-						4																								.			
-3-	7					\vdash	-	┼	╁──		1	ŀ	\parallel	H	+	\parallel	+	\dagger	+	\parallel	+	H	+	╫	$\dagger \dagger$	H	+	+	H	H	H	H	\dagger	F
	1																																	
L	1					$ \Lambda $	SS	5	80	43																								L
	_						1				1	ſ			T			T			T	П		\prod	\prod				\prod				T	
	-							ļ																										F
-4	1					_				<u> </u>	_	L	\prod	\prod	4	\coprod	\prod	1	\parallel	\prod	1	\prod	\prod	\prod	\prod	Щ	$\downarrow \downarrow$	4	$\!$	H	+	$\!$	4	F
	\exists																																	F
F	1			_																														L
F	$\frac{1}{4}$	1.37	Auger refusal			-	-		-	+-	1	F	H	H	H	+	H	\dagger	+	╫	+	$\dag \uparrow$	╫	H	\parallel	+	+	\parallel	$\dagger \dagger$	+	+	\parallel	\dagger	F
			Well Installed																				$\ $											L
	_		Screen: 4.37 to 0.91 Sand: 4.37 to 0.61 m	1																														\vdash
-5			Hole Plug: 0.61 m to		Eac		+	T	1		7	1	Ħ	+	\parallel	\dagger	\parallel	t		\parallel	1			\parallel	1	T			\prod	\prod				F
	_																																$\ $	
F	\dashv											ļ										Ц							Ц		Ц	Ш		
-	7												AF	PE	N	XIC																		
	\exists																																	
\vdash	4			1	1	1	ı		1		1	1																						

.

	(₁ ,	70.	St. Lawrence & Inspection (Tes	stin	g		(OF	FIC	E B)	R	E	į	1	O	L	.[=	F	R۱	E	C	O	F	} [)			
																												3_				
١.	0047	ION	own of Smiths Falls Compost Site																C/	٩SI	NG	_	Н	F	_A	110	æ	r				
	DATE	OF BO	RING June 24, 2025		ATE OF	WL R	EADIN	G	June	26,	2025	5				_			DA	AΤι	JM							_	_			
			SOIL PROFILE				S	AMP	LES						1 4	D					TE	2Т					_	RES	2111	TC		
	×			5	- SN	NOI		es.	<u>}</u>	J.	LABORATORY TESTS PERFORMED				LA	D					1 (וכ					-	EO	UL			
DEPTH	ELEVATION	DEPTH	SOIL DESCRIPTION	STRAT. PLOT	WATER CONDITIONS	DIDIO	TYPE	NUMBE	RECOVERY	N - VALUE	LABOF PERF	Γ				W	AT		CO VP	NT	EN	Τ&	AT W		RBE	RG	LIN	AITS	3.			
	19			S	8	3				-				-			05					ĊŦ				D F	30T	-	<u></u>			_
l ₀ _											 	ů	П	T	NAI	wii C	2		na:	T	П		io II	П	, r.c	TT		60 	π	П		80
			125 mm Topsoil Silt & Sand			$\mathbb{N}/$																										Н
			Brown, moist, loose			X	SS	1	20	6																						H
-			with clay					<u> </u>				H	H	\dagger	H	+	\parallel	\parallel	+	+	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	$\dagger \dagger$	\dagger	\dagger	H		H
																												$\ $				H
1_						\bigvee	CC		120				\parallel	+	\parallel	\prod	\coprod	\parallel	\parallel	+	\coprod	ig	\coprod	\prod	\prod	\parallel	\prod	$\!$	$\!$	\coprod	\parallel	Н
						$ \wedge$	SS	2	30	9																						ļΗ
																																IF
_						7						I				T	I	1	1		\prod	Ħ	\prod	\prod		\parallel	\prod	\prod		\prod		H
						lΥ	SS	3	55	4																						IF
2	1.	98	Silty Sand	1		u	_	_				H	\parallel	+	\parallel	H	ig	₽	+	+	H	H	H	H	+	+	H	╫	₩	$\!$	H	$oxed{H}$
	'`	, , ,	Brown, moist,																													F
			gravelly, compact, becoming brown grey,	·		\backslash																										IF
			very moist and dense below 3.0 m			X	SS	4	60	23	1	Ĭ		+							\prod	\prod	T					\prod	\prod	\prod	П	E
			DETOM 2.0 III			\mathbb{Z}																										
-3-						_	igg	<u> </u>				\parallel	\perp	\parallel	H	H	\parallel	\mathbb{H}	H	\parallel	H	H	H	+	+	+	H	╫	#	╫	H	+
E			•			X	SS	5	55	50+																						E
																												\prod				ŀ
-												\prod			\prod																	
-4-	1					-	-	-	-			H	+		╫	H	H	+	\parallel		+	H	\parallel	+	+	+	\mathbb{H}	#	+	H	H	╫
				_																												
	$\frac{1}{4}$.	29	Auger refusal																	\coprod		Ц		Щ	Ш			\prod	\coprod	\coprod	Ц	밡
-			Well Installed																													
	1		Screen: 4.29 to 0.91 : Sand: 4.29 to 0.61 m																													上
-5-			Hole Plug: 0.61 to su	rfa	de	-		-	 	-	-	H	+	H	H	╫	H	\parallel	+	H	\parallel	\parallel	+	H	+	H	+	#	\dagger	#	$\dagger \dagger$	#
E	}																															
F	-		·																													止
F	1												API	PEI	۱D۱	X																
]																															

	<u></u>	7 D	St. Lawrence & Inspection (Tes Co.	stin Lto	9 1.		(OFF	FIC	E B	OREHOLE RECORD
	CI IEN	т Т	own of Smiths Falls									REPORT NO. <u>25C163</u> BOREHOLE NO. <u>5</u>
1		TION	Compost Site									casing _HF Auger
<u> </u>	DATE	OF BO			DATE OF	WLR		G AMP		20,	2023	DATUM
-	1		SOIL PROFILE		1			AWIF	123	Γ	£ 6	LAB TEST RESULTS
E	TION	E	SOIL DESCRIPTION	STRAT. PLOT	WATER	CONDITION	TYPE	BER	RECOVERY	N - VALUE	LABORATORY TESTS PERFORMED	WATER CONTENT & ATTERBERG LIMITS.
DEPTH	ELEVATION	DEPTH	SUL BLOUM HOW	STRAT	WAT	COND	₹	NOM	RECO	> N	PE PE	WP W WL
-	-					 						DYNAMIC PENETRATION TEST BLOWS PER FOOTK
-0	_		Topsoil			\ /		<u> </u>				0 20 40 60 80
			with gravel			V	SS	1	<u>55</u>	19		
<u> </u> -						\square	20	<u> </u>	25	19		
	0	. 61	Silty Sand	1								
	1		Black then brown, moist, compact with									
Ľ.	1		gravel, with black			X	SS	2	50	12		
匚			below 1.5 m to 1.8 m and very moist and			\triangle						
-	1		dense below 2.4 m					_				
	1					V	aa		4.5	_		
2	1						SS	3	45	7		
F				-		/	SS	4	80	 50+		
F	}					A		-				<u> </u>
F	2	. 64	Auger refusal									
3			Well Installed						<u> </u>			
Ě			Screen: 2.64 to 0.91 Sand: 2.64 to 0.61 m	m								
L			Hole Plug: 0.61 m to	sur	face							
L	1						 	 	<u> </u>	<u> </u>	-	
	1		,									
-4	1							_	<u> </u>			
F	1											
	-											
	1								<u> </u>			
F	1											
-5	1					_	-	├		-	-	<u> </u>
F												
F	-											
F	1											APPENDIX
	1											

.

			St. Lawrence	Tee Co.	tin Ltc	g :i.		(OFF	IC	ЕВ	C)	R	E	Ļ	-1														
			own of Smiths Falls																RE	POF	TF	NO.		2.	<u>5C</u> 6	<u>16</u>	3				ĺ
			Compost Site																CA	SIN	IG		HF	7 7	Δ11	æ	r				
	DATE (OF BO	RING June 24, 2025	D	ATE OF	WL R	EADIN	GJ	<u>une</u>	26,	2025	_						_	DA [*]	TUI	VI .										
			SOIL PROFILE				S	AMPI	LES											_	-0-	-					25.		TO		ı
	2			-0Т	SN	NO		œ	Ϋ́	구 무	LABORATORY TESTS PERFORMED			1	_At	3				1	EO	•					n E i	รบเ	.13		
DEPTH	ELEVATION	DEPTH	SOIL DESCRIPTION	STRAT. PLOT	WATER CONDITIONS	CONDITION	TYPE	NUMBER	RECOVERY	N - VALUE	ABOR TES PERFO				_	W	ATI	R		ITE	NT		ATT W	ERE	ER	G LI		S.			┨
	ELE			STF	NOS	00		2	æ	Z								_	_			-	-	_			_				
9-												0	_	DY	NAN	1IC	PEI 20		RATI	ON	TES	4 C		VS P	ER I	001	6. 60	.к.			80
			Silt & Sand			$\ \ /$																									Ш
			blackm moist, compact with gravel, with no	7		У	SS	1	50	13																					Н
			gravel from 0.8 m to			$\not\mid \wedge$		Ė	30		1	+	\coprod	\parallel	\mathbb{H}	+	H	\parallel	\parallel	H	\coprod	\parallel	$\!$	$oxed{H}$	$\!$	Н		╫	₩	H	\square
			2.1 m, brown and loose below 0.8 m, becoming																												H
			compact with gravel			\mathbb{N}																									IH
1 -			below 2.3 m			X	SS	2	50	5				П			T	Ħ		\prod	\parallel					П		\parallel	\prod	\prod	H
						$\langle \cdot \rangle$	}												H												H
<u> </u>						_						\parallel	H	Н	4	4	H	H	\parallel	$\!$	$\!$	\coprod	H	$\frac{1}{1}$	H	-	4	-	$\!$	╫	H
						\mathbb{N}																									$\ \Pi \ $
						ΙX	SS	3	55	11										$\ $											
-2-	İ										†		Ħ	+			Ħ	\parallel	\parallel		\parallel	Ħ	Ħ			1	T		\parallel	\parallel	H
_						\mathbf{M}							\prod	\perp		\parallel	Ц	\prod	\prod	\coprod	Щ	\parallel	\coprod	\coprod	\prod	\coprod		Щ	Щ	\coprod	Ш
						X	SS	4	100	10																					旧
	}					Γ	V											$\ $													口
-3-	<u> </u>					\geq			 			\parallel	H	+	+	\parallel	H	╫	\dagger	╫	\parallel	\parallel	H	$\dagger \dagger$	$\dagger \dagger$	╁	\dagger		Ï	$\dagger \dagger$	怈
F	3.	07	Auger refusal				ļ																								口
	1		Well Installed														\coprod	\coprod	\coprod	\coprod				Ц	\coprod	\coprod	Ц	Ш	\perp	\coprod	比
-	1		Screen: 3.07 to 0.91 m Sand: 3.07 to 0.61 m	n I																											
	1		Hole Plug: 0.61 m to s	uri	ace																										世
-4	1					-	-	-	 			H	H	\parallel	+	H	H	H	H	+	+	+	Ш	+	H	H	H	+	+	+	壯
F																															
																		\prod	\prod				Ш			\coprod				Щ	此
	1											\prod																			
	1																														L
-5	1						-	 	ļ		4	\parallel	+	+	1	\parallel	H	H	H	\parallel	+	#	+	H	+	+	H	#	+	\mathbb{H}	#
	1																														
	1																														F
	1						 				1	1	ΑPI	PEN	IDI.	X													-	_	
L.	4		i	1	1	. 1	1			1																					

		St. Lawrence ' & Inspection (Tes	stin	ā		(OFF	IC	E B	BO	F	E	:	-10	0	L	E	I	R	E	C	0	F	? [)		
	CATION	Cown of Smiths Falls Compost Site														_	CAS	SIN	G_		${ m I\!F}$	_A	UC	re:	r_			
	DATE OF BO	RING June 24, 2025	0	OATE OF	WL R	EADIN	<u>د</u> G	<u> Tune</u>	26,	2025	5						DAT	UM	_									
		SOIL PROFILE		.		S	AMP	LES		_			LA	n				TC	ет					_	IES	111	TC	
ОЕРТН	ELEVATION DEPTH	SOIL DESCRIPTION	STRAT. PLOT	WATER CONDITIONS	CONDITION	TYPE	NUMBER	RECOVERY	N - VALUE	LABORATORY TESTS PERFORMED				W		W	ON P	TE	NT 8	A A	ITE I	RBE	RG	LIN	AITS	<u>.</u> 3.		
0-											'n	יס	/NA	MIC	20 20		ATIO	T NC		BL 40	ows	PE	R FO		! 50	к		80
	0.18	Topsoil Silt & Sand Brown, moist, compact with gravel noted			\bigvee	SS	1	50	20																			
1.		below 1.5 m			\																							
-'					\bigwedge	SS	2	100	12																			
2					X	SS	3	75	10																			
- 4-	0.26	7				SS	4	100	50+																			
	2.36	Well Installed Screen: 2.36 to 0.91 Sand: 2.36 to 0.61 m	IM																									
-3- 		Hole Plug: 0.61 m to	sur	face																								
-4-																												
	- - - -																											
-5																												
											A	PPE	N Di	IX	-	e insk												

ATTACHMENT E
Town of Smiths Falls IPZ

ATTACHMENT F
Water Well Records

31 c/16 E 31 c/16 E 31 c/16 E 31 c/16 E 31 c/16 E 31 c/16 E 31 c/16 E	SOURCES COMM		GROUND WATER 35 N JUL 1 2 18	[o 1528
Elev. 45 R 18141016 WATER WE			ONTARIO WA	· ·
		age, Town or City	and the contract of the contra	
	Date complete	a 946	5	1961
	ddress	(day Tues, Unilles	Falls	year)
Casing and Screen Record			ing Test	
Inside diameter of casing 4 in	Į.	10		_
√Total length of casing 22 ft.	_			5 G.P.M.
Type of screen				
Length of screen	Duration o	f test pumping	Ihr.	<i>l</i>
Depth to top of screen		r or cloudy at end		
Diameter of finished hole 4 in.				5 G.P.M.
	with pump	setting of	70 feet bel	ow ground surface
Well Log				er Record
Overburden and Bedrock Record	From ft.		Depth(s) at which water(s) found	Kind of water (fresh, salty, sulphur)
	- 0	2	40	0.1
- Clay	15	- 80	78	bress.
	7.0			
	<u> </u>			
For what purpose(s) is the water to be used? Watering tan		Location	n of Well	11
drinking papers toilets		liagram below sho		ell from
Is well on upland, in valley, or on hillside? upland.	·	and lot line. I		
Drilling or Boring Firm C. V. movismy		1)		
Drining of Boring Print			Δ,	[N
Address Frankrille Ont.	•	♦ ///	>~ '',	
Addicss		1/2	300	
Licence Number 275	,		1 4/	
Name of Driller or Borer Carl Besaulnier. Address & stons Corners.	2			
Address & stora Corners.				•
Date June 14th.		Ne	M	Professional Comments (Comments of Comments
67/ Mouris an		LP		
(Signature of Licensed Drilling or Boring Contractor)		* * * * * * * * * * * * * * * * * * *		`
Form 7 15M Sets 60-5930			,	`
OWRC COPY				S.S8

ENL'A'
31 C/16 E

UTM 1/18 | 2 | 41 /1 /1 /17 16 | E

19 | R | 41 / 17 | 3 | 0 | 2 | 0 | N

Elev. 10 | 4 | 0 | 7 | Basin 25





No

The Well Drillers Act

Department of Mines, Province of Ontario

Water W	/ell	Rec	ord		
A /	n 34	Harra Town	or City. C. L. Z.	neka	Mont
		or City)	- City . L. F.S		
		S. mail	(Falls		· · · · · · · · · · · · ·
Date Completed (day) (month) (year)					
Pipe and Casing Record		P	umping Test		
Length (s) of casing (s). Type of screen. Length of screen. Distance from top of screen to ground level.	Pumping lev Pumping rat Duration of	el. 20 test, /	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	level	Ce 2
Wa	ter Record				
Kind (fresh or mineral). Quality (hard, soft, contains iron, sulphur, etc.). Appearance (clear, cloudy, coloured) For what purpose(s) is the water to be used?	and and a	- 	Depth(s) to Water Horizon(s)	Kind of Water	No. of Feet Water Rises
How far is well from possible source of contamination? What is the source of contamination? Enclose a copy of any mineral analysis that has been made	look.	house			
Well Log	1 -		Loca	tion of Well	
Overburden and Bedrock Record	From	To			
Strail Sonolitone & fings in its grant	O ft.	ft.	well from ro		
Situation: Is well on upland, in valley, or on hillside? Drilling Firm Address Name of Driller Date	Le son		62	CSS.S	Finds
FORM 5			Signature of	Licensee	

ENL'A'
31 e/16 E

19 R 4 9 7 3 1 0 16 N

Elev 9 R + 0 14 1 10



The Water-well Drillers Act, 1954
Department of Mines



Water-Well Record

	T on amle				NaAth	•
County or Territorial District	Lanark	Town	_		•	
			n v	ill <mark>age, Town or Ci</mark> ress	D Howith	
			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	337 Cr	eighton Str	eet, Ottawa.
(day)	(month)	(year)	<u> </u>	Agent.		
Pipe and Casin	g Record				Pumping Test	
Casing diameter(s)	mich		Stat	ic level	y many	
Length(s)			Pum	ping rate	350 C	₽ / s
Type of screen			Pum	ping level	20010	Í
Length of screen			Dura	ation of test	J. J.	La contra
Well Log	:	<u></u>		,	Water Record	
Overburden and Bedrock Record	From ft.	To ft.		Depth(s) at which water(s) found	No. of feet water rises	Kind of water (fresh, salty, or sulphur)
clean and qu	and The			142615	8 147	in duest
Line Stand Sa		15	0			· · · · · · · · · · · · · · · · · · ·
		ļ				
	•					
	 		-	· · · · · · · · · · · · · · · · · · ·		
				·		
For what purpose(s) is the water	to be used?	1		T	-41 · 6 337-D1	PH
			1	Loca In diagram below:	ation of Well	f well from
Is water clear or cloudy?		2		oad and lot line.		
Is well on upland, in valley, or on	hillside?,	May				λ :
Drilling firm	Juc of m			, 32	11 Contin	Bunk
Address 133	el][a:	Jan.		1 2	O. K.S. W.	r /
				\$	$\stackrel{\wedge}{\circ}$	/
Name of Driller						
Address	y the					4
75-7-1	•			1	٠/ح	
Licence Number	foregoing			110	PROX. /MI	426
statements of fact			Λ	1	OKOK /M/	1. Kitelly
1.01.11						
Date	gnaure of Licensee	W_		E	<i>→</i>	r - R
	T or micensee	•			00	= 1)
orm 5						
			-	5	CSS.	.S8



The Water-well Drillers Act, 1954 Department of Mines

NOV 8 1956 GEOLOGICAL BRANCH
DEPARTMENT of MINES

Water-Well Record

County or Territorial District	WYTTYWW.	L.10W	nsmo	Village Town or Ci	hty NORTH	
			Ado	Village, Town or Ci	The Lalle	2 CNT
(day)	(mợp ch)	(year)			R. C. C. C. C. C. C. C. C. C. C. C. C. C.	
Pipe and Casing	g Record				Pumping Test	
Casing diameter(s)	ich		Sta	tic level	tilon	o Loss
Length(s)			Pu	mping rate	00 9 /4 1X	
Type of screen		•••••	1	mping levelL	77 16 7	m a last
Length of screen	• • • • • • • • • • • • • • • • • • • •		Du	ration of test	in the	
Well Log					Water Record	
Overburden and Bedrock Record	From ft.	To ft.		Depth(s) at which water(s) found	No. of feet water rises	Kind of water (fresh, salty, or sulphur)
tot well, 16 ft	0	/6				
Ansil.	<u> </u>	-		417 48	-2x /7	<u></u>
Days				17	0071	1
				100		
hard sonolslone	16	4.8	ft			
						<u> </u>
For what purpose(s) is the water	to be used? /	1		T -	N	C
		ruse	' /		ation of Well show distances of	well from
s water clear or cloudy?	lear		1	1	. Indicate north	
s well on upland, in valley, or on			- /			
	comple		1	\		
Drilling firm			~			
Address			(P.			
Yana de Daniel	A 1	d die in	15	The state of the s		
Name of Driller	Sand State of State o		ر. ص	3/10/2		
Address	•••••••••••			10,		
Licence Number2.2.	••		7	er Si		
I certify that the			4.	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	N. Committee	
statements of fact	are true.				<u>.</u>	
Date sug 34 th	ignature of License	lon		/	至	
				,		ri.
m 5						

Ontario Water Resources Commission Act ONTARIO WATER RESOURCES COMMISSION Township Village, Town or City No RTH Date completed.... **Pumping Test** Casing and Screen Record 18 FT. 6 5/8 IN Inside diameter of casing Test-pumping rate ... Total length of casing 28 FT. Pumping level... Type of screen 0 Duration of test pumping..... Length of screen Water clear or cloudy at end of test CLEAR Depth to top of screen...... Recommended pumping rate Diameter of finished hole with pump setting of 25 feet below ground surface **Water Record** Well Log Kind of water (fresh, salty, sulphur) Depth(s) at To ft. From which water(s) Overburden and Bedrock Record found FRESH 30 0 EARTH 38 SANDSTONE Location of Well For what purpose(s) is the water to be used? In diagram below show distances of well from HOUSEHOLD road and lot line. Indicate north by arrow. Is well on upland, in valley, or on hillside? Uplano Drilling or Boring Firm THOMPSON 13 RDS Licence Number..... Name of Driller or Borer GERALD HOMPSON (Signature of Licensed Drilling or Boring Contractor) Form 7 15M Sets 60-5930 055.58 OWRC COPY

GROUND WATER BRANI

۸.	ENL'A'		No.		p
WITM 1 8 2 4 1 7 1 6	31 C/16			35 N	Nº 1570
19 R 41917131311	10 N	W. E.		DEC	
Elev. 19 12 1014121/1			TARIO	RECENV	
· .		ater-well D D epart men:	rillers Act, 1954	MAR 28 1957	,]
Basin 2 5 1 1		-	il i	GEOLOGI	isa 1
104 3			ell Reco	-	my . Li J
County or Territorial District	Lanach	Tow	nship, Village, Town or	City horth	Elemsley
Con	Street and I	Number (i	f in Village, Town or	City)	
Owner	J./.	57	Address	A Salva	••••••
A (day)	(month)	(year)	1137		
Pipe and Casin	g Record			Pumping Test	
Casing diameter(s)	***************************************		Static level	f L	,
Length(s)		•••••	Pumping rate 2	o gol M	
Type of screen			,	<i>ij</i> •	
Length of screen	••••••••••••	•••••••	Duration of test	<u> </u>	•••••
Well Log	:			Water Record	
Overburden and Bedrock Record	From ft.	To ft.	Depth(s) at which water(s) found	No. of feet water rises	Kind of water (fresh, salty, or sulphur)
Sandstong.	0	37	3.5	17	Trech
	 				<u> </u>
		 			
For what purpose(s) is the water	to be used?		L	ocation of Well	JN
Is water clear or cloudy?	ear-		11	v show distances of	/
Is well on upland, in valley, or on			totad and lot lin	e. Indicate north	by arrow.
upl	and				
Drilling firm	Mangalage	£	c		
Address	wall.	(207.4	N.6. 5.3	• 44
Nome of Dating	[M -		1° 68	mile Lot. 3	last
Name of Driller	, ,		\\ \	mue	<u></u>
	#		15 14		
Licence Number 1077	•		- 77		
I certify that the	foregoing				
statements of fact	are true.				
Date Mar 26 Cecil	Munro gnature of License				

UTM 18 2 41174119 E 19 R 4973501 N Ontario Water Reso Elev 9 R 04115 WATER WEL Basin 25 1 1 1	Ownship, Village, To Date completed	ORD	B5 N ONTA RESOURCE	ARIO WATER ES CUMMISSION LMSLEY 1962 year)
	dress	IHS FA	ALL S	
Casing and Screen Record		<u> </u>		
Inside diameter of casing	Static level		1817	<i></i>
Total length of casing 18 Ff.	Test-pumping ra	ite		G.P.M.
Type of screen				
Length of screen			_	
Depth to top of screen		-		•
Diameter of finished hole				
	Interio Water Resources Commission Act ER WELL RECORD Township, Village, Town or City Date completed (day Pumping Test Static levei Test-pumping rate Pumping level Duration of test pumping Water clear or cloudy at end of test Recommended pumping rate with pump setting of From ft. To John Condition To Water Record Depth(s) at Kind of water Without Record To whichwater(s) found To whichwater(s) found Depth(s) At Rind of water Condition of Well In diagram below show distances of well from road and lot line. Indicate north by arrow. N N N N N N N N N N N N N			
Well Log				T
Overburden and Bedrock Record			which water(s)	(fresh, salty,
SANOY LOAM	0	3		
SANOV LOAM GREY LIMESTONE	3		1 4 1	
For what purpose(s) is the water to be used?	In diagram			ell from
	9			
Is well on upland, in valley, or on hillside? Drilling or Boring Firm R.H.MILLER Address BROCKVILLE Licence Number Name of Driller or Borer C.ROBERTSON Address Date WORTH GOWER OWER No No No No No No No No No No No No No N	HWX	CSS.S8	·	

	3502	306 J	NOV 25	URCES 968
County or District LANARK	The Ontario Water Resources Commission Act WATER WELL RECORD Static LANARK Lot 2 Date completed 27 Gress R S Smalls Fall Commission Gress R S Smalls Fall Commission Costing and Screen Record Pumping Test Test-pumping rate Pumping level Duration of test pumping Water clear or cloudy at end of test Recommended pumping rate Recommended pumping rate Overburden and Bedrock Record Water Record Prom To Depth(s) at White Record Water Record Prom To Depth(s) at White Record Water Record Prom To Depth(s) at White Record Prom To William Water (Fresh, aslive) Water Record The World Water Record Prom To Depth(s) at White Record Water Record Water Record Prom To Depth(s) at White Record Water Record In diagram below show distances of well from road and for line. Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow. Prom To Depth(s) at White Record and Indicate north by arrow.	MISSION EGY		
Casing and Screen Record	The Ontorio Water Resources Commission Act WATER WELL RECORD WATER WELL RECORD AND RK Township, Village, Town or City WELL RESOURCES COMMISSION Lot 2 Date completed 27 Gay Gress R 3 Small Full Full Full Full Full Full Full F			
The Ontario Water Resources Commission Active Seasin 25 WATER WELL RECO County or District ANDRK Township, Village, Tow Con. Lot. 2 Date completed datess Prompting assing Con. Seasing and Screen Record Inside diameters assing Static level Test-pumping rate Pumping level Length of screen Duration of test pum Water clear or cloud Recommended pum with pump setting of the season	rate	<u> </u>	G.P.M.	
Diameter of finished hole	Recommended	pumping rate	WATER RESOURCES NOV 25 1968 ONTARIO WATER SOURCES COMMISSION PROVED FOR MATER SOURCES COMMISSION ORTH ELIBER CAN G.P.M. G.P.M. G.P.M. feet below ground surface Water Record Depth(s) at which water(s) found Test Water Record Test Sources G.P.M. State of Water (fresh, salty, sulphur) F Well istances of well from ate north by arrow.	
Well Log	From	To	Depth(s) at	Kind of water
Overburden and Bedrock Record			which water(s)	
Heil Senton Rock	\$4	1118	125'	
	In diagra			ell from
Is well on upland, in valley, or on hillside? Drilling or Boring Firm Address Licence Number Name of Driller or Borer Address Date (Signature of Licensed Drilling or Boring Contractor)	road and	d lot line. Ind	icate north by	
O W R C COPY			CSS.S8	7,75

31°/16E

41° 41973300

The Ontario Water Resources Commission Act

WATER WELL RECORD

(L)	

(Township) Village, Town or City North Elmsley County or District Lenerk Con. 5 VI Lot 3 Date completed 27 5 month dress R. R. # 2, Smiths Falls, Ontario Casing and Screen Record **Pumping Test** Inside diameter of casing 5" Static levei 18! Total length of casing 21' Test-pumping rate 8 G.P.M. Pumping level 601 Type of screen Length of screen Duration of test pumping 2 hrs Water clear or cloudy at end of test lear Depth to top of screen Diameter of finished hole 5111 Recommended pumping rate 6 G.P.M. with pump setting of ________ feet below ground surface Well Log **Water Record** Depth(s) at Kind of water From То Overburden and Bedrock Record (fresh, salty, sulphur) which water(s) found Sand and fill 2 Sands tone Shale 2 12 Solid Brown Sandstone 12 73 75 fresh Location of Well For what purpose(s) is the water to be used? In diagram below show distances of well from Domestic use road and lot line. Indicate north by arrow. Is well on upland, in valley, or on hillside? upland Drilling or Boring Firm PRIVATE Lloyd Trodena بالماعاد Address R. # 2, Smiths Falls, Ont لأت . Licence Number 2827 30 Name of Driller or Borer Lloyd Trodena Address R. R. # 2, Smiths Falls, Ont. Jyne 28, 1968 HWY (Signature of Licensed Drilling or Boring Contractor) Form 7 5M 60-20912 659.33 OWRC COPY

11824117050E

OWRC COPY



318/115

2v. 5 R 0 4 2 5 The Ontario Water Resources Commission Act
WATER WELL RECORD

County or District - LANARK T	ownship, Villag	e, Town or City.	NORTH E	MSLEY
Con S Lot 3	Date completed	<i>7</i>	MAY 174 FA	((() /
	ress // // 7		ng Test	
Casing and Screen Record	Ct-ti- level			
inside diameter of casing	Static level)	G.P.M.
Total length of casing 26	l est-pumpin	g rate 50		
Type of screen	Pumping lev	el	1 HOUR	
Length of screen	Duration of	test pumping	of test Cho	·DY
Depth to top of screen	Water clear	or cloudy at end o	of test	CPM
Diameter of finished hole	Recommend	led pumping rate	6 feet belo	G.I.W.
	with pump s	setting of		
Well Log		·		r Record Kind of water
Overburden and Bedrock Record	From ft.	To ft.	Depth(s) at which water(s) found	
EBEY SANDSTONE	0	72	66	FRESA
			n of Well	
For what purpose(s) is the water to be used?	. T.,	==	ow distances of we	ell\from •
DOMESTIC	road	and lot line. I	ndicate ndrth by	arrow /
Is well or upland, in valley, or on hillside?				~ /\mathrew{1}
Drilling or Boring Firm THOMPSON BAOS			1 An	. L
Address LANAAK BR#3		V	Ĭ.	1
Licence Number 3303	1	BORAMAHA	Z/E	' 多。
Name of Driller or Borer By CAM - ASN		·V	THE H	1 33
CANTON ARES			800	V
may 2 1969			~ °	1.
Date				•
(Signature of Licensed Drilling or Boring Contractor)				
Form 7 15M-60-4138				
			C	SS.S8

The Ontario Water Resources Commission Act

WATER	WELL	RECC)RD
-------	------	------	------------

INTY OR DISTRICT	2. CHECK X CORRECT	TOWNSHIP, BOROUGH,		GE 3	con.	, BLOCK, TRACT,	14 15 SURVEY, ETC.	,	22 23 LOT 25:
+E	ENT LANARY	N &	Frms L.	EY			DATE COM	PLETED //	18-53
			3mi	T 14 (= ALLS		DAY / 8	/ 4	YRZ
		ING 7	2950	RC ELEVATION	2,51 5	BASIN CODE	1 1 1	1 1 1	
<u>. </u>	10 12		24	25 26	30	31			
	LOG	OF OVERBURD		DROCK MAIL					- FEET
ENERAL COLOUR	COMMON MATERIAL	OTHER M	MATERIALS		GENER	AL DESCRIPTION		FROM	TO
brown	soil							0	4
1	sandstone							4	86
			· · · · · · · · · · · · · · · · · · ·					<u> </u>	-
									1
								-	
								-	
						-			-
		-					J		-
					·				-
1								-	1
¥ 6	~								
31) laac	146/02 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	dd Ad III L	لبلبلن	للتنال					لب
32	14 15 21	32		43		54 (S) OF OPENING OT NO.)	65 31-33 DIAM	FTER 34-20	75
MATER FOUND	ER RECORD	51 CASING &	WALL	DEPTH - FEET		ERIAL AND TYPE		INCHES	41-4
AT - FEET	FRESH 3 SULPHUR 14	INCHES MATERIAL	INCHES	FROM TO	13-16 S MAT	ERIAL AND TYPE		DEPTH TO TOP OF SCREEN	FEET
15:18	SALTY 54 MINERAL	2 GALVANIZI		0 2		DI II C C I N	C 0 CEA	LING P	ECOR
	□ FRESH 3 □ SULPHUR □ P	4 □ OPEN HOL			[61]	PLUGGIN	G & SEF	ALING K	ECOK
		17-18 1 T STEEL	19	00	20-23 DEPTH	SET AT - FEET	MATERIAL AN	D TYPE (C	EMENT GROU
	☐ FRESH 3 ☐ SULPHUR 24 ☐ SALTY 4 ☐ MINERAL	17-18 1 STEEL 2 GALVANIZ 3 CONCRETI			20-23 DEPTH		MATERIAL AN	D TYPE LEA	EMENT GROU D PACKER, E
25-28 1	☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 29	2 GALVANIZ	E	00	20-23 DEPTH FROM	ı TO		D TYPE (C	EMENT GROU D PACKER, E
25-28 1 2 30-33 1	□ SALTY	2	E LE 26 ED E	00	20-23 DEPTH FROM 27-30	M TO		D TYPE (C	EMENT GROUD PACKER, E
25-28 1 2 30-33 1 2	☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 29 ☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 34 80 ☐ SALTY 4 ☐ MINERAL	2	E LE 26 ED E LE	00	20-23 DEPTH FROM	M TO 10-13 14-17 18-21 22-25 26-29 30-33	80	D TYPE LEA	EMENT GROU) PACKER, E
25-28 1 2 30-33 1	☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 29 ☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 34 80 ☐ SALTY 4 ☐ MINERAL	2	E LE 26 ED E LE US PUMPING 15-16	00	20-23 DEPTI FROM	M TO 10-13 14-17 18-21 22-25 26-29 30-33	N OF/WE	LEAN LEAN	D PACKER, E
25-28 1 2 30-33 1 2 PUMPING TEST M	☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 29 ☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 34 80 ☐ SALTY 4 ☐ MINERAL ETHOD 10 PUMPING RATE 2 ☐ BAILER WATER LEVEL END 0	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-29 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM	E LE 26 ED E LE CF PUMPING 15-16	17-18	SC 27-30 DEPTH FROM	M TO 10-13 14-17 18-21 22-25 26-29 30-33	N OF WE	LEAN LEAN	D LOTH
25-28 1 2 2 30-33 1 2 PUMPING TEST M PUMPING TEST M STATIC	☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 29 ☐ SALTY 4 ☐ MINERAL ☐ FRESH 3 ☐ SULPHUR 34 80 ☐ SALTY 4 ☐ MINERAL ETHOD 10 PUMPING RATE 2 ☐ BAILER WATER LEVEL END OF PUMPING WATER LEVEL END OF PUMPING WATER LEVEL END OF PUMPING WATER LEVEL WATER LEVEL END OF PUMPING WATER LEVEL WATER LEVEL END OF PUMPING	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-29 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 45 MIN	E LE 26 ED E LE STANDER STANDE	00 17-18 MINS.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	LEAN LEAN	D PACKER, E
25-28 1 2 30-33 1 2 1 1 1 1 1 1 1 1	SALTY	2 GALVANIZ 3 CONCRETI 4 OFEN HO 24-29 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 0 0 0 0 0 0 0 0	E LE 26 ED E LE 15-16 HOURS 1 PUMPING 20 RECOVERY WITES 6 MINUTES 6 MINUTES 6 MINUTES 6 MINUTES 1 E MI	00 17-18 MINS.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	LEAN LEAN	D LOTH
25-28 1 2 30-33 1 2 PUMPING TEST M 1 PUM	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 BC SALTY 4 MINERAL SALTY 4 MIN	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 Q 29-31 FEET ET AT WATER AT C C C C C C C C C C C C C	E LE 26 ED E E IS-16 HOURS 10 PUMPING 15-16 HOURS 11 PUMPING 20 RECOVERY NUTES 32-34 32-34 FEET END OF TEST LEAR 2 CLOL	17-18 MINS. ES 85-37 7 10DY	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
25-28 1 2 2 30-33 1 2 2 2 5-28 1 2 2 5-28 1 2 2 5-28 1 2 2 5-28 1 2 2 5-28 1 2 2 5-28 1 2 5-2	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 BC SALTY 4 MINERAL SALTY 4 MIN	2 GALVANIZ 3 CONCRETI 4 POPEN HO 24-29 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION 6 PM LEVELS DURING 3 OMINUTES 6 O 2 69-31 7 FEET ET AT WATER AT	E LE 26 ED E LE 15-16 HOURS 10 PUMPING 25 RECOVERY NUTES 60 MINUT 32-34 END OF TEST LEAR 2 CLOL	17-18 MINS. FES 35-37 FEET 42	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	LEAN LEAN	D LOT4
25-28 1 2 25-28 1 2 30-33 1 1 PUMPING TEST M 11 PUMPING TEST M 12 PUMPING TEST M 14 PUMPING TEST M 15 PUMPING TEST M 16 PUMPING TEST M 17 PUMPING TEST M 16 PUMPING TEST M 17 PUMPING TEST M 17 PUMPING TEST M 18	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 BC SALTY 4 MINERAL SALTY 4 MIN	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 Q 29-31 FEET 43-45 RECOMME! FUMPING FEET AT WATER AT FUMPING FEET FEET FUMPING F	E LE 26 ED E LE 15-16 HOURS 10 PUMPING 20 RECOVERY NUTES 60 MINUT 32-34 FEET 2 CLOL NOED	17-18 MINS. ES 85-37 7 7 42 10DY 46-49	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
25-28 1 2 25-28 1 2 2 30-33 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	□ SALTY 4 □ MINERAL □ FRESH 3 □ SULPHUR 29 □ SALTY 4 □ MINERAL □ FRESH 3 □ SULPHUR 34 80 □ FRESH 3 □ SULPHUR 34 80 □ FRESH 3 □ SULPHUR 34 80 □ SALTY 4 □ MINERAL □ SA	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 Q 29-31 0 Q 29-31 FEET 43-45 RECOMME! FEET AT WATER AT FUMING 1C CAPACITY 5 ABANDONED.	E LE 26 ED E LE 26 ED E LE 26 15-16 HOURS 50 RECOVERY NUTES 60 MINUT 32-34 STEET END OF TEST LEAR 2 CLOL	17-18 MINS. FEET 42 IDY 46-49 GPM.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
25-28 1 2 25-28 1 2 30-33 1 1 PUMPING TEST M 11 PUMPING TEST M 12 PUMPING TEST M 12 PUMPING TEST M 13 PUMPING TEST M 14 PUMPING TEST M 15 PUMPING TEST M 15 PUMPING TEST M 15 PUMPING TEST M 16 PUMPING TEST M 17 PUMPING TEST M 18	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 BC SALTY 4 MINERAL SALTY 4 MIN	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 Q 29-31 0 Q 29-31 FEET 43-45 RECOMME! FEET AT WATER AT FUMING 1C CAPACITY 5 ABANDONED.	E LE 26 ED E LE 26 ED E LE 26 15-16 HOURS 50 RECOVERY NUTES 60 MINUT 32-34 STEET END OF TEST LEAR 2 CLOL	17-18 MINS. FEET 42 IDY 46-49 GPM.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
25-28 1 2 25-28 1 2 2 30-33 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 BC SALTY 4 MINERAL SALTY 4 MIN	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 Q 29-31 0 Q 29-31 FEET 43-45 RECOMMER FEET AT 11 C CAPACITY 5 ABANDONED, 7 UNFINISHED 5 COMMERCIAL	E LE 26 ED E LE 26 ED E LE 26 15-16 HOURS 50 RECOVERY NUTES 60 MINUT 32-34 STEET END OF TEST LEAR 2 CLOL	17-18 MINS. FEET 42 IDY 46-49 GPM.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
25-28 1 2 25-28 1 2 2 30-33 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 BC SALTY 4 MINERAL SALTY 4 SAL	2 GALVANIZ 3 CONCRETI 4 POPEN HO 24-29 GALVANIZ 3 GALVANIZ 3 GALVANIZ 3 GALVANIZ 4 POPEN HO 11-14 DURATION GPM LEVELS DURING 45 MIN 6 ABANDONED, FEET RATE 5 ABANDONED, 7 UNFINISHED 5 COMMERCIAL 6 MUNICIPAL 7 PUMPINS	ELE 26 ED ED E ELE OF PUMPING 15-16 HOURS 11 D PUMPING 25 RECOVERY RECOVERY RECOVERY RECOVERY LEAR 2 CLOUNDED INSUFFICIENT SUP POOR QUALITY	17-18 MINS. FEET 42 IDY 46-49 GPM.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
25-28 1 2 25-28 1 2 2 30-33 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	SALTY 4 MINERAL	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 Q 29-31 FEET 43-45 RECOMMER FEET AT STEET AT 11 C CAPACITY 5 ABANDONED, 7 UNFINISHED 5 COMMERCIAL 6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR	ELE 26 ED ED E ELE OF PUMPING 15-16 HOURS 11 D PUMPING 25 RECOVERY RECOVERY RECOVERY RECOVERY LEAR 2 CLOUNDED INSUFFICIENT SUP POOR QUALITY	17-18 MINS. FEET 42 IDY 46-49 GPM.	IN DIAGRAM B LOT LINE. INI	10-13 14-12 18-21 22-28 26-29 30-33 LOCATIOI ELOW SHOW DIST. DICATE NORTH BY	N OF WE	FILE LEA	D LOTH
25-28 1 2 25-28 1 2 25-28 1 1 2 2 25-28 1 1 2 2 25-28 1 1 2 2 25-28 1 1 2 2 25-28 1 1 2 2 25-28 1 1 2 2 2 25-28 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	SALTY	2 GALVANIZ 3 CONCRETI 4 POPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 POPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 6 OZ 29-31 COZ 29-31 FEET 43-45 RECOMME! FEET AT SOME PUBLIC SUPPLY 6 ABANDONED, 7 UNFINISHED 5 COMMERCIAL 6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR 9 9	ELE 26 ED ED E E E E E E E E E E E E E E E E	17-18 MINS. FEET 42 IDY 46-49 GPM.	IN DIAGRAM B LOT LINE. INI	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
PUMPING TEST IN PUMPING TEST I	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 80 SALTY 4 MINERAL SALTY 4 SALTY	2	ELE 26 ED ED ELE OF PUMPING 15-16 HOURS 1 D PUMPING 32-34 RECOVERY NUTES FEET END OF TEST LEAR CLOU INSUFFICIENT SUP POOR QUALITY CONDITIONING NOT USED NG NG	17-18 MINS. FEET 42 IDY 46-49 GPM.	SC 27-30 DEPTH FROM	10-13 14-17 18-21 22-25 26-29 30-33 LOCATIO	N OF WE	FILE LEA	D LOTH
PUMPING TEST M TO THE PUMPING TEST M TO THE	SALTY 4 MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 80 SALTY 4 MINERAL SALTY 4 SALTY	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0	ELE 26 ED ED ELE OF PUMPING 15-16 HOURS 1 D PUMPING 32-34 RECOVERY NUTES FEET END OF TEST LEAR CLOU INSUFFICIENT SUP POOR QUALITY CONDITIONING NOT USED NG NG	17-18 MINS. ES 85-37 FEET 42 IDY 46-49 PLY DRILLERS	IN DIAGRAM B LOT LINE. INI	10-13 14-12 16-21 22-25 26-28 30-33 16-21 16-21 22-25 30-33 16-21	N OF WE ANCES OF WELL F	FILE ROM ROAD AND	D Lot4 Lot 3
25-28 1 2 2 30-33 1 2 2 30-33 1 1 2 2 30-33 1 1 2 2 30-33 1 1 2 2 30-33 1 1 2 2 30-33 1 1 2 30-33 1 2 30-33 1 1 2 30-33 1 1 2 30-33 1 1 2 30-33 1 1 2 30-33 1 1 2	SALTY	2 GALVANIZ 3 CONCRETI 4 POPEN HO 24-29	ELE 26 ED ED ELE OF PUMPING 15-16 HOURS 1 D PUMPING 32-34 RECOVERY NUTES FEET END OF TEST LEAR CLOU INSUFFICIENT SUP POOR QUALITY CONDITIONING NOT USED NG NG	17-18 MINS. FEST 42 JDY 46-49 GPM. DRILLERS	IN DIAGRAM B LOT LINE. INI	TO 10-13 14-17 18-21 22-25 26-29 30-33 16-21 PY 18-21 PY	BO OF WE ARROW WELL F	ELL FROM ROAD ANI	Diofy Lot 3
PUMPIG TEST M 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 30-	SALTY	2	ELE 26 ED ED E E E E E E E E E E E E E E E E	17-18 17-18	IN DIAGRAM B LOT LINE. INI	10-13 14-12 16-21 22-25 26-28 30-33 16-21 16-21 22-25 30-33 16-21	BO OF WE ANCES OF WELL F	FILE ROM ROAD AND	Diofy Lot 3
PUMPING TEST M 25-28 1 2 30-33 1 2 PUMPING TEST M STATIC LEVEL 19- 2	SALTY MINERAL FRESH 3 SULPHUR 29 SALTY 4 MINERAL FRESH 3 SULPHUR 34 86 SALTY 4 MINERAL SALTY 5 MATER LEVEL END OF PUMPING 22-24	2 GALVANIZ 3 CONCRETI 4 POPEN HO 24-29	ELE 26 ED ED E E E E E E E E E E E E E E E E	17-18 17-18	IN DIAGRAM B LOT LINE. INI AND REMARKS: E F INSPECTION	10-13 14-17 18-21 22-29 26-29 30-33 LOCATIOI ELOW SHOW DIST. DICATE NORTH BY CONTRACTOR 3 70.5	BO OF WE ANCES OF WELL F	ELL FROM ROAD ANI	D Lot4 Lot 3
PUMPING TEST M 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 2 30-33 1 2 30-3	SALTY MINERAL	2 GALVANIZ 3 CONCRETI 4 OPEN HO 24-25 1 STEEL 2 GALVANIZ 3 CONCRETI 4 OPEN HO 11-14 DURATION GPM LEVELS DURING 30 MINUTES 0 30 MINUTES FEET FEET FEET A3-45 RECOMMER FEET PUMPINS FEET CCAPACITY 5 ABANDONED, 7 UNFINISHED 5 COMMERCIAL 6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR 9 UNFINISHED 5 COMMERCIAL 6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR 9 DIAM 10 BORIVI 10 DIAM 10 DIAM 11 DIAM 12 DIAM 13 DIAM 14 DIAM 15 DIAM 16 BORIVI 17 DIAM 18 DIAM 17 DIAM 18 DIAM 19 DRIVI	ELE 26 ED ED ELE 26 ED ELE 36 IS-16 HOURS 1	17-18 17-18 17-18 17-18 18-18	IN DIAGRAM B LOT LINE. INI AND REMARKS: E F INSPECTION	10-13 14-17 18-21 22-29 26-29 30-33 LOCATIOI ELOW SHOW DIST. DICATE NORTH BY CONTRACTOR 3 70.5	BO OF WE ANCES OF WELL F	ELL FROM ROAD ANI	Diofy Lot 3



WATER WELL RECORD

		1. PRINT ONLY IN SP 2. CHECK X CORREC	T BOX WHERE APP		1 1		3502		MUNICIP. 3590 10 BLOCK, TRACT, S	URVEY, ETC.	3 dN 1	LOT	22 23 24
COUNTY OR DI	ISTRICT (enark Eds	TOWNSHIP, BO	ROUGH, CITY,			7	GON. , 1	$\overline{\mathcal{U}}$		COMPLETED	£	3
				J	M, T	- 1	FALL	2 .		DAY_	/8 MO.	No.	YR. 79
				739	120	RC. EL	EVATION 0425		BASIN CODE				1 <u>V</u>
		LO	G OF OVER	BURDEN	AND BE	DROCK	MATERIA						
GENERAL CO	DLOUR COI	MOST MMON MATERIAL	C	THER MATE	RIALS			GENERAL	DESCRIPTION		FRO	EPTH - F	TO
brow	7- 5	soil									С)	/
,.		5 Anos Tone	-								7	/ -	73
			I								-		
									-			-	******
				4946									
									-				
#3	WELL												
				-	_A.							+	
31	0.0044 d a	<u> </u>	 36 1 8							البلن			l L
32	10 14 15]					4		65		75 8
41	WATER R	ECORD	51 CASIN	1G & O	PEN HO		- FEET	W) OF OPENING NO.)	31-33		84-38 LEN	
WATER EQUNI AT = FEET		OF WATER 3 SULPHUR	INCHES	MATERIAL	THICKNESS INCHES	FROM	TO 13-16	ū	RIAL AND TYPE		DEPTH TO OF SCR	NCHES TOP EEN	41-44 8
1070	2 ☐ SALTY	4 MINERAL		TEEL '' ALVANIZED ONCRETE	138	٥	0025	61 P	LUGGIN	2 9 5	EALING	DEC	FEET
20-	2 SALTY	4 MINERAL	7 4 □ C	PEN HOLE	108		20-23	DEPTH S	ET AT - FEET		AND TYPE	(CEMEN	T GROUT,
25-	1 FRESH 2 SALTY	4 MINERAL	3 □ 0	SALVANIZED CONCRETE SPEN HOLE			0073	FROM 10-					
30-	1 G FRESH 2 SALTY	4 ☐ MINERAL	24-25 1 🗆 S	TEEL 26 ALVANIZED			27-30	18-		aol			
b	1 TRESH 2 SALTY	4 MINERAL	4 🗆 c	ONCRETE OPEN HOLE									
1 71 /	TEST METHOD PUMP ² □ B	10 PUMPING RATE	11-14 GPM.	DURATION OF PU	6 0001	7-18 IINS.			OCATION			AND	
N LE	VEL PUI	MPING	R LEVELS DURING	38)	PUMPING		LOT	A NOTE OF	OW SHOW DISTAL	ARROW.	3	2+4	
2030	3 3	5 FEET 030 FE	28 03529-31	45 MINUTES 2	مسدد		، م لاه				, M	3	
Z IF FLOWING GIVE RAT	NG, E	33-41 PUMP INTAKE	SET AT	NATER AT END C		42 0	,o ² 1, (# //	51 OK			
15	ENDED PUMP TYPE	RECOMMENDED		RECOMMENDED PUMPING	4	6-49	`	\setminus :	K//	.13			
50-53	SHALLOW [] [DEEP SETTING	FEET F	RATE		SPM. /	\bigcap	X			6		
FIN		WATER SUPPLY CBSERVATION WE		DONED, INSUF		LY	\geq						
STA OF \	105	TEST HOLE :	7 ☐ UNFIN		WONETT.			•					
14/4	1 :	DOMESTIC STOCK	5 COMMERC	ıL.			4						
	ILEK .	3 ☐ IRRIGATION 4 ☐ INDUSTRIAL	7 ☐ PUBLIC S 8 ☐ COOLING	OR AIR COND		5	۸. `			2			
	57	OTHER CABLE TOOL	6	9 NOT NOT	מאבט	$-\parallel$	417.4 F	Pils					
0	HOD F	²	TIONAL) 7. E) 8	☐ DIAMOND ☐ JETTING			,	11/15					
DRIL		A D ROTARY (AIR) AIR PERCUSSION	9 :	☐ DRIVING		DR	ILLERS REMARI						
e	F WELL CONTRA	**************************************	RISON	,	ENCE NUMBER	ONIC	DATA SOURCE	58 C	3705	59-62 DATE R	203'	71	63-68
ADDRES	S , ,	7	TASI	_				CTION	INSPEC				
 	F DRILLER OR	SOBER .	<u> </u>		ENCE NUMBER	- Ise			/	 _		Р	1,
O SIGNATI	UDE OF CONTRA	стов	SUBMI	ISSION DATE		OFFICE				C 50.0	ść	w	
0	C COP	LOW	AND DAY	МО	YR		'[u ·*		

3/C16E

The Ontario Water Resources Commission Act



WATER WELL RECORD

Water management in O	Ontario 1. PRINT ONLY IN SPACE 2. CHECK X CORRECT	BOX WHERE APPLICABLE 1 2		776 - 351002	CON. 22 23 24
COUNTY OR DISTRICT	+ F + 77 S	TOWNSHIP, BOROUGH, CITY, TOWN, VIL	•	BLOCK, TRACT SURVE	330
L / // / / / / /		Smit			DAY HO WAY YR 70
		73350	RC ELEVATION 5	RC. BASIN CODE	<u> </u>
	LOG	OF OVERBURDEN AND B	EDROCK MATERIA	ALS (SEE INSTRUCTIONS)	
GENERAL COLOUR	MCST COMMON MATERIAL	OTHER MATERIALS		GENERAL DESCRIPTION	DEPTH - FEET FROM TO
brown	soil				0 3
brown	sandstone			1	.3 60
#1					
				-	
31 0003	1492 0060	9/8			
32	14 15 21	32	43	54	65 75 80 31-33 DIAMETER 34-38 LENGTH 39-40
WATER FOUND	R RECORD	TOTAL WALL	DEPTH - FEET	SIZE(S) OF OPENING (SLOT NO.)	INCHES FEET
CO5510-13	MRESH 3 SULPHUR 14	INCHES THICKNESS INCHES 10-11 STEEL 12	FROM TO 13-16	MATERIAL AND TYPE	DEPTH TO TOP 41-44 80 OF SCREEN
15-18	SALTY 4 MINERAL FRESH 3 SULPHUR	S 2 GALVANIZED 781	0 25	61 PLUGGING	
20-23	SALTY 4 MINERAL PRESH 3 SULPHUR	4 OPEN HOLE 17-18 1 STEEL 2 GALVANIZED	20-23	DEPTH SET AT - FEET M	IATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.)
2 🗆	SALTY 4 MINERAL FRESH 3 SULPHUR	3 ☐ CONCRETE 4 OPEN HOLE	0060	10-13 14-17	
30-33	SALTY 4 MINERAL SALTY 34 80 FRESH 3 SULPHUR 34 80	24-25 T STEEL 26 2 GALVANIZED 3 CONCRETE		26-29 30-33 80	
DIMMING TEST METH	SALTY 4 MINERAL	4 OPEN HOLE		10000001	DE WELL COSTH
71 PUMP	2 BAILER 000	05 GPM. 01 15-16 00) 17-18 MINS. IN	DIAGRAM BELOW SHOW DISTANCES	OF WELL 1
STATIC LEVEL	WATER LEVEL 25 WATER 1 PUMPING 22-24 15 MINUTES 26-28	LEVELS DURING 2 RECOVERY 30 MINUTES 45 MINUTES 60 MIN		T LINE. INDICATE NORTH BY ARRO	νw. (43) τοτ 3 - γγομονί
526 FEET	031 FEET 026 FEET	OLG 29-31 OLG 2-34 OLG FEET FEET	G5-37	c ANA -	7 8 8mi
IF FLOWING, GIVE RATE	38-41 PUMP INTAKE SET	FEET WATER AT END OF TEST	OUDY 46-49 R.OF P.		Latoli X
RECOMMENDED PUM	P TYPE RECOMMENDED PUMP DEEP SETTING	43-45 RECOMMENDED PUMPING OS	46-49 GPM.	B	
	OL.O GPM./FT. SPECIFIC		$\exists \mid (\)$		
FINAL STATUS	WATER SUPPLY CBSERVATION WELL	⁵ ☐ ABANDONED, INSUFFICIENT SU ⁶ ☐ ABANDONED, POOR QUALITY	UPPLY)	1	
OF WELL	3 ☐ TEST HOLE 4 ☐ RECHARGE WELL	7 UNFINISHED			
WATER	DOMESTIC STOCK DIRECTION	5 COMMERCIAL 6 MUNICIPAL 7 PUBLIC SUPPLY	.		>
USE O	4 INDUSTRIAL	B COOLING OR AIR CONDITIONING 9 NOT USED		SA, TH FALLS	
METHOD	57 1 CABLE TOOL	6 ☐ BORING		FALLS	Coc or
OF DRILLING	FOTARY (CONVENTION ROTARY (REVERSE) TOTARY (AIR)	NAL) / ☐ DIAMOND 8 ☐ JETTING 9 ☐ DRIVING			
NAME OF WELL C	5 AIR PERCUSSION	LICENCE NUMBI	ER DATA	RKS: SU @ 01/1/510 A . 58 CONTRACTOR 59-62	DATE RECEIVED 20371 63-68 80
o C	U MORK		SOURCE DATE OF INSI	1 3705	1 220011
ADDRESS		ASPEK.	R R		un
NAME OF DRILLE	<i></i>	LICENCE NUMBI	1 1 1		PL
SIGNATURE OF CO	ONTRACTOR .	SUBMISSION DATE DAY MO Y	R. OFFICE		CSS.89 WI
OWRC C				:	Δ

MINISTRY OF THE ENVIRONMENT The Ontario Water Resources Act

ļ	W W	ATER WEL		16 E
-	2. СНЕСК 🗵 СОБ	RRECT BOX WHERE APPLICABLE	3503752 35007 CAN	<u>ا ئى يى ا</u>
	COUNTY OR DISTRICT Langr K	North Elma	CON., BLOCK, TRACT, SURVEY ATC.	2 3-27 2 3-53
		5 Carol	Creseint DAY MO	VR. 4
ſ		973000 185 255 LOG OF OVERBURDEN AND BEDRO	5 26 30 31	47
ł	GENERAL COLOUR MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION FROM FROM	FEET
	Brown Soil		0	Z
	Alua Clar	and Created		100
}	por coup o	and GraveC		14
	White Sandy	Cinestone	14.	136
ŀ				
				· · · ·
ŀ				
Y		1430511 10136111581		
ĺ	41) WATER RECORD	51 CASING & OPEN HOLE	RECORD DEPTH - FEET SIZE(S) OF OPENING SIZE(S) OPENING SIZE(S) O	75 80 NGTH 39-40
Ì	WATER FOUND AND OF WATER 10-13 FRESH 3 SULPHUR 14	DIAM MATERIAL THICKNESS INCHES FR	DEPTH - FEET ROM TO OF SCREEN OF SCREEN	FEET 41-44 80
	2 G SALTY 4 MINERAL 15-18 1 FRESH 3 G SULPHUR 19	000-11 W SPEEL 12 2 GALVANIZED 188 C	61 PLUGGING & SEALING RECOI	FEET
7	2 SLTY 4 MINERAL 20-23 FRESH 3 SULPHUR 24	4 OPEN HOLE 17-18 1 STEEL 2 GALVANIZED	20-23 DEPTH SET AT - FEET MATERIAL AND TYPE (CEMEN	T GROUT, KER, ETC.)
	2 SALTY 4 MINERAL 25-26 1 FRESH 3 SULPHUR 29 2 SALTY 4 MINERAL	3 ☐ CONCRETE 4 ☐ OPEN HOLE 24-25 1 ☐ STEEL 26	10-12 14-17 10-12 12-25	
İ	30-33 1	BO 2 GALVANIZED 3 CONCRETE 4 OPEN HOLE	26-29 30-33 80	
	71 PUMPING TEST METHOD 10 PUMPING RA	// O/ 15-16 () 17-18	LOCATION OF WELL 17	7.3
4	STATIC WATER LEVEL 25 LEVEL PUNPING WATER	PUMPING PUMPING	IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AN LOT LINE. INDICATE NORTH BY ARROW.	0
	F00% (5/7)	ES 30 MINUTES 45 MINUTES 60 MINUTES 6-28 29-31 32-34 50 FEET FEET FEET FEET FEET FEET		1
	TET FEET FEET FEET FEET FEET FEET FEET		. /	
	SHALLOW DEEP SETTING	PUMPING FEET RATE GPM	50'\	
 	54	SPECIFIC CAPACITY 5 ABANDONED, INSUFFICIENT SUPPLY	well \	
	FINAL STATUS OF WELL 4 RECHARGE WELL	VELL 6 ABANDONED, POOR QUALITY 7 UNFINISHED		
- 1				
	55-56 DOMESTIC	5 COMMERCIAL 6 MUNICIPAL	1/2) L	
	1 Z DOMESTIC		the fact	
	WATER USE DOMESTIC CONTROL STOCK GRIGATION INDUSTRIAL OTHER OTHER S7 CABLE TOOL	6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR CONDITIONING 9 NOT USED 6 BORING	ight for	LUS
	WATER USE DOMESTIC STOCK STOCK MERIGATION INDUSTRIAL OTHER OTHER	6 MUNICIPAL 7 PUBLIC SUPPLY 9 COOLING OR AIR CONDITIONING 9 NOT USED 6 BORING ENTIONAL) 7 DIAMOND ISE) 9 DETTING 9 DORIVING	DRILLERS REMARKS:	lus
	WATER USE DOMESTIC DOMESTIC CASIC TOPE OTHER METHOD	6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR CONDITIONING 9 NOT USED 6 BORING ENTIONAL) 7 DIAMOND ISSE) 9 JETTING N	DATA SR CONTRACTOR #59-62 DATE RECEIVED	
	WATER USE DOMESTIC DOMESTIC CASIC TOPE OTHER METHOD	6 MUNICIPAL 7 PUBLIC SUPPLY 8 COOLING OR AIR CONDITIONING 9 NOT USED 6 BORING ENTIONAL) 7 DIAMOND ISSE) 8 JETTING 9 DRIVING	DRILLERS REMARKS: DATA SOURCE SB CONTRACTOR 359-62 DATE RECEIVED 0 7 74 DATE OF INSPECTION INSPECTION	
	WATER USE DOMESTIC DOMESTIC CASIC TOPE OTHER METHOD	MUNICIPAL OUBLIC SUPPLY OUBLIC SUPPLY OUBLING OR AIR CONDITIONING OUBLING OR AIR CONDITIONING OUBLING OUB	DRILLERS REMARKS: DATA SOURCE SB CONTRACTOR SS-62 DATE RECEIVED O 7 74	
	WATER USE WATER USE Domestic Cook IRRIGATION INDUSTRIAL OTHER OTHER OTHER OF OTABY (CONVE) OF OTABY (AIR) OTABY (A	MUNICIPAL OUBLIC SUPPLY OUBLIC SUPPLY OUBLING OR AIR CONDITIONING OUBLING OR AIR CONDITIONING OUBLING	DRILLERS REMARKS: S8 CONTRACTOR 359-62 DATE RECEIVED 0 7 74 DATE OF INSPECTION INSPECTOR REMARKS:	63-68 80

	S AIR PERCOSSION		DRII	LLERS REMARKS					
ב ב ב	ADDRESS F ROCK Drilling Co LTD	l i	SE ONLY	DATA 58 SOURCE DATE OF INSPECTION	CONTRACTOR 1119 NSP	S9-62 DATE RECEIVED 3 0 0	3 7 6	63-68	80
È 2,	HAME OF BRILET OR BORER HOSPET OF	LICENCE NUMBER	CE U	REMARKS:	1			P	
֓֞֝֝֝֟֝֝֟֝ <u>֚</u>	SIGNATURA OF CONTRACTION DES AULA I SUBMISSION D	ATE	OFF			CSS.S8	7	WI	
_	The Comment						FOF	RM 7 MOE 07-	-091

MINISTRY OF THE ENVIRONMENT

The Ontario Water Resources Act
WATER WELL RECORD

FORM 7 MOE 07-091

Ontario		SPACES PROVIDED	[3504]	376 35007	Z CAN	ر. س م ارات
COUNTY OR DISTRICT	4	TOWNSHIP, BOROUGH, CITY, TOWN, VILLA	GE /	SCON., BLOCK, TRACT, SURV	EY. ETC.	LOT 25-2
		Marth F/m	slex		DATE COMPLETED	48-53
		THING R. R. A. 3	Striff S	RC BASIN CODE	DAY 24 MO	3_ YR. 7
	10 12	973200	Ş 6,425	RC BASIN CODE 26 1		
	L	OG OF OVERBURDEN AND BED	DROCK MATERIAL	S (SEE INSTRUCTIONS)	-	
GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS		GENERAL DESCRIPTION	DE FROM	PTH - FEET
	F://				0	3
ares	1 mestage				3	35
0'/	Sand 11				3.5	137
	00,009					
				1.01		
`						
31 000	3 01 1 003	5215 013721581		بليللينيا ليلي	عللتينا ليل	ليليا
32	14 15	32		1		111,
	TER RECORD	51 CASING & OPEN HO	LE RECORD	SIZE(S) OF OPENING	31-33 DIAMETER 34-	
AT - FEET	KIND OF WATER FRESH 3 SULPHUR 4	INSIDE WALL DIAM. MATERIAL THICKNESS INCHES INCHES	FROM TO	MATERIAL AND TYPE	DEPTH TO T OF SCREEN	TOP 41-44
132 196	SALTY 4 MINERAL	10-11 1 STEEL 12 2 GALVANIZED	0025	6		FEET
	FRESH 3 SULPHUR 19 SALTY 4 MINERAL	By 4 OPEN HOLE 188	0 45	61 PLUGGIN	IG & SEALING RE	CORD
	FRESH 3 SULPHUR 24	77-18 1 ☐ STEEL 19 2 ☐ GALVANIZED 3 ☐ CONCRETE	10.23	FROM TO 10-13 14-17		AD PACKER, ETC.)
	FRESH 3 SULPHUR 29	4 OPEN HOLE 24-25 1 STEEL 26	27-30	18-21 22-25		
	FRESH 3 SULPHUR 34	Z GALVANIZED 3 CONCRETE		26-29 30-33 80		
<u> </u>	SALTY 4 MINERAL	4 OPEN HOLE			<u></u>	
71 PUMPING TEST MET	POD 10 PUMPING RA	00 15-16 20	17-18	LOCATION	OF WELL /	773
STATIC LEVEL	WATER LEVEL 25 END OF WATER PUMPING	LEVELS DURING PUMPING RECOVERY	IN DIA LOT LI	GRAM BELOW SHOW DISTANC NE. INDICATE NORTH BY A		AD AND
19-21		1 1	ES 15-37		A1.	
	035 FEET 035 F		42		Λ,	
IF PLOWING. GIVE RATE RECOMMENDED PUR	GPM	FEET 1 CLEAR 2 CLOU			T	
RECOMMENDED PUT	PUMP	A // PUMPING	6-49 GPM.	1		
50-53		PECIFIC CAPACITY] 100	100	r3	
FINAL	1 WATER SUPPLY 2 OBSERVATION WI	5 ABANDONED, INSUFFICIENT SUPP	LY 4	(45)	CONVI	
STATUS OF WELL	3 TEST HOLE 4 RECHARGE WELL	7 UNFINISHED		125	11	
,	DOMESTIC 2 DOMESTIC	5 COMMERCIAL 6 MUNICIPAL			150'	
WATER (3 IRRIGATION 4 INDUSTRIAL	7 PUBLIC SUPPLY 8 COOLING OR AIR CONDITIONING		" N	X	
	OTHER	9 □ NOT USED		# E	CONY.	
METHOD 4	257 I□ CABLE TOOL 2 □ ROTARY (CONVE	6 ☐ BORING NTIONAL) 7 ☐ DIAMOND	1	5.1		
OF DRILLING	3 ROTARY (REVERS	E) 8 1 JETTING 9 DRIVING		/		
	5 AIR PERCUSSION		DRILLERS REMARK			
NAME OF WELL	React Dail	LICENCE NUMBER	DATA SOURCE DATE OF INSPE	1119	3 0 0 6 7	? R
	7.7° ~	07	O DATE OF INSPE	CTION I SPECTOR	2HO	
NAME OF DRILL	EN OR BOWER TO SPEL	LICENCE NUMBER	S REMARKS		10	Р
CONTRACTOR	ace Desage	Laces 1119	0/ OFFICE	(CSS, S8	
200	21 / O . V.	DAY 24 MO. 6 YR	اة اير			WI



The Ontario Water Resources Act

WATER WELL RECORD

114 Saumure Circle Well

Ontario	1. PRINT ONLY IN S 2. CHECK 🗵 CORR	ECT BOX WHERE APPLICABLE		3564601	35007	15 N 30 22 25 27
COUNTY OR DISTRICT		Mental	CITY, TOWN, VILLAGE	USLey	CON., BLOCK, TRACT, SURVEY	DATE COMPLETED 48-63
			3 511		LLS SINCODE	DAY 10 07 76
	M 10 12		3350 5	DHQ5	\$ 216° L	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		OG OF OVERBURD		CK MATERIALS	S (SEE INSTRUCTIONS) GENERAL DESCRIPTION	DEPTH - FEET
GENERAL COLOUS	COMMON NATELINE	OTHER	MATERIALS		GENERAL DESCRIPTION	FROM 10 2
Red	Sand Stor	n P				2 100
bray	Junosio	7.5				
		-				
31 00	0.27.28 01	002/8		البلبليا إ		
32	14 15			PECOED T	SIZE(S) OF OPENING	65 75 80 31-33 DIAMETER 34-38 LENGTH 39-40
41 W	VATER RECORD		G & OPEN HOLE	DEPTH - FEET	Z (SLOT NO.)	INCHES FEET DEPTH TO TOP 41-44 80 OF SCREEN
AT - FEET 10-13	RESH 3 SULPHUR 14	DIAM MATERIA	INCHES 12	0 95	os	FEET
15-18	1 FRESH 3 SULPHUR 15 2 SALTY 4 MINERAL	4 3 CONCR	ETE 00	0025	61 PLUGGIN	NG & SEALING RECORD
20-23	1 FRESH 3 SULPHUR 24 2 SALTY 4 MINERAL	17-18 1 ☐ STEEL 2 ☐ GALVAI 3 ☐ CONCR		20-23	FROM TO 10-13 14-17	MATERIAL AND TYPE LEAD PACKER ETC.)
25-28	1 FRESH 3 SULPHUR 2	9 4 OPEN 1	HOLE 26	27-30	18-21 22-25	
30-33	1 FRESH 3 SULPHUR 3	2	ETE		26-29 30-33 80	
PUMPING TES	T METHOD 10 PUMPING F		ON OF PUMPING		LOCATION	
STATIC LEVEL	WATER LEVEL 25	R LEVELS DURING	1 D PUMPING 2 RECOVERY	IN DIA	AGRAM BELOW SHOW DISTAN INE. INDICATE NORTH BY	CES OF WELL FROM ROAD AND ARROW.
	19-21 22-24 15 MINU	26-28 29-31	MINUTES 60 MINUTES 32-34 35-3	11		
DO S IF FLOWING GIVE RATE		AKE SET AT WATER		12	3	
RECOMMEND	ED PUNP TYPE RECOMME!	NDED 43-45 RECOM	MENDED 46-4	19	0 0	
50-53	LLOW DEEP SETTING	SPECIFIC CAPACITY	002 "		A.	~
FINAL		WELL 6 ABANDONE	D. INSUFFICIENT SUPPLY		1	Ø 3
STATU OF WE	JS 3 TEST HOLE 4 RECHARGE WE	7 🗍 UNFINISHI	EO	198	HOON GWEN / W	<u>→</u>
WATE	2 STOCK I IRRIGATION	5 ☐ COMMERCIAL 6 ☐ MUNICIPAL 7 ☐ PUBLIC SUPPL			MOON	
USE		■ ☐ COOLING OR A			-	
метн	OD 2 ROTARY (CON		IAMON D	71	 	
OF DRILLI	3 G ROTARY (REV	PERSE) 8 🗔 J) 9 🗆 D	ETTING PRIVING	DRILLERS REMA	S Niths	۶
NAME OF	WELL CONTRACTOR	*	LICENCE NUMBER	T DATA	58 CONTRACTOR 558	9-62 DATE RECEIVED 63-68
E ADDRESS	- Swac		2131	SOURCE DATE OF INS	SPECTION INSPECTO	96
ON SIGNATURE OF SI	DRILLER OD RER	anes'	LICENCE NUMBER	S REMARKS	4.5/11	P/15
NO SIGNATU	RE OF CONTOR	ypr submissio		OFFICE		CSS.S8 WI
$ \cdot \langle \omega \rangle$	it sold	DAY 2		실 [의		FORM 7 MOE 07-0

MINISTRY OF THE ENVIRONMENT The Ontario Water Resources Act WATER WELL RECORD

DEPTH - FEET OM TO 3 2 2 /2 34-33 LENGTH NCHES
044 YR
3 2 2 2 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
3 2 2 2 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
3 2 2 2 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
2 /2 34-38 CENGTH
34-31 CENGTH
TO TOP 41-4 EEN FE
RECORD
(CEMENT GROU- LEAD PACKER, ET
ROAD AND
A 1
\mathcal{N}
11
\
6:
377
Р

The Ontario Water Resources Act 3/C/6 WATER WELL RECORD

NTY OR DISTRICT	1	TOWNSHIP, BOROUGH, CITY	, TOWN, VILLAGE	,	CON., BLOCK, TE	RACT, SURVEY ETC.	10	LOT 25-2
/	.k	Vort	Elm	s ley		JATE DATE	COMPLETED	
		RR.	73 Jap	it/s to	1/e On T.	DAY_	29 mP3	yr. Z
	" 10	772	799		5 4 KG			
		G OF OVERBURDEN	AND BEDR	OCK MATERIA			DEPTH	- FEET
NERAL COLOUR	MOST COMMON MATERIAL	OTHER MAT	ERIALS		GENERAL DESCR	IPTION	FROM	то
	clay						0	11
grey	l'inestone						90	90
7 ///	Sand3/one						70	1-11
	1							
					A			1
							1 1 1	\{\alpha\}_{\alpha\}
			****					1
D bout	1 02 1 0096	215 0144	1210		1.1.111	1,1,1,11		<u> </u>
2 1 2	102 0094		70	J [1111]				
wa-	TER RECORD	CASING &	OPEN HOLE	RECORD	SIZE IS L OF OPEN	ING 31-33	DIAMETER 34-38	LENGTH 3
ATER FOUND AT - FEET	KIND OF WATER	INSIDE DIAM MATERIAL INCHES	WALL THICKNESS INCHES	DEPTH - FEET FROM TO	MATERIAL AND	TYPE	DEPTH TO TOP OF SCREEN	41-44
	FRESH 3 SULPHUR SALTY 4 MINERAL	OG 11 1 KSTEEL 1	2	13 -1	. O			FEET
	FRESH 3 SULPHUR 19 SALTY 4 MINERAL	3 CONCRETE OPEN HOLE	188	0 002 2	.	LUGGING & S		ORD
20-23	FRESH ³ □ SULPHUR ²⁴ □ SALTY ⁴ □ MINERAL	1 ☐ STEEL 1 2 ☐ GALVANIZED 3 ☐ CONCRETE				O MATERIA	L AND TYPE LEAD F	ACKER, ETC.)
25-28 1 2] FRESH 3] SULPHUR ²⁹] SALTY 4] MINERAL	4 OPEN HOLE	5	27-3	0 18-21	22-25		
30-33] FRESH 3] SULPHUR 34 60] SALTY 4] MINERAL	2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE			26-29	30-33 80		
UMPING TEST ME	THOD 10 PUMPING RATE			1	LOCAT	ION OF W	ELL	
1 DE PUMP	2 ☐ BAILER OO	1 🛣	-16 30 17-11 URS 30 MINS	INC	DIAGRAM BELOW SHOW	DISTANCES OF WORTH BY ARROW.	ELL FROM ROAD	AND
19-21 0/0	END OF WATER LI	30 MINUTES 45 MINUTES 29-31 33	RECOVERY 60 MINUTES 2-34 35-3		LINE. INDICATE N	ORIH BI ARROW.		,
O/O FEET	المما	1025 FEET F	EET FEE	т .			λ	/
IF FLOWING, GIVE RATE RECOMMENDED PU	GPM	FEET 1 CX CLEAR	2 CLOUDY	-1 i			1	
RECOMMENDED PU	PUMP	PUMPING	009 GP		XV2		•	
50-53]				
FINAL STATUS	1 W WATER SUPPLY 2 OBSERVATION WEL				80'7			
OF WELL	3 TEST HOLE 4 RECHARGE WELL	7 UNFINISHED		11	2	,))		
WATER	DOMESTIC	5 COMMERCIAL 6 MUNICIPAL 7 DUBLIC SUPPLY	**			/ //		
USE	4 INDUSTRIAL OTHER	8 COOLING OR AIR CONE				(//		//.
METHOD	57 1 CABLE TOOL	6 BORING		11	*	Sni		#
	2 ROTARY (CONVENT 3 ROTARY (REVERSE 4 ROTARY (AIR)	10NAL) 7 ☐ DIAMOND) 8 ☐ JETTING 9 ☐ DRIVING			•	, e		
DRILLING	5 AIR PERCUSSION	· · · · · · · · · · · · · · · · · · ·		DRILLERS REM				-
NAME OF WELL	CONTRACTOR A Da-	1/ing CalTD	1/1 9	DATA SOURCE	58 CONTRACTO	_	0.604°	1
NAME OF DRILL	FO Too	B.T.		O DATE OF IN	SPECTION	INSPECTOR	Kn/	, -0
NAME OF DRILL	ER OR BORER 105 DE	/ Un I	ICENCÉ NUMBER	OFFICE USE			- Andrew	
1 / /	/ 1/1	/ - ~ +	11.0-	네팅(1)				

The Ontario Water Resources Act 31016 WATER WELL RECORD

Ontario 1. PRINT ONLY IN SPACES PROVIDED 11 3505040 3505040	CAN 05
2 CHECK CORRECT BOX WHERE APPLICABLE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE COUNTY OR DISTRICT TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE TOWNSHIP, BOROUGH, CITY, TOWN VILLAGE	<i>ဝ</i> ဝီ <u>ဒ</u> ီ"
on the Full S	е сомретер 48-53 ОН мо 06 уг/8
7299 5 0925 5 26	11 11 12
LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)	DEPTH - FEET
GENERAL COLOUR COMMON MATERIAL OTHER MATERIALS GENERAL DESCRIPTION	FROM TO /29
BRN SMND STON 2	
Jun 0 4 mm	•
, which is a second of the sec	
	(5.70)
	Recit
31 bu 24618 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	65 75 80
1 Z 10 14 15 21 32 SIZE(S) OF OPENING 31-3	INCHES FEET
WATER FOUND AT - FEET TO THE TOWN MATERIAL INCHES THE TOWN MATERIAL AND TYPE THE TO	DEPTH TO TOP 41-44 50 OF SCREEN
6-1 TA STEEL	& SEALING RECORD
4 FT OPEN HOLE	ERIAL AND TYPE (CEMENT GROUT LEAD PACKER, ETC.)
2 SALTY MINERAL 3 CONCRETE 10-13 14-17 15-28 1 FRESH 3 SULPHUR 25 4 OPEN HOLE 27-50 18-21 22-25	
2 SALTY 4 MINERAL 2 SALTY 4 MINERAL 2 GALVANIZED 30-33 1 FRESH 3 SULPHUR 34 00 3 CONCRETE 2 GALVANIZED 26-29 30-33 60	
2 SALTY 4 MINERAL 4 OPEN HOLE	WELL
1 DIAGRAM BELOW SHOW DISTANCES	OF WELL FROM ROAD AND
STATIC WATER LEVELS DURING LEVEL WATER LEVELS DURING LEVEL PUMPING WATER LEVELS DURING RECOVERY	ow.
8 0/0 FEET 060 7EET 06032.34 06035.37	
IF FLOWING. SO-41 PUMP INTAKE SET AT WATER AT END OF TEST	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
RECOMMENDED PUMP TYPE PUMP RECOMMENDED PUMP PUMP PUMP SETTING FEET RATE OF PAMP	IMIL
FINAL STATUS OF WELL So-53 FINAL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STATUS OF WELL STOCK OF MUNICIPAL	
FINAL STATUS 1 WATER SUPPLY 5 ABANDONED, INSUFFICIENT SUPPLY 2 OBSERVATION WELL 6 ABANDONED, POOR QUALITY 3 TEST HOLE 7 UNFINISHED	
OF WELL • RECHARGE WELL 55:56 1 P DOMESTIC 5 COMMERCIAL	
WATER 01 S INSTRIAL DESCRIPTION OF PUBLIC SUPPLY INSTRIBLE OF INDUSTRIAL DESCRIPTION OF THE PUBLIC SUPPLY	/ / ///
OSE OTHER ONT USED	Smrth alls
METHOD CABLE TOOL 6 BORING	
DRILLING A GROTARY (AIR) DRIVING AIR PERCUSSION DRILLERS REMARKS:	TAY'E RECEIVED 63.68 80
NAME OF WELL CONTRACTOR	1 606 7 8
ADDRESS ADDRESS LICENCE NUMBER DATE OF INSPECTION INSPECTOR INSPECTOR	. 8
ADDRESS NAME OF DRILLER OR BORER SIGNATURE OF CONTRACTOR SUBMISSION DATE SUBMISSION DATE SUBMISSION DATE SUBMISSION DATE SUBMISSION DATE SUBMISSION DATE	en en en en en en en en en en en en en e
S SCHATURE OF CONTRACION SUBMISSION DATE	CSS.58

The Ontario Water Resources Act WATER WELL RECORD

FORM NO. 0506-4-77 FORM 7

3505850 Ontario . PRINT ONLY IN SPACES PROVIDED 2. CHECK X CORRECT BOX WHERE APPLICABLE TOWNSHIP ROPOLICH CITY TOWN COUNTY OR DISTRICT DAY 18 40 1 LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS) DEPTH GENERAL DESCRIPTION MOST COMMON MATERIAL OTHER MATERIALS GENERAL COLOUR 00 71 0112215 **(31)** 0071 24 32 34 - 38 CASING & OPEN HOLE RECORD 51 SCREEN 41 WATER RECORD KIND OF WATER DEPTH TO TOP OF SCREEN FRESH 3 SULPHUR
SALTY 4 MINERAL 0110 1 | FRESH 3 | SULPHUR
2 | SALTY 4 | MINERAL 61 **PLUGGING & SEALING RECORD** DEPTH SET AT - FEET MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.) FRESH 3 SULPHUR
SALTY 4 MINERAL FROM GALVANIZED CONCRETE 1 FRESH 3 SULPHUR
2 SALTY 4 MINERAL OPEN HOLE 18 - 21 22.25 ☐ GALVANIZED 30.33 26.29 1 ☐ FRESH 1 ☐ SULPHUR CONCRETE Z [] SALTY 4 [] MINERAL LOCATION OF WELL 71 O/ 15-16 HOURS 00/0 2 🕱 BAILER 1 🗆 PUMP IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE INDICATE NORTH BY ARROW. PUMPING RECOVERY WATER LEVEL END OF PUMPING WATER LEVELS DURING 15 MINUTES | 30 MINUTES *م*ک ٿڙ 03 00 0° 020 00 PUMPING PUMP INTAKE SET AT IF FLOWING 90 1 DYCEAR RECOMMENDED PUMP SETTING RECOMMENDED PUMP TYPE FEET PUMPOO SHALLOW : | MATER SUPPLY
2 | CBSERVATION WELL 5 ABANDONED, INSUFEICIENT SUPPLY FINAL 4 ABANDONED, POOR QUALITY
7 UNFINISHED STATUS 3 TEST HOLE OF WELL . RECHARGE WELL DOMESTIC COMMERCIAL MUNICIPAL 2 STOCK 3 | IRRIGATION WATER PUBLIC SUPPLY USE /5 COOLING OR AIR CONDITIONING

9 not used OTHER 6 | BORING
7 | DIAMOND
8 | JETTING ABLE TOOL METHOD ROTARY (CONVENTIONAL)

ROTARY (REVERSE) OF 4 | ROTARY (AIR)

8 | AIR PERCUSSION 9 DRIVING DRILLING DRILLERS REMARK SE CONTRACTOR ONLY 1707 171 CONTRACTOR DATE OF INSPECTION USE LICENCE NUMBE REMARKS OFFICE DAY 26

THE ENVIRONMENT COPY

MINISTRY OF



The Ontario Water Resources Act 3) C/66 WATER WELL RECORD

FORM NO. 0506—4—77 FORM 7

Ontario		N SPACES PROVIDED RRECT BOX WHERE APPLICABLE		35064	96	350/0	CON	,, 06
COUNTY OR DISTRICT	1.10	TOWNSHIP BOROUGH CITY	TOWN WILAGE	9 M e	CON	BLOCK, TRACT, SURVEY	<u> </u>	Φ3 ö "
		3 < 3	ρ.	In o		i	DATE COMPLETED	1000 82
		7.74	199	5 04/5	آگل اُ	26	" ""	iv i
	L	OG OF OVERBURDEN	AND BEDR	OCK MATERIA	LS (SEE)	31		
GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MAT	ERIALS		GENER	AL DESCRIPTION	DE FROM	EPTH - FEET
15RV	Smuls	6× -					0	/14

				•				
							140	
								§
31) 1911/4	AG 1.8] [] []			11,,,11,	1,1,1
32	14 15 21	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		اللسيال	111	54	بللسيا ل	111
WATER FOUND	TER RECORD	CASING &	OPEN HOLE	RECORD DEPTH - FEET	Ш	S) OF OPENING \$1-3 (NO)	34-	
AT - FEET	FRESH 3 SULPHUR 14	DIAM MATERIAL INCHES 10-11 1 STEEL 12		FROM TO 13-16	SCB	RIAL AND TYPE	DEPTH TO T OF SCREEN	
15-18	SALTY MINERAL SULPHUR ST	OS GALVANIZED CONCRETE OPEN HOLE	188	0 0000	61	PLUGGING 8	k SEALING RE	
20-23	SALTY ⁴ MINERAL FRESH ³ SULPHUR ²⁴	17-18 I STEEL IS	1	20-23	DEPTH :	SET AT - FEET MATE		CEMENT GROUT AD PACKER ETC :
25-28 1	SALTY 4 MINERAL FRESH 3 SULPHUR 29	3 CONCRETE 4 OPEN HOLE 24-25 1 STEEL 26		27-30		0-13 14-17 0-21 22-25		
30-33 1] SALTY 4 MINERAL] FRESH 3 SULPHUR 34	2 GALVANIZED 3 GONCRETE				-29 30-33 80		
PUNPING TEST NET	SALTY 4 MINERAL THOD 10 PUMPING RAT	□ OPEN HOLE 11-14 DURATION OF PL	MPING			OCATION OF	WELL	
1 DUMP	WATER LEVEL 25	О _{БРМ} О 15-1	16 0 0 17-18 18 MINS PUMPING			OW SHOW DISTANCES O		AD AND
LEVEL	END OF WATER		RECOVERY 60 MINUTES		INE. IND	DICATE NORTH BY ARRO	w .	
19-21 ORO FEET OF FLOWING. GIVE RATE RECOMMENDED PUS	07- 5 0 25	SET AT WATER AT END	P & 3,	.	;	\ .		
F FLOWING. GIVE RATE RECOMMENDED PUR	GPM S	FEET 1 DELEAR	2 CLOUDY			X /2 /47		
SHALLOW	PUMP	D 43-45 RECOMMENDED PUMPING DOC RATE	95 "···	11		15	Od T	
	1 WATER SUPPLY] 		X THINH	1-+4.	•.
FINAL STATUS	2 OBSERVATION WE	\$ ☐ ABANDONED, INSUF ELL \$ ☐ ABANDONED POOR 7 ☐ UNFINISHED				<i></i>		
OF WELL	4 RECHARGE WELL	5 COMMERCIAL		1			. /	
WATER USE	2 STOCK 3 IRRIGATION 4 INDUSTRIAL	MUNICIPAL PUBLIC SUPPLY COOLING OR AIR CONDI	TIONING				3 Wirs To	5 m
002 (/)	OTHER	• □ NOT					43	-:/1
METHOD OF	CABLE TOOL CONVEN CONVE						3 h/rs 50 43 h/4h	vu,
DRILLING	4 ROTARY (AIR) 5 AIR PERCUSSION	DRIVING		DRILLERS REMARK	s			1
NAME OF WELL	CONTRACTOR	Lic	ENCE NUMBER] []DATA		1707 S9-62 DAY) RECEIVED A C	0.0
ADDRESS	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		<u> </u>	SOURCE SOURCE	CTION	INSPECTOR	, o 00	83
NAME OF DRILLE	ER OR BORER		ENCE NUMBER	O REMARKS				
SIGNATURE OF C	CONTRACTOR	SUBMISSION DATE	2.	OFFICE			CSS	S.ES
	たび マンロル	name law 11 va	1 35	110			_	

The Ontario Water Resources Act WATER WELL RECORD

Ontario	1. PRINT ONLY IN SPA		11	35082	04	MUNICIP	CON.		 .
COUNTY OR DISTRICT	2. CHECK A CORRECT	TOWNSHIP, BOROUGH, CITY,	TOWN. VILLAGE		CON	BLOCK, TRACT, SURV	EY ETC		22 23 LOT 25-2
		200	Magu	<u>. </u>		6			30
		-	8	H. E	1/2	9,7	DAY) NO	<u>"</u> "
		ING	<u> </u>	ELEVATION	PC I	BASIN CODE	" '	100	
1 2 -18	18	17 18	1 121 121	1 11111	30	31			
		OF OVERBURDEN A	AND BEDRO	OCK MATERIAL	LS (SEE)	NSTRUCTIONS) -	<u>. 4.</u>		
GENERAL COLOUR CO	MOST JAINTEN NOMMO	OTHER MATE	RIALS		GENER	AL DESCRIPTION		DEPTH FROM	- FEET
eli	ev & 87000 .							0	12
:	Scarled							17	14
2000	0 0			-				111	20
gray tolan	r. samero	re						-77	10
, , , , , , , , , , , , , , , , , , ,									
									:
		`.							
								<i>,</i>	
									-
									-
- I		1 1 1 1 1			1 11	111		1 1 1	1 1 1
31					الللا			1111	ا للا
32 10 14 15				13-1111		54 OF OPENING	31-33 DIAMET	ER 34-38 L	75 ENGTH 39-
41 WATER R	 	51 CASING & O		RECORD	Z (SLOT	NO)	DIAMEI		
AT - FEET	OF WATER		THICKNESS	см то	SC WATE	RIAL AND TYPE		DEPTH TO TOP OF SCREEN	41-44
FRESH 2 SALTY	4 MINERALS 6 GAS	10-11 1 STEEL 12 GALVANIZED		13 -16	S				FEET
IS-18 FRESH 2 SALTY	4 DMINERALS	3 CONCRETE 4 COPEN HOLE 5 CPLASTIC	188 (3 22	61	PLUGGIN	G & SEALI	NG RECO	RD
20-23 1 _ FRESH		1 STEEL 19	, ,	20-21	DEPTH S	ET AT - FEET	MATERIAL AND		NT GROUT, CKER, ETC.)
2	6 GAS	3 □ CONCRETE 4 □ OPEN HOLE 5 □ PLASTIC			10	-13 14-17			
2 SALTY	4 □ MINERALS 6 □ GAS	24-25 1 STEEL 26		27-30	18	21 22-25			
30-33 1 FRESH 2 SALTY	3 □SULPHUR 34 BO 4 □ MINERALS 6 □ GAS	3 □ CONCRETE 4 □ OPEN HOLE 5 □ PLASTIC			26-	29 30-33 80			
PUMPING TEST METHOD	10 PUMPING RATE	11-14 DURATION OF PUMI	PING						-
1 1 PUMP 2 0 8/	AILER	20 GPM HOURS	17-18 	:	L	O'CATION () F WELL		
STATIC WATER END LEVEL PUMP	OF WATER LEVEL	LS DURING # □ RI		IN DIAG	GRAM BELO NE. IND	IW SHOW DISTANCI ICATE NORTH BY A	ES OF WELL F RROW.	ROM ROAD A	ND
TE FLOWING. TE FLOWING. RECOMMENDED PUMP TYPE		30 MINUTES 45 MINUTES 29-31 32-34	60 MINUTES					/	
J FEET 40	FEET LO FEET 4		TEST 42					N.	
GIVE RATE	GPM GPM	ĺ	. CLOUDY					11	
RECOMMENDED PUMP TYPE	RECOMMENDED .	43-45 RECOMMENDED	46-49			11.			
SHALLOW A DE	EEP SETTING S	O FEET RATE 2	9 GPM			80			
54						A			
CTATUC 2	WATER SUPPLY OBSERVATION WELL	ABANDONED, INSUFFI ABANDONED POOR QU							
OF WELL	TEST HOLE RECHARGE WELL	, UNFINISHED 9 DEWATERING			XX	4 mil	e		
1.		COMMERCIAL MUNICIPAL			×>				
WATER ,	☐ IRRIGATION 7	Dublic Supply Cooling or Air Condition	ONING			XXX .		1.0	
	OTHER	9 NOT U			•	XX			
	CABLE TOOL	■ □ BORING				1. X	×		
OF ,	ROTARY (CONVENTION. ROTARY (REVERSE)	■ □ JETTING				·	•		
CONSTRUCTION	☐ ROTARY (AIR) AIR PERCUSSION :	• □ DRIVING □ DIGGING □	OTHER	DRILLERS REMARKS	5 :			110	15
NAME OF WELL CONTRAC	TOR	WELL C	ONTRACTOR'S	I DATA		ONTRACTOR 59-62	DATE RECEIVED		63-68
5 Air-Ro	& Drillin	a GLTD. LICENCE	E NUMBER	SOURCE			JAN	0 8 1988	3
NAME OF THE PRINCE	7 4. 4	19 T	· 7	DATE OF INSPEC	TION	INSPECTOR			
NAME OF WELL TECH	NICI DE PER	WELL T	ECHNICIAN'S	M REMARKS		L			
SIGNATURE OF TECHNIC	Gal Way	SUBMISSION DATE	005	OFFICE				CSS.	FC
		, pare		:				~ ~ ~	

			*			
	linistry f the	\A/A7		ntario Water Resourc		
	nvironment	WAI	EK	WELL	RECC	טאי
ornano <u>s</u>	1. PRINT ONLY IN	SPACES PROVIDED	35096	49 35007	CON	1 65
COUNTY OR DISTR	ict ~ L	TOWNSHIP, BOROUGH CITY, TOWN, VILLAGE	Inola	CON . BLOCK, TRACT. SURVEY	ETC ETC	10T 33.17 7-2
1 1122			til T	1/ 00	DATE COMPLETED DAY 23 MO	4.53 90
			ELEVATION	RC BASIN CODE	DAY MO	Y YR. 10
<u> </u>	10 12	OG OF OVERPHEDEN AND REDDO	L L	1.5		
GENERAL COLO	UR NOST	OG OF OVERBURDEN AND BEDRO	JCK MIATERIA	GENERAL DESCRIPTION		1 - FEET
	clay X 9 C	1/4/			FROM	28
950	3 modest on		:		28	158
4.7				, A.		7.00
	The state of the s					
						-
						-
<u> </u>			-			
31		4444	ليللسا	لللبلليبا لبل	بليللينيا لي	
32 10 N	VATER RECORD	51 CASING & OPEN HOLE	Li Li	SIZE S. OF OPENING 3	55 1-33 DIAMETER 34-38	75 80 LENGTH 39-40
WATER FOUND AT - FEET	KIND OF WATER	INSIDE WALL INCOMESS	DEPTH - FEET	!!	INCHES	FEET
14/5	FRESH 3 SULPHUR 4 MINERALS 6 GAS	10-11 14 STEEL	13-16	MATERIAL AND TYPE	DEPTH TO TOP OF SCREEN	41-44 30 FEET
150	FRESH 3 SULPHUR 19	2 GALVANIZED 3 GONCRETE 4 GOPEN HOLE 5 DPLASTIC	33	61 PLUGGING	& SEALING RECO	RD
20-23	FRESH 3 SULPHUR 24	17-18 1 DSTEEL 2 DGALVANIZED 3 DCONCRETE	20-23	DEPTH SET AT - FEET MA		NT GROUT
	FRESH 3 SULPHUR 29	4 OPEN HOLE 5 PLASTIC	27-30	10-12 14-17		
30-33	FRESH 3 SULPHUR 34 SC	2 □ GALVANIZED 3 □ CONCRETE 4 □ OPEN HOLE		26-29 30-33 80		
PHIMPING TEST	GAS GAS	5 PLASTIC		10047108101		
71 / A PUM	P 2 BAILER	12 GPM 15-16 17-18 HOURS MINS	IN DIA	LOCATION OF		ND.
LEVEL	WATER LEVEL 25 END OF WATER L PUMPING 15 MINUTES	EVELS DURING PUMPING PRECOVERY 30 MINUTES 45 MINUTES 60 MINUTES		NE INDICATE NORTH BY ARR		
	FEET SO FEET SOFE	ET SORET SORET SORET		7	a/.	
IF FLOWING.	36-41 PUMP INTAKE	SET AT WATER AT END OF TEST 42			1	
RECOMMENDED	PUMP TYPE RECOMMENDED PUMP SETTING				/	
10-51		GFM			 	
FINAL STATUS	1 WATER SUPPLY 2 OBSERVATION WEI			_	11	
OF WEL	L 4 RECHARGE WELL	7 UNFINISHED DEWATERING				
WATER	D STOCK	5 COMMERCIAL 6 MUNICIPAL 7 PUBLIC SUPPLY		120/2		
USE	4 INDUSTRIAL OTHER	DOCUMENT OF AIR CONDITIONING To not used		16K,	-1	
			1		·	- 1

DRI	LLERS REMARKS						48230
USE ONLY	DATA SOURCE DATE OF INSPECTION REMARKS	54	CONTA	1	1 mspe	9	TAN 1 8 1991
OFFICE							CSS.ES

♥ Ontario

Ministry of the Environment

Print only in spaces provided.

Mark correct box with a checkmark, where applicable.

			WAILE	, AA EET	- neo	JND
11 2	351351	9	Municipality 3500	Con.	Y	22 23 24
nship/Borough/City/Tow	nVillage Emsle	4	Con block t	ract survey,	etc. Lot	25-27
5mth	sFalls	, D~	ナ	Date completed C	27 08	م الله الله الله الله الله الله الله الل
Northing	RC Elevation	RC	Basin Code			iv L L L L

County or District		Township/Borough/City/	Town/Village	20 51 01.	Con bloc	tract survey,	etc.	ot 25-27
		Address	1 ~ ~	- 00	~ +	Date completed (27 r	200 B
		Northing	15 to	C Elevation	RC Basin Code	ii	day	nonth year
21	W 10 12 12		24 25		30 31			1 1 1 47
General colour Most comm		RBURDEN AND BEDR Other materials	OCK MATE		eneral description			th - feet
General colour	Jul 400 1	Outer materials					From	5
Sanc	19301	actor a					5	85
Bray Samo	29 1770	esturce	+				25	16
Jun	10514	3			***	·	23	163
,								

31			لتتناك	البلبلا		ـــا لـــــ	لىلك	ا لىلىـ
32		32	لــــــا اـــــــا		54		ليلا	75 80
41 WATER RECORD Water found Kind of water	Inside	SING & OPEN HOLE I	RECORD Depth - f		Sizes of opening Slot No.)	31-33 Diameter	34-38 Len	gth 39-40 feet
10-13 Frest Sulph	inches 10:11 10:11	Material thickness inches Steel 12	From	To 13-16	Material and type		Depth at top	
2 Saity Gas	2 3	Galvanized Concrete Open hole	\wedge	, > 🖺				feet
2 Salty 2 Minter	gls D 6 / 4 5 17-18 1 1	Plastic 19		20-23	PLUGGING Annular space	& SEALING	RECOR!	
20-23 1 Fresh 3 Sulph 2 Salty 6 Gas	ur 24 83 3	Galvanized Concrete Open hole	0	ZO Fro	oth set at - feet Mai	erial and type (Ce		
25-28 1 Fresh 3 Sulph	ur 29 9 5 🗆	Plastic Steel		27-30	10-13 み 27 C	emen	<i>t q</i>	rout
30-33 1 Fresh 3 Sulph	ur 34 60 L 2	Galvanized Concrete Open hole	20/1	17 < L	18-21 22-25 26-29 30-33 80			
² □ Salty ₆ □ Gas		Plastic						
71 Pumping test method 10 Pum Pump 2 Bailer	ping rate OO GPM Du	ration of pumping 15-16 17-18 Hours Mins			LOCATION OF			
	/ater levels during 1 ☐ Pu			In diagram belov Indicate north by	v show distances v arrow.		١	ot line.
	26-28 29-31	minutes 32-34 60 minutes 35-37				. 50		12
	p intake set at Wa	feet feet ter at end of test	١,		لو	-		1
		☐ Clear Cloudy lecommended 46-49	'	\	JA X	9.)	
Shallow Deep pum	setting SO feet P	ump rate GPM		\	901			
FINAL STATUS OF WELL	54							
2 ☐ Observation well 6 ☐ A	Abandoned, insufficient supply Abandoned, poor quality Abandoned (Other)	9 ☐ Unfinished 10 ☐ Replacement well		\ _				
4 Recharge well 8 C	Dewatering			1				
WATER USE Domestic 5 🗆 G	55-56 Commercial	9 🗀 Not use		\				
3 ☐ Irrigation 7 ☐ 8	Municipal Public supply Cooling & air conditioning	10 Other		\				
METHOD OF CONSTRUCTION	M 67			\		*		
	Air percussion	9 Driving 10 Digging		/	11			
3 ☐ Rotary (reverse) 7 ☐ B 4 ☐ Rotary (air) 8 ☐ 3	Diamond	11 Other		(431		234	361
Name of Well Contractor	т.	Well Contractor's Licence No.	Data	58 Cont	tractor	59-62 Date rece	ived	63-68 80
Aireach	Myblta	1 419	Source Date of	of inspection	1 1 1 9 Inspector	OCT	09	2001
18R+2 TO	sper l	ont'	I SE		Парасто			
Name of Well Technician	Driers	Well Technician's Licence No.	Remai	rks				
Signature of Teath of Connact	1	Submission date	MINISTRY					
William		day ino yr	-					

2 - MINISTRY OF THE ENVIRONMENT COPY

0506 (07/00) Front Form 9

♥ Ontario Ministry of the

Environment

WATER WELL RECORD 3513956 Print only in spaces provided. 35007 CON LOG Mark correct box with a checkmark, where applicable. 11 County or District Con block tract survey, etc. Township/Borough/City/Town/Village oods North Elmole (O O Ž completed 21 \Box ليسسيا LOG OF OVERBURDEN AND BEDROCK MATERIALS (see instructions) Depth - feet General colour Most common material From 2 0 roche 141 WATER RECORD CASING & OPEN HOLE RECORD (Slot No.) Water found Wall thickness Depth - feet Material From inches 1 ☐ Fresh 3 ☐ Sulphur 2 ☐ State ☐ Minerals ☐ Gas Depth at top of screen Steel Galvanized 3 Concrete
4 Open hole
5 Plastic 188 22 D bŦ **PLUGGING & SEALING RECORD** 1 Steel
2 Galvanized
3 Concrete Annular space 3 Sulphur
4 Minerals
6 Gas 1 🗆 Fresh Depth set at - feet Material and type (Cement grout, bentonite, etc.) 2 Salty SO \bigcirc From Sulphur Minerals Gas □ Fresh <u>taro</u> 1 Steel
2 Galvanized
3 Concrete
4 Gopen hole
5 Plastic 2 | Salty 30-33 1 Fresh
2 Salty Ю 20 141 26-29 30-33 Pumping test method

Pump 2 Bailer Pumping rate **LOCATION OF WELL** 50gpm 17-18 Mins In diagram below show distances of well from road and lot line. Indicate north by arrow. Water level end of pumping 1 Pumping Water levels during 15 minutes 26-28 30 minutes 29-31 60 minutes 45 minutes 2 25_{feet} Water at end of test Pump intake set at Cloudy
46-49 ☐ Clear **GPM** 43-45 Recommended pump type pump setting 130 feet pump rate ☐ Shallow ▲ Deep 50 FINAL STATUS OF WELL 1 Water supply
2 Observation well
3 Test hole
4 Recharge well WATER USE

1 Domestic
2 Stock 55-56 5 Commercial
6 Municipal
7 Public supply
8 Cooling & air conditioning METHOD OF CONSTRUCTION 57 5 Air percus
6 Boring
7 Diamond
8 Detting 9 Driving
10 Digging
11 Other 248196 Well Contractor's Licence No.

Well Technician's Licence No Submission da

ONLY	Data source	58 Contractor	19	59-62 Date rece	0 4	2002	80
USE	Date of inspection		Inspector				
1.	Remarks						
MINISTRY							
ئے					0506 (0	07/00) Front Form	m 9

Ministry of the Environment, Conservation and Parks

Well Tag No. (Place Sticker and/or Print Below)

Tag#: A 228111

Well Record

Regulation 903 Ontario Water Resources Act Page of

Address of Well Location (Street Number/Name)	Township Drymond 1	V. Flash 2	Concession?
County/District/Junicipality	City/Town/Village		Province Postal Code Ontario
UTM Coordinates Zone, Easting NAD 8 3 14 17350 4 9 73 226	Municipal Plan and Sublo	t Number	Other Other
Overburden and Bedrock Materials/Abandonment Sealing Rec		The state of the s	
General Colour Most Common Material O	ther Materials	General Description	From 15
Gray Limestone			5 22
Gray Linestone			2280
bray Drown Sandstone			42 144
CHIOIZO	n Rezid	uals allalle	cted
) / / /
And Records	- A 1+1- 12	> Flilisiams P	2 1721
Annular Space		Results of W	2-46 L NIT 5-54 SAMON S 144 MAN
Depth Set at (m/ft) Type of Sealant Used From To (Material and Type)	Volume Placed (m³/ft³)	After test of well yield, water was:	Draw Down Recovery Time Water Level Time Water Level (min) (m/ft) (min) (m/ft)
U 22 (hich	$\frac{3}{B \cdot a}$	☐ Other, specify If pumping discontinued, give reason:	(min) (m/ft) (min) (m/ft) Static
Grout	Dass	0	1 18 1 17
		Pump intake set at (m/tt)	2 1
Method of Construction Well U	en ji name ili namani, sulamme kasuula mese	Pumping rate (Vmin / GPM)	3 9 3 /
☐ Cable Tool ☐ Diamond ☐ Public ☐ Comm ☐ Rotary (Conventional) ☐ Jetting ☐ Domestic ☐ Municiple ☐ Rotary (Reverse) ☐ Driving ☐ Livestock ☐ Test Hx	pal Dewatering	Duration of pumping hrs + min	5 16 5 17
	g & Air Conditioning	Final water level end of pumping (m/ft)	
Other, specify Other, specify	Status of Well	If flowing give rate (lymin / GPM)	15 15 17
Inside Open Hole OR Material Wall Depth (m/ft) Diameter (Galvanized, Fibreolass, Thickness	Water Supply Replacement Well	Recommended gump depth (m/ft)	20 [7 20]
(cm/in) Concrete, Plastic, Steel) (cm/in) From To	Test Hole Recharge Well	Recommended pump rate	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
618 31221 180 0 22	Dewatering Well Observation and/or	(Vmin / GPM) 15 CCM	40 7 40 17
	 Monitoring Hole ☐ Alteration 	Well production (Vmin (GPM)) Disinfected?	50 [50] 7
	 (Construction) □ Abandoned, Insufficient Supply 	XYes □ No 1 25 17 17 L	60 18 60 17
Outside Naterial Diameter (Plantic Chief) Siot No. Depth (m/ft)	Abandoned, Poor Water Quality	Map of W Please provide a map below following	ell Location ng instructions on the back.
Diameter (cm/in) (Plastic, Galvanized, Steel) Slot No. From To	Abandoned, other, specify	1 000	Hwy Lt)
	Other, specify	1 Was 1	0.11/1
	Hole Diameter	$ \cdot \rangle$	Buildins
Water found at Depth Kind of Water: ☐ Fresh ☐ Untested ☐ Depth (m(ft) ☐ Gas ☐ Other, specify	pth (m/ft) Diameter To (cm/in),	I I a E	
Water found at Depth Kind of Water: ☐ Fresh ☐ Untested (m/ft) ☐ Gas ☐ Other, specify	22 1011	Jal	-57T
Water found at Depth Kind of Water: Fresh Untested (m/ft) Gas Other, specify	17006	~ ~ ~	le li
Well Contractor and Well Technician Informa	1 18 19 19 1 1 20 1 1 20 1 20 1 1 20 1 1 1 1 1 1 1		
52545 Ont-Linited	/ell Contractor's Licence No.		_
Business Address (Street Number/Name)	unicipality 11 day	Comments:	
Postal Code Business E-mail Address		Well owner's Date Package Delivere	ed Ministry Use Only
Bus, Telephone No. (inc. area code) Name of Well Technician (Last Name	, First Name)	Information package delivered	Audit No. 2 3252 75
Well Technician's Licence No. Signature of Technician and or Confractor D	ate Submitted	Yes Date Work Completed	2€ JAN 2 6 2021
0508E (2018/12)	Ministry's Copy	MAN DE ME	© Queen's Printer for Ontario, 2018

RLC-HydroG

ATTACHMENT G

Laboratory Certificate of Analysis – TP2-9



Your Project #: SMITH FALLS SNOW DUMP

Site Location: SMITH FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

Report Date: 2024/12/27

Report #: R8461482

Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C4BK543 Received: 2024/12/17, 10:02

Sample Matrix: Soil # Samples Received: 10

·		Date	Date		
Analyses	Quantity	Extracted	Analyzed	Laboratory Method	Analytical Method
Methylnaphthalene Sum	10	N/A	2024/12/23	CAM SOP-00301	EPA 8270D m
Hot Water Extractable Boron	10	2024/12/20	2024/12/23	CAM SOP-00408	R153 Ana. Prot. 2011
Free (WAD) Cyanide	10	2024/12/23	2024/12/23	CAM SOP-00457	OMOE E3015 m
Conductivity	1	2024/12/20	2024/12/21	CAM SOP-00414	OMOE E3530 v1 m
Conductivity	9	2024/12/21	2024/12/21	CAM SOP-00414	OMOE E3530 v1 m
Hexavalent Chromium in Soil by IC (1)	10	2024/12/24	2024/12/24	CAM SOP-00436	EPA 3060A/7199 m
Petroleum Hydro. CCME F1 & BTEX in Soil (2)	10	N/A	2024/12/20	CAM SOP-00315	CCME PHC-CWS m
Petroleum Hydrocarbons F2-F4 in Soil (3)	2	2024/12/21	2024/12/22	CAM SOP-00316	CCME CWS m
Petroleum Hydrocarbons F2-F4 in Soil (3)	8	2024/12/21	2024/12/23	CAM SOP-00316	CCME CWS m
F4G (CCME Hydrocarbons Gravimetric)	6	2024/12/24	2024/12/24	CAM SOP-00316	CCME PHC-CWS m
Acid Extractable Metals by ICPMS	10	2024/12/20	2024/12/23	CAM SOP-00447	EPA 6020B m
Moisture	10	N/A	2024/12/20	CAM SOP-00445	Carter 2nd ed 70.2 m
PAH Compounds in Soil by GC/MS (SIM)	10	2024/12/21	2024/12/21	CAM SOP-00318	EPA 8270E
pH CaCl2 EXTRACT	10	2024/12/23	2024/12/23	CAM SOP-00413	EPA 9045 D m
Sodium Adsorption Ratio (SAR)	10	N/A	2024/12/24	CAM SOP-00102	EPA 6010C

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, EPA, APHA or the Quebec Ministry of Environment.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.



Your Project #: SMITH FALLS SNOW DUMP

Site Location: SMITH FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

> Report Date: 2024/12/27 Report #: R8461482

Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C48K543 Received: 2024/12/17, 10:02

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

- * RPDs calculated using raw data. The rounding of final results may result in the apparent difference.
- (1) Soils are reported on a dry weight basis unless otherwise specified.
- (2) No lab extraction date is given for F1BTEX & VOC samples that are field preserved with methanol. Extraction date is the date sampled unless otherwise stated.
- (3) All CCME PHC results met required criteria unless otherwise stated in the report. The CWS PHC methods employed by Bureau Veritas conform to all prescribed elements of the reference method and performance based elements have been validated. All modifications have been validated and proven equivalent following "Alberta Environment's Interpretation of the Reference Method for the Canada-Wide Standard for Petroleum Hydrocarbons in Soil Validation of Performance-Based Alternative Methods September 2003". Documentation is available upon request. Modifications from Reference Method for the Canada-wide Standard for Petroleum Hydrocarbons in Soil-Tier 1 Method: F2/F3/F4 data reported using validated cold solvent extraction instead of Soxhlet extraction.

Encryption Key

Jolanta Goralczyk
Project Manager
27 Dec 2024 15:24:09

Please direct all questions regarding this Certificate of Analysis to:

Jolanta Goralczyk, Project Manager

Email: Jolanta.Goralczyk@bureauveritas.com

Phone# (905)817-5751

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITH FALLS SNOW DUMP

Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 METALS & INORGANICS PKG (SOIL)

TP2-9

Bureau Veritas ID		ALZV70			ALZV71	ALZY/2		
Sampling Date		2024/12/12			2024/12/12	/ / /		
Sampling Date		14:00			14:30	15:00		
COC Number		N/A			N/A	N/A		
	UNITS	S8 Lab-Dup	RDL	QC Batch	S9	S10	RDL	QC Batch
Calculated Parameters								
Sodium Adsorption Ratio	N/A				0.27 (1)	0.25 (1)		9833362
Inorganics								
Conductivity	mS/cm	0.17	0.002	9842216	0.26	0.17	0.002	9842216
Available (CaCl2) pH	рН	7.74		9843356	7.62	7.77		9843356
WAD Cyanide (Free)	ug/g				ND	ND	0.01	9843083
Chromium (VI)	ug/g				ND	ND	0.18	9845363
Metals								
Hot Water Ext. Boron (B)	ug/g				0.18	0.12	0.050	9840710
Acid Extractable Antimony (Sb)	ug/g	-			ND	0.48	0.20	9840566
Acid Extractable Arsenic (As)	ug/g				1.8	2.9	1.0	9840566
Acid Extractable Barium (Ba)	ug/g				81	100	0.50	9840566
Acid Extractable Beryllium (Be)	ug/g				0.26	0.29	0.20	9840566
Acid Extractable Boron (B)	ug/g				ND	ND	5.0	9840566
Acid Extractable Cadmium (Cd)	ug/g				ND	0.16	0.10	9840566
Acid Extractable Chromium (Cr)	ug/g				12	13	1.0	9840566
Acid Extractable Cobalt (Co)	ug/g				5.0	4.9	0.10	9840566
Acid Extractable Copper (Cu)	ug/g				11	16	0.50	9840566
Acid Extractable Lead (Pb)	ug/g				6.1	67	1.0	9840566
Acid Extractable Molybdenum (Mo)	ug/g				0.65	0.70	0.50	9840566
Acid Extractable Nickel (Ni)	ug/g				8.0	8.9	0.50	9840566
Acid Extractable Selenium (Se)	ug/g				N D	ND	0.50	9840566
Acid Extractable Silver (Ag)	ug/g				ND	ND	0.20	9840566
Acid Extractable Thallium (TI)	ug/g				0.095	0.11	0.050	9840566
Acid Extractable Uranium (U)	ug/g				0.45	0.42	0.050	9840566
Acid Extractable Vanadium (V)	ug/g				26	27	5.0	9840566
Acid Extractable Zinc (Zn)	ug/g				15	46	5.0	9840566
Acid Extractable Mercury (Hg)	ug/g				ND	0.10	0.050	9840566

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate

ND = Not Detected at a concentration equal or greater than the indicated Detection Limit.

(1) Sodium was not detected. To report SAR the sodium detection limit was used in the calculation. This value represents a maximum ratio.



Bureau Veritas Job #: C4BK543 Report Date: 2024/12/27 St Lawrence Testing & Inspection Co Ltd Client Project #: SMITH FALLS SNOW DUMP

Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 PAHS (SOIL)

TP2-9

Bureau Veritas ID		ALZV67	ALZV69		ALZV70	ALZV71		ALZV72		
Sampling Date		2024/12/12	2024/12/12		2024/12/12		2	2024/12/12		
Sampling Date		13:00	13:30		14:00	14:30	/	15:00		
COC Number		N/A	N/A		N/A	N/A	4	N/A		
	UNITS	S6	S7	RDL	S8	S9 T	RDL	S10	RDL	QC Batch
Calculated Parameters										
Methylnaphthalene, 2-(1-)	ug/g	ND	0.13	0.071	ND	ND	0.0071	ND	0.071	9833271
Polyaromatic Hydrocarbons			-							
Acenaphthene	ug/g	ND	0.12	0.050	ND	ND	0.0050	ND	0.050	9842259
Acenaphthylene	ug/g	ND	ND	0.050	ND	ND	0.0050	ND	0.050	9842259
Anthracene	ug/g	0.10	0.28	0.050	ND	ND	0.0050	ND	0.050	9842259
Benzo(a) anthracene	ug/g	0.37	0.35	0.050	ND	ND	0.0050	0.099	0.050	9842259
Benzo(a) pyrene	ug/g	0.42	0.30	0.050	ND	ND	0.0050	0.14	0.050	9842259
Benzo(b/j)fluoranthene	ug/g	0.54	0.37	0.050	ND	ND	0.0050	0.17	0.050	9842259
Benzo(g, h,i) perylene	ug/g	0.35	0.19	0.050	ND	ND	0.0050	0.11	0.050	9842259
Benzo(k)fluoranthene	ug/g	0.21	0.15	0.050	ND	ND	0.0050	0.058	0.050	9842259
Chrysene	ug/g	0.32	0.28	0.050	ND	ND	0.0050	0.081	0.050	9842259
Dibenzo (a,h) anthracene	ug/g	0.081	0.056	0.050	ND	ND	0.0050	ND	0.050	9842259
Fluoranthene	ug/g	0.90	0.98	0.050	ND	ND	0.0050	0.21	0.050	9842259
Fluorene	ug/g	ND	0.19	0.050	ND	ND	0.0050	ND	0.050	9842259
Indeno(1,2,3-cd)pyrene	ug/g	0.35	0.20	0.050	ND	ND	0.0050	0.10	0.050	9842259
1-Methylnaphthalene	ug/g	ND	0.066	0.050	ND	ND	0.0050	ND	0.050	9842259
2-Methylnaphthalene	ug/g	ND	0.068	0.050	ND	ND	0.0050	ND	0.050	9842259
Naphthalene	ug/g	ND	0.081	0.050	ND	ND	0.0050	ND	0.050	9842259
Phenanthrene	ug/g	0.42	1.1	0.050	ND	ND	0.0050	0.10	0.050	9842259
Pyrene	ug/g	0.76	0.73	0.050	ND	ND	0.0050	0.22	0.050	9842259
Surrogate Recovery (%)										
D10-Anthracene	%	104	112		91	97		120		9842259
D14-Terphenyl (FS)	%	99	99		80	89		100		9842259
D8-Acenaphthylene	%	94	93		83	92		94		9842259
										

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



Bureau Veritas Job #: C4BK543 Report Date: 2024/12/27 St Lawrence Testing & Inspection Co Ltd Client Project #: SMITH FALLS SNOW DUMP

Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 PHCS, BTEX/F1-F4 (SOIL)

TP2-9

Bureau Veritas ID		ALZV71		ALZV72		
Sampling Date		2024/12/1	L2	2024/12/12		
Sampling Date		14:30		15:00		
COC Number		N/A	_	N/A		
	UNITS	59	Z	S10	RDL	QC Batch
BTEX & F1 Hydrocarbons						
Benzene	ug/g	ND		ND	0.020	9841741
Toluene	ug/g	ND		ND	0.020	9841741
Ethylbenzene	ug/g	ND		ND	0.020	9841741
o-Xylene	ug/g	ND		ND	0.020	9841741
p+m-Xylene	ug/g	ND		ND	0.040	9841741
Total Xylenes	ug/g	ND		ND	0.040	9841741
F1 (C6-C10)	ug/g	ND		ND	10	9841741
F1 (C6-C10) - BTEX	ug/g	ND		ND	10	9841741
F2-F4 Hydrocarbons						
F2 (C10-C16 Hydrocarbons)	ug/g	8.5		14	7.0	9842094
F3 (C16-C34 Hydrocarbons)	ug/g	ND		110	50	9842094
F4 (C34-C50 Hydrocarbons)	ug/g	ND		450	50	9842094
Reached Baseline at C50	ug/g	Yes		No		9842094
Surrogate Recovery (%)						
1,4-Difluorobenzene	%	103		102		9841741
4-Bromofluorobenzene	%	86		91		9841741
D10-o-Xylene	%	99		97		9841741
D4-1,2-Dichloroethane	%	103		101		9841741
o-Terphenyl	%	100		105		9842094

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

ND = Not Detected at a concentration equal or greater than the indicated

Detection Limit.

RLC-HydroG

ATTACHMENT H

Laboratory Certificate of Analysis – Borehole Soils



Your Project #: COMPOST SITE Site Location: SMITH FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

Report Date: 2025/07/03

Report #: R8569338 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C577434 Received: 2025/06/28, 11:30

Sample Matrix: Soil # Samples Received: 13

		Date	Date		
Analyses	Quantity	Extracted	Analyzed	Laboratory Method	Analytical Method
Methylnaphthalene Sum (1)	13	N/A	2025/07/03	CAM SOP-00301	EPA 8270D m
Hot Water Extractable Boron (1)	13	2025/07/03	2025/07/03	CAM SOP-00408	R153 Ana. Prot. 2011
Hexavalent Chromium in Soil by IC (1, 2)	13	2025/07/03	2025/07/03	CAM SOP-00436	EPA 3060A/7199 m
Petroleum Hydro. CCME F1 & BTEX in Soil (1, 3)	7	N/A	2025/06/30	CAM SOP-00315	CCME PHC-CWS m
Petroleum Hydro. CCME F1 & BTEX in Soil (1, 3)	6	N/A	2025/07/01	CAM SOP-00315	CCME PHC-CWS m
Petroleum Hydrocarbons F2-F4 in Soil (1, 4)	13	2025/06/30	2025/07/01	CAM SOP-00316	CCME CWS m
F4G (CCME Hydrocarbons Gravimetric) (1)	4	2025/07/03	2025/07/03	CAM SOP-00316	CCME PHC-CWS m
Acid Extractable Metals by ICPMS (1)	13	2025/07/02	2025/07/02	CAM SOP-00447	EPA 6020B m
Moisture (1)	13	N/A	2025/06/28	CAM SOP-00445	Carter 2nd ed 70.2 m
PAH Compounds in Soil by GC/MS (SIM) (1)	1	2025/07/02	2025/07/02	CAM SOP-00318	EPA 8270E
PAH Compounds in Soil by GC/MS (SIM) (1)	12	2025/07/02	2025/07/03	CAM SOP-00318	EPA 8270E

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, EPA, APHA or the Quebec Ministry of Environment.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested. This Certificate shall not be reproduced except in full, without the written approval of the laboratory.



Your Project #: COMPOST SITE Site Location: SMITH FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

> Report Date: 2025/07/03 Report #: R8569338

Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C577434

Received: 2025/06/28, 11:30

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

- * RPDs calculated using raw data. The rounding of final results may result in the apparent difference.
- (1) This test was performed by Bureau Veritas Mississauga, 6740 Campobello Rd , Mississauga, ON, L5N 2L8
- (2) Soils are reported on a dry weight basis unless otherwise specified.
- (3) No lab extraction date is given for F1BTEX & VOC samples that are field preserved with methanol. Extraction date is the date sampled unless otherwise stated.
- (4) All CCME PHC results met required criteria unless otherwise stated in the report. The CWS PHC methods employed by Bureau Veritas conform to all prescribed elements of the reference method and performance based elements have been validated. All modifications have been validated and proven equivalent following "Alberta Environment's Interpretation of the Reference Method for the Canada-Wide Standard for Petroleum Hydrocarbons in Soil Validation of Performance-Based Alternative Methods September 2003". Documentation is available upon request. Modifications from Reference Method for the Canada-wide Standard for Petroleum Hydrocarbons in Soil-Tier 1 Method: F2/F3/F4 data reported using validated cold solvent extraction instead of Soxhlet extraction.

Encryption Key

Jolanta Goralczyk Project Manager 03 Jul 2025 17:46:45

Please direct all questions regarding this Certificate of Analysis to:

Jolanta Goralczyk, Project Manager

Email: Jolanta.Goralczyk@bureauveritas.com

Phone# (905)817-5751

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 METALS PACKAGE (SOIL)

UNITS S1 S2 RDL QC Batch S2 RDL QC Batch RDL QC Batch S3 RDL QC Batch RDL QC Batch S3 RDL QC Batch RDL	Bureau Veritas ID		ASLF63	ASLF64			ASLF64			ASLF65		
10:00 10:30 10:30 10:30 10:0	Sampling Date		2025/06/24	2025/06/24			2025/06/24			2025/06/25		
UNITS S1 S2 RD QC Batch S2 RD QC Batch S3 RD QC Batch S3 RD QC Batch RD QC Batch S3 RD QC Batch RD Q			10:00	10:30			10:30			10:00		
No. No.	COC Number		N/A	N/A			N/A			N/A		
No		UNITS	\$1	S2	RDL	QC Batch		RDL	QC Batch	\$3	RDL	QC Batch
No. No.	Inorganics					·						
Description Location Locati	Chromium (VI)	ug/g	ND	ND	0.18	9962182	ND	0.18	9962182	ND	0.18	9962182
cicl Extractable Antimony (Sb) ug/g ND ND 0.20 9961905 0.25 0.20 9961 cicl Extractable Arsenic (As) ug/g 1.9 ND 1.0 9961905 2.4 1.0 9961 cicl Extractable Barium (Ba) ug/g 65 52 0.50 9961905 62 0.50 9961 cicl Extractable Beryllium (Be) ug/g 0.26 ND 0.20 9961905 0.22 0.20 9961 cicl Extractable Boron (B) ug/g ND ND 5.0 9961905 ND ND 5.0 9961905 cid Extractable Boron (B) ug/g ND ND 0.10 9961905 ND ND 5.0 9961905 ND 0.10 9961905 ND 0.10 9961905 ND 0.10 9961905 ND 0.10 9961905 12 1.0 9961905 12 1.0 9961905 12 1.0 9961905 12 1.0 9961905 12 1.0	Metals	· · · · · · · · · · · · · · · · · · ·				l		·				l
Cid Extractable Arsenic (As) Ug/g 1.9 ND 1.0 9961905 2.4 1.0 9961	Hot Water Ext. Boron (B)	ug/g	0.15	ND	0.050	9962324				0.22	0.050	9962324
Cicid Extractable Barium (Ba) Ug/g 65 52 0.50 9961905 62 0.50 9961	Acid Extractable Antimony (Sb)	ug/g	ND	ND	0.20	9961905				0.25	0.20	9961905
cicl Extractable Beryllium (Be) ug/g 0.26 ND 0.20 9961905 0.22 0.20 9961 cicl Extractable Boron (B) ug/g ND ND 5.0 9961905 ND ND 5.0 9961 cicl Extractable Cadmium (Cd) ug/g ND ND 0.10 9961905 ND ND 0.10 9961 cicl Extractable Cadmium (Cr) ug/g 11 8.5 1.0 9961905 12 1.0 9961 cicl Extractable Cromium (Cr) ug/g 4.6 3.6 0.10 9961905 3.1 0.10 9961 cicl Extractable Cobalt (Co) ug/g 4.6 3.6 0.10 9961905 3.1 0.10 9961 cid Extractable Copper (Cu) ug/g 9.7 7.6 0.50 9961905 17 1.0 9961 cid Extractable Lead (Pb) ug/g 7.7 3.0 1.0 9961905 17 1.0 9961 cid Extractable Molybdenum (Mo) ug/g	Acid Extractable Arsenic (As)	ug/g	1.9	ND	1.0	9961905				2.4	1.0	9961905
cid Extractable Boron (B) ug/g ND ND 5.0 9961905 ND 5.0 9961 cid Extractable Cadmium (Cd) ug/g ND ND 0.10 9961905 ND 0.10 9961 cid Extractable Chromium (Cr) ug/g 11 8.5 1.0 9961905 12 1.0 9961 cid Extractable Cobalt (Co) ug/g 4.6 3.6 0.10 9961905 3.1 0.10 9961 cid Extractable Copper (Cu) ug/g 9.7 7.6 0.50 9961905 12 0.50 9961 cid Extractable Lead (Pb) ug/g 7.7 3.0 1.0 9961905 17 1.0 9961 cid Extractable Molybdenum (Mo) ug/g ND ND 0.50 9961905 1.4 0.50 9961 cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50	Acid Extractable Barium (Ba)	ug/g	65	52	0.50	9961905				62	0.50	9961905
Second Extractable Cadmium (Cd) Ug/g ND ND O.10 9961905 ND O.10 9961905 O.10 9961905 O.10 9961905 O.10 9961905 O.10 9961905 O.10 9961905 O.10 O.10 9961905 O.10	Acid Extractable Beryllium (Be)	ug/g	0.26	ND	0.20	9961905				0.22	0.20	9961905
cid Extractable Chromium (Cr) ug/g 11 8.5 1.0 9961905 12 1.0 9961 cid Extractable Cobalt (Co) ug/g 4.6 3.6 0.10 9961905 3.1 0.10 9961 cid Extractable Copper (Cu) ug/g 9.7 7.6 0.50 9961905 12 0.50 9961 cid Extractable Lead (Pb) ug/g 7.7 3.0 1.0 9961905 17 1.0 9961 cid Extractable Molybdenum (Mo) ug/g ND ND 0.50 9961905 1.4 0.50 9961 cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.	Acid Extractable Boron (B)	ug/g	ND	ND	5.0	9961905				ND	5.0	9961905
cid Extractable Cobalt (Co) ug/g 4.6 3.6 0.10 9961905 3.1 0.10 9961 cid Extractable Copper (Cu) ug/g 9.7 7.6 0.50 9961905 12 0.50 9961 cid Extractable Lead (Pb) ug/g 7.7 3.0 1.0 9961905 17 1.0 9961 cid Extractable Molybdenum (Mo) ug/g ND ND 0.50 9961905 1.4 0.50 9961 cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND ND 0.20 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961	Acid Extractable Cadmium (Cd)	ug/g	ND	ND	0.10	9961905				ND	0.10	9961905
cid Extractable Copper (Cu) ug/g 9.7 7.6 0.50 9961905 12 0.50 9961 cid Extractable Lead (Pb) ug/g 7.7 3.0 1.0 9961905 17 1.0 9961 cid Extractable Molybdenum (Mo) ug/g ND ND 0.50 9961905 1.4 0.50 9961 cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND ND 0.20 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Vanadium (V) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 0.0 0.0 0.0 <td< td=""><td>Acid Extractable Chromium (Cr)</td><td>ug/g</td><td>11</td><td>8.5</td><td>1.0</td><td>9961905</td><td></td><td></td><td></td><td>12</td><td>1.0</td><td>9961905</td></td<>	Acid Extractable Chromium (Cr)	ug/g	11	8.5	1.0	9961905				12	1.0	9961905
cid Extractable Lead (Pb) ug/g 7.7 3.0 1.0 9961905 17 1.0 9961 cid Extractable Molybdenum (Mo) ug/g ND ND 0.50 9961905 1.4 0.50 9961 cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND ND 0.20 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 0.6 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Cobalt (Co)	ug/g	4.6	3.6	0.10	9961905		-		3.1	0.10	9961905
cid Extractable Molybdenum (Mo) ug/g ND ND 0.50 9961905 1.4 0.50 9961 cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND 0.070 0.050 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Copper (Cu)	ug/g	9.7	7.6	0.50	9961905				12	0.50	9961905
cid Extractable Nickel (Ni) ug/g 7.6 5.3 0.50 9961905 7.5 0.50 9961 cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND 0.070 0.050 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Lead (Pb)	ug/g	7.7	3.0	1.0	9961905				17	1.0	9961905
cid Extractable Selenium (Se) ug/g ND ND 0.50 9961905 ND 0.50 9961 cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND 0.070 0.050 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Molybdenum (Mo)	ug/g	ND	ND	0.50	9961905				1.4	0.50	9961905
cid Extractable Silver (Ag) ug/g ND ND 0.20 9961905 ND 0.20 9961 cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Nickel (Ni)	ug/g	7.6	5.3	0.50	9961905				7.5	0.50	9961905
cid Extractable Thallium (TI) ug/g 0.074 0.052 0.050 9961905 0.070 0.050 9961 cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Selenium (Se)	ug/g	ND	ND	0.50	9961905				ND	0.50	9961905
cid Extractable Uranium (U) ug/g 0.45 0.41 0.050 9961905 0.40 0.050 9961 cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Silver (Ag)	ug/g	ND	ND	0.20	9961905				ND	0.20	9961905
cid Extractable Vanadium (V) ug/g 24 18 5.0 9961905 16 5.0 9961 cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Thallium (TI)	ug/g	0.074	0.052	0.050	9961905				0.070	0.050	9961905
cid Extractable Zinc (Zn) ug/g 19 11 5.0 9961905 29 5.0 9961	Acid Extractable Uranium (U)	ug/g	0.45	0.41	0.050	9961905				0.40	0.050	9961905
25 3.0 3301	Acid Extractable Vanadium (V)	ug/g	24	18	5.0	9961905				16	5.0	9961905
cid Extractable Mercury (Hg)	Acid Extractable Zinc (Zn)	ug/g	19	11	5.0	9961905				29	5.0	9961905
	Acid Extractable Mercury (Hg)	ug/g	ND	ND	0.050	9961905				0.056	0.050	9961905

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS Sampler Initials: GM

O.REG 153 METALS PACKAGE (SOIL)

	ASLF66	ASLF67	ASLF68	ASLF69			ASLF69		
	2025/06/25	2025/06/25	2025/06/25	2025/06/25			2025/06/25		
	10:30	10:45	11:30	10:45			10:45		
	N/A	N/A	N/A	N/A			N/A		
UNITS	S4	S 5	S 6	S7	RDL	QC Batch	S7 Lab-Dup	RDL	QC Batch
ug/g	ND	ND	ND	ND	0.18	9962182			
ug/g	0.24	0.070	0.43	0.11	0.050	9962324	0.098	0.050	9962324
ug/g	ND	ND	0.55	ND	0.20	9961905			
ug/g	1.5	1.1	2.8	1.4	1.0	9961905			
ug/g	77	51	110	100	0.50	9961905			
ug/g	ND	ND	0.34	ND	0.20	9961905			
ug/g	ND	ND	ND	ND	5.0	9961905			
ug/g	ND	ND	0.25	ND	0.10	9961905			
ug/g	11	8.6	18	11	1.0	9961905			
ug/g	3.3	3.1	4.8	3.1	0.10	9961905			
ug/g	6.8	6.5	16	9.0	0.50	9961905			
ug/g	30	3.1	75	4.0	1.0	9961905			
ug/g	0.80	ND	1.3	ND	0.50	9961905			77-744
ug/g	5.9	5.3	25	6.0	0.50	9961905			
ug/g	ND	ND	ND	ND	0.50	9961905			
ug/g	ND	ND	ND	ND	0.20	9961905			
ug/g	0.094	ND	0.10	ND	0.050	9961905		-	
ug/g	0.43	0.44	0.51	0.47	0.050	9961905			
ug/g	20	19	26	20	5.0	9961905	"		
ug/g	28	11	93	14	5.0	9961905			
ug/g	ND	ND	0.082	ND	0.050	9961905			
	ug/g ug/g ug/g ug/g ug/g ug/g ug/g ug/g	2025/06/25 10:30 N/A UNITS	2025/06/25 10:30 10:45 N/A	2025/06/25 2025/06/25 10:30 10:45 11:30 N/A	2025/06/25 2025/06/25 2025/06/25 10:30 10:45 11:30 10:45	2025/06/25 10:30 10:45 11:30 10:45	2025/06/25 2025/06/25 2025/06/25 11:30 10:45 10:45 11:30 10:45	2025/06/25 2025/06/25 2025/06/25 11:30 10:45	2025/06/25 2025/06/25 2025/06/25 2025/06/25 10:30 10:45 11:30 10:45

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS Sampler Initials: GM

O.REG 153 METALS PACKAGE (SOIL)

Bureau Veritas ID		ASLF70	ASLF71	ASLF72	ASLF73	ASLF74	ASLF75		
Sampling Date		2025/06/25	2025/06/25	2025/06/25	2025/06/24	2025/06/24	2025/06/25		
	ļ	13:00	13:30	14:00	14:30	13:00	13:30		
COC Number		N/A	N/A	N/A	N/A	N/A	N/A		
	UNITS	58	S9	510	S11	S12	S13	RDL	QC Batch
Inorganics				· <u>··</u>		***************************************			
Chromium (VI)	ug/g	ND	ND	ND	ND	ND	ND	0.18	9962182
Metals		•			<u> </u>				
Hot Water Ext. Boron (B)	ug/g	0.18	0.13	0.26	ND	0.12	1.5	0.050	9962324
Acid Extractable Antimony (Sb)	ug/g	0.39	ND	0.41	ND	ND	ND	0.20	9961905
Acid Extractable Arsenic (As)	ug/g	2.8	2.8	2.3	1.2	1.3	1.8	1.0	9961905
Acid Extractable Barium (Ba)	ug/g	51	370	140	88	97	100	0.50	9961905
Acid Extractable Beryllium (Be)	ug/g	0.21	0.28	0.25	ND	ND	0.22	0.20	9961905
Acid Extractable Boron (B)	ug/g	ND	ND	ND	ND	ND	6.2	5.0	9961905
Acid Extractable Cadmium (Cd)	ug/g	0.11	ND	0.43	ND	ND	ND	0.10	9961905
Acid Extractable Chromium (Cr)	ug/g	11	13	27	11	9.7	10	1.0	9961905
Acid Extractable Cobalt (Co)	ug/g	3.2	4.8	3.7	4.5	4.4	4.5	0.10	9961905
Acid Extractable Copper (Cu)	ug/g	20	9.1	34	11	9.1	12	0.50	9961905
Acid Extractable Lead (Pb)	ug/g	42	15	74	4.7	4.4	13	1.0	9961905
Acid Extractable Molybdenum (Mo)	ug/g	0.91	1.2	1.1	ND	ND	ND	0.50	9961905
Acid Extractable Nickel (Ni)	ug/g	7.4	9.5	11	7.7	7.5	8.1	0.50	9961905
Acid Extractable Selenium (Se)	ug/g	ND	ND	ND	ND	ND	ND	0.50	9961905
Acid Extractable Silver (Ag)	ug/g	ND	ND	1.7	ND	ND	ND	0.20	9961905
Acid Extractable Thallium (Tl)	ug/g	0.070	0.098	0.10	0.065	0.065	0.075	0.050	9961905
Acid Extractable Uranium (U)	ug/g	0.40	0.49	0.51	0.43	0.45	0.44	0.050	9961905
Acid Extractable Vanadium (V)	ug/g	24	24	23	22	20	19	5.0	9961905
Acid Extractable Zinc (Zn)	ug/g	44	23	110	16	15	32	5.0	9961905
Acid Extractable Mercury (Hg)	ug/g	0.089	ND	0.20	ND	ND	ND	0.050	9961905

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE

Site Location: SMITH FALLS Sampler Initials: GM

O.REG 153 METALS PACKAGE (SOIL)

Bureau Veritas ID		ASLF75		
Sampling Date	1	2025/06/25		
		13:30		
COC Number		N/A		
	UNITS	S13 Lab-Dup	RDL	QC Batch
Metals	-			
Acid Extractable Antimony (Sb)	ug/g	ND	0.20	9961905
Acid Extractable Arsenic (As)	ug/g	1.7	1.0	9961905
Acid Extractable Barium (Ba)	ug/g	100	0.50	9961905
Acid Extractable Beryllium (Be)	ug/g	0.21	0.20	9961905
Acid Extractable Boron (B)	ug/g	5.9	5.0	9961905
Acid Extractable Cadmium (Cd)	ug/g	ND	0.10	9961905
Acid Extractable Chromium (Cr)	ug/g	10	1.0	9961905
Acid Extractable Cobalt (Co)	ug/g	4.5	0.10	9961905
Acid Extractable Copper (Cu)	ug/g	12	0.50	9961905
Acid Extractable Lead (Pb)	ug/g	14	1.0	9961905
Acid Extractable Molybdenum (Mo)	ug/g	ND	0.50	9961905
Acid Extractable Nickel (Ni)	ug/g	7.9	0.50	9961905
Acid Extractable Selenium (Se)	ug/g	ND	0.50	9961905
Acid Extractable Silver (Ag)	ug/g	ND	0.20	9961905
Acid Extractable Thallium (Tl)	ug/g	0.082	0.050	9961905
Acid Extractable Uranium (U)	ug/g	0.46	0.050	9961905
Acid Extractable Vanadium (V)	ug/g	19	5.0	9961905
Acid Extractable Zinc (Zn)	ug/g	32	5.0	9961905
Acid Extractable Mercury (Hg)	ug/g	ND	0.050	9961905

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS Sampler Initials: GM

O.REG 153 PAHS (SOIL)

Bureau Veritas ID		ASLF63	ASLF64			ASLF64			ASLF65		
Sampling Date		2025/06/24 10:00	2025/06/24 10:30			2025/06/24 10:30			2025/06/25 10:00		
COC Number		N/A	N/A	-		N/A			N/A		
	UNITS	S1	S2	RDL	QC Batch	S2 Lab-Dup	RDL	QC Batch	S3	RDL	QC Batch
Calculated Parameters											
Methylnaphthalene, 2-(1-)	ug/g	ND	ND	0.0071	9959980				0.018	0.0071	9959980
Polyaromatic Hydrocarbons	·					*****				· · · · · · · · · · · · · · · · · · ·	
Acenaphthene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.0070	0.0050	9961299
Acenaphthylene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	ND	0.0050	9961299
Anthracene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.020	0.0050	9961299
Benzo(a)anthracene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.053	0.0050	9961299
Benzo(a)pyrene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.052	0.0050	9961299
Benzo(b/j)fluoranthene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.079	0.0050	9961299
Benzo(g,h,i)perylene	ug/g	0.0064	ND	0.0050	9961299	ND	0.0050	9961299	0.035	0.0050	9961299
Benzo(k)fluoranthene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.025	0.0050	9961299
Chrysene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.052	0.0050	9961299
Dibenzo(a,h)anthracene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.0091	0.0050	9961299
Fluoranthene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.13	0.0050	9961299
Fluorene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.0093	0.0050	9961299
Indeno(1,2,3-cd)pyrene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.036	0.0050	9961299
1-Methylnaphthalene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.0084	0.0050	9961299
2-Methylnaphthalene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.0092	0.0050	9961299
Naphthalene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.011	0.0050	9961299
Phenanthrene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.13	0.0050	9961299
Pyrene	ug/g	ND	ND	0.0050	9961299	ND	0.0050	9961299	0.095	0.0050	9961299
Surrogate Recovery (%)											
D10-Anthracene	%	90	94		9961299	92		9961299	93		9961299
D14-Terphenyl (FS)	%	74	80		9961299	78		9961299	77		9961299
D8-Acenaphthylene	%	83	83		9961299	82		9961299	89		9961299

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS Sampler Initials: GM

O.REG 153 PAHS (SOIL)

				J.MEG 133 I	71115 (5012)	′					
Bureau Veritas ID		ASLF66	ASLF67	ASLF68	ASLF69		ASLF70		ASLF71		
Sampling Date		2025/06/25	2025/06/25	2025/06/25	2025/06/25		2025/06/25		2025/06/25		
		10:30	10:45	11:30	10:45		13:00		13:30		İ
COC Number		N/A	N/A	N/A	N/A		N/A		N/A		
	UNITS	S4	S5	S6	S7	RDL	S8	RDL	S9	RDL	QC Batch
Calculated Parameters		· · · · · · · · · · · · · · · · · · ·				 ·					
Methylnaphthalene, 2-(1-)	ug/g	0.090	ND	ND	ND	0.0071	ND	0.071	ND	0.0071	9959980
Polyaromatic Hydrocarbons				· · · · · · · · · · · · · · · · · · ·		L	<u> </u>				
Acenaphthene	ug/g	0.20	ND	0.0087	ND	0.0050	ND	0.050	ND	0.0050	9961299
Acenaphthylene	ug/g	0.039	ND	0.0072	ND	0.0050	ND	0.050	ND	0.0050	<u> </u>
Anthracene	ug/g	0.56	0.011	0.034	ND	0.0050	ND	0.050	ND	0.0050	9961299
Benzo(a)anthracene	ug/g	1.2	0.023	0.088	0.0052	0.0050	0.060	0.050	0.014	0.0050	9961299
Benzo(a)pyrene	ug/g	1.1	0.018	0.086	0.0050	0.0050	0.073	0.050	0.017	0.0050	9961299
Benzo(b/j)fluoranthene	ug/g	1.5	0.024	0.12	0.0060	0.0050	0.11	0.050	0.025	0.0050	9961299
Benzo(g,h,i)perylene	ug/g	0.60	0.011	0.054	ND	0.0050	0.11	0.050	0.018	0.0050	9961299
Benzo(k)fluoranthene	ug/g	0.50	0.0096	0.041	ND	0.0050	ND	0.050	0.0079	0.0050	9961299
Chrysene	ug/g	0.98	0.020	0.074	ND	0.0050	0.056	0.050	0.013	0.0050	9961299
Dibenzo(a,h)anthracene	ug/g	0.16	ND	0.014	ND	0.0050	ND	0.050	ND	0.0050	9961299
Fluoranthene	ug/g	2.6	0.045	0.19	0.010	0.0050	0.12	0.050	0.032	0.0050	9961299
Fluorene	ug/g	0.24	ND	0.011	ND	0.0050	ND	0.050	ND	0.0050	9961299
Indeno(1,2,3-cd)pyrene	ug/g	0.66	0.011	0.055	ND	0.0050	0.066	0.050	0.014	0.0050	9961299
1-Methylnaphthalene	ug/g	0.044	ND	ND	ND	0.0050	ND	0.050	ND	0.0050	9961299
2-Methylnaphthalene	ug/g	0.046	ND	ND	ND	0.0050	ND	0.050	ND	0.0050	9961299
Naphthalene	ug/g	0.080	ND	ND	ND	0.0050	ND	0.050	ND	0.0050	9961299
Phenanthrene	ug/g	2.0	0.033	0.11	0.0055	0.0050	0.058	0.050	0.015	0.0050	9961299
Pyrene	ug/g	2.0	0.034	0.15	0.0082	0.0050	0.13	0.050	0.026	0.0050	9961299
Surrogate Recovery (%)				· · · · · · · · · · · · · · · · · · ·			··· ,				
D10-Anthracene	%	86	89	87	92		100		92		9961299
D14-Terphenyl (FS)	%	73	71	75	79		97		79		9961299
D8-Acenaphthylene	%	85	83	82	76		104		87		9961299

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 PAHS (SOIL)

Bureau Veritas ID		ASLF72		ASLF73	ASLF74	ASLF75		
Sampling Date		2025/06/25		2025/06/24	2025/06/24	2025/06/25		
Sampling Date		14:00		14:30	13:00	13:30		
COC Number		N/A		N/A	N/A	N/A		
	UNITS	S10	RDL	S11	S12	\$13	RDL	QC Batch
Calculated Parameters								
Methylnaphthalene, 2-(1-)	ug/g	ND	0.071	ND	ND	ND	0.0071	9959980
Polyaromatic Hydrocarbons				· · · · · · · · · · · · · · · · · · ·				J
Acenaphthene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Acenaphthylene	ug/g	ND	0.050	ND	ND	ND	0.0050	
Anthracene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Benzo(a)anthracene	ug/g	0.058	0.050	ND	ND	0.0092	0.0050	9961299
Benzo(a)pyrene	ug/g	0.074	0.050	ND	ND	0.019	0.0050	9961299
Benzo(b/j)fluoranthene	ug/g	0.11	0.050	ND	ND	0.033	0.0050	9961299
Benzo(g,h,i)perylene	ug/g	0.077	0.050	ND	ND	0.017	0.0050	9961299
Benzo(k)fluoranthene	ug/g	ND	0.050	ND	ND	0.010	0.0050	9961299
Chrysene	ug/g	0.054	0.050	ND	ND	0.012	0.0050	9961299
Dibenzo (a, h) anthracene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Fluoranthene	ug/g	0.13	0.050	ND	ND	0.016	0.0050	9961299
Fluorene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Indeno(1,2,3-cd)pyrene	ug/g	0.060	0.050	ND	ND	0.016	0.0050	9961299
1-Methylnaphthalene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
2-Methylnaphthalene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Naphthalene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Phenanthrene	ug/g	ND	0.050	ND	ND	ND	0.0050	9961299
Pyrene	ug/g	0.11	0.050	ND	ND	0.012	0.0050	9961299
Surrogate Recovery (%)								
D10-Anthracene	%	108		89	94	92		9961299
D14-Terphenyl (FS)	%	101		72	79	76		9961299
D8-Acenaphthylene	%	104		82	81	88		9961299

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

ND = Not Detected at a concentration equal or greater than the indicated Detection Limit.



Bureau Veritas Job #: C577434 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE

Site Location: SMITH FALLS Sampler Initials: GM

O.REG 153 PHCS, BTEX/F1-F4 (SOIL)

Bureau Veritas ID		ASLF63			ASLF63			ASLF64	ASLF65		
Sampling Date		2025/06/24			2025/06/24			2025/06/24	2025/06/25		
Jamping Date		10:00			10:00			10:30	10:00		
COC Number		N/A			N/A			N/A	N/A		
	UNITS	S1	RDL	QC Batch	S1 Lab-Dup	RDL	QC Batch	S2	\$3	RDL	QC Batch
BTEX & F1 Hydrocarbons					· · · · · · · · · · · · · · · · · · ·						
Benzene	ug/g	ND	0.020	9960382	ND	0.020	9960382	ND	ND	0.020	9960382
Toluene	ug/g	ND	0.020	9960382	ND	0.020	9960382	ND	ND	0.020	9960382
Ethylbenzene	ug/g	ND	0.020	9960382	ND	0.020	9960382	ND	ND	0.020	9960382
o-Xylene	ug/g	ND	0.020	9960382	ND	0.020	9960382	ND	ND	0.020	9960382
p+m-Xylene	ug/g	ND	0.040	9960382	ND	0.040	9960382	ND	ND	0.040	9960382
Total Xylenes	ug/g	ND	0.040	9960382	ND	0.040	9960382	ND	ND	0.040	9960382
F1 (C6-C10)	ug/g	ND	10	9960382	ND	10	9960382	ND	ND	10	9960382
F1 (C6-C10) - BTEX	ug/g	ND	10	9960382	ND	10	9960382	ND	ND	10	9960382
F2-F4 Hydrocarbons											
F2 (C10-C16 Hydrocarbons)	ug/g	ND	7.0	9960611				ND	ND	7.0	9960611
F3 (C16-C34 Hydrocarbons)	ug/g	ND	50	9960611				ND	87	50	9960611
F4 (C34-C50 Hydrocarbons)	ug/g	ND	50	9960611				ND	130	50	9960611
Reached Baseline at C50	ug/g	Yes		9960611				Yes	Yes		9960611
Surrogate Recovery (%)											
1,4-Difluorobenzene	%	102		9960382	104		9960382	105	105		9960382
4-Bromofluorobenzene	%	95		9960382	94		9960382	94	96		9960382
D10-o-Xylene	%	101		9960382	100		9960382	101	102		9960382
D4-1,2-Dichloroethane	%	100		9960382	99		9960382	97	96		9960382
o-Terphenyl	%	90		9960611				90	90		9960611

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 PHCS, BTEX/F1-F4 (SOIL)

Bureau Veritas ID	ļ	ASLF66	ASLF67	ASLF68	ASLF69			ASLF69		
Sampling Date	1	2025/06/25	2025/06/25	2025/06/25	2025/06/25			2025/06/25		
		10:30	10:45	11:30	10:45			10:45		
COC Number		N/A	N/A	N/A	N/A			N/A		
	UNITS	S4	S 5	\$6	S7	RDL	QC Batch	S7 Lab-Dup	RDL	QC Batch
BTEX & F1 Hydrocarbons			*							· · · · · · · · · · · · · · · · · · ·
Benzene	ug/g	ND	ND	ND	ND	0.020	9960382			
Toluene	ug/g	ND	ND	ND	ND	0.020	9960382			
Ethylbenzene	ug/g	ND	ND	ND	ND	0.020	9960382			
o-Xylene	ug/g	ND	ND	ND	ND	0.020	9960382			
p+m-Xylene	ug/g	ND	ND	ND	ND	0.040	9960382			-
Total Xylenes	ug/g	ND	ND	ND	ND	0.040	9960382			
F1 (C6-C10)	ug/g	ND	ND	ND	ND	10	9960382			
F1 (C6-C10) - BTEX	ug/g	ND	ND	ND	ND	10	9960382	· · · · · · · · · · · · · · · · · · ·		
F2-F4 Hydrocarbons										
F2 (C10-C16 Hydrocarbons)	ug/g	7.0	ND	ND	ND	7.0	9960611	ND	7.0	9960611
F3 (C16-C34 Hydrocarbons)	ug/g	120	ND	69	ND	50	9960611	NĐ	50	9960611
F4 (C34-C50 Hydrocarbons)	ug/g	160	ND	56	ND	50	9960611	ND	50	9960611
Reached Baseline at C50	ug/g	No	Yes	Yes	Yes		9960611	Yes		9960611
Surrogate Recovery (%)		· ·					···········			
1,4-Difluorobenzene	%	103	102	102	101		9960382			
4-Bromofluorobenzene	%	94	95	95	96		9960382			
D10-o-Xylene	%	108	110	100	109		9960382			
D4-1,2-Dichloroethane	%	98	101	101	101		9960382			
o-Terphenyl	%	90	88	87	90		9960611	97		9960611

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

O.REG 153 PHCS, BTEX/F1-F4 (SOIL)

Bureau Veritas ID		ASLF70	ASLF71	ASLF72	ASLF73	ASLF74	ASLF75		
Sampling Date		2025/06/25	2025/06/25	2025/06/25	2025/06/24	2025/06/24	2025/06/25		
Jumphing Date	ļ	13:00	13:30	14:00	14:30	13:00	13:30		
COC Number		N/A	N/A	N/A	N/A	N/A	N/A		
	UNITS	S8	S9	S10	S11	S12	S13	RDL	QC Batch
BTEX & F1 Hydrocarbons									
Benzene	ug/g	ND	ND	ND	ND	ND	ND	0.020	9960382
Toluene	ug/g	ND	ND	0.024	ND	ND	ND	0.020	9960382
Ethylbenzene	ug/g	ND	ND	ND	ND	ND	ND	0.020	9960382
o-Xylene	ug/g	ND	ND	ND	ND	ND	ND	0.020	9960382
p+m-Xylene	ug/g	ND	ND	ND	ND	ND	ND	0.040	9960382
Total Xylenes	ug/g	ND	ND	ND	ND	ND	ND	0.040	9960382
F1 (C6-C10)	ug/g	ND	ND	ND	ND	ND	ND	10	9960382
F1 (C6-C10) - BTEX	ug/g	ND	ND	ND	ND	ND	ND	10	9960382
F2-F4 Hydrocarbons				• • • • • • • • • • • • • • • • • • • •					
F2 (C10-C16 Hydrocarbons)	ug/g	8.9	ND	ND	ND	ND	ND	7.0	9960611
F3 (C16-C34 Hydrocarbons)	ug/g	140	ND	170	ND	ND	ND	50	9960611
F4 (C34-C50 Hydrocarbons)	ug/g	1000	110	360	ND	ND	ND	50	9960611
Reached Baseline at C50	ug/g	No	No	No	Yes	Yes	Yes		9960611
Surrogate Recovery (%)			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				· · · · · · · · · · · · · · · · · · ·		
1,4-Difluorobenzene	%	105	102	104	102	104	103		9960382
4-Bromofluorobenzene	%	94	96	94	96	96	96		9960382
D10-o-Xylene	%	106	96	100	102	101	107		9960382
D4-1,2-Dichloroethane	%	101	101	103	102	102	101		9960382
o-Terphenyl	%	89	87	85	88	87	91		9960611
DDI - Donostoble Detection I	114	·					 		

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

ND = Not Detected at a concentration equal or greater than the indicated Detection Limit.



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE

Site Location: SMITH FALLS

Sampler Initials: GM

RESULTS OF ANALYSES OF SOIL

Bureau Veritas ID		ASLF63	ASLF64	ASLF65	ASLF66	ASLF67	ASLF68	ASLF69		<u> </u>
Sampling Date		2025/06/24 10:00	2025/06/24 10:30	2025/06/25 10:00	2025/06/25 10:30					
COC Number		N/A	N/A	N/A	N/A	N/A	N/A	N/A		
	UNITS	S1	S2	53	S4	S 5	S6	S7	RDL	QC Batch
Inorganics								****	<u> </u>	
Moisture	%	12	10	9.2	19	8.5	29	13	1.0	9960116
RDL = Reportable Detec	tion Limit								1.0	3300110
QC Batch = Quality Con	trol Batch									

Bureau Veritas ID		ASLF70	ASLF71	ASLF72	ASLF73	ASLF74	ASLF75		
Sampling Date		2025/06/25 13:00	2025/06/25 13:30	2025/06/25 14:00	2025/06/24 14:30	2025/06/24 13:00	2025/06/25 13:30		
COC Number		N/A	N/A	N/A	N/A	N/A	N/A		· · · · · · · · · · · · · · · · · · ·
	UNITS	S8	S9	S10	S11	512	S13	RDL	QC Batch
Inorganics									
Moisture	%	9.3	8.4	12	11	10	16	1.0	9960116
RDL = Reportable Detection QC Batch = Quality Cont				···					



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

PETROLEUM HYDROCARBONS (CCME)

				•			
Bureau Veritas ID		ASLF66	ASLF70	ASLF71	ASLF72	i	
Sampling Date		2025/06/25 10:30	2025/06/25 13:00	2025/06/25 13:30	2025/06/25 14:00		
COC Number		N/A	N/A	N/A	N/A		
	UNITS	S4	58	S9	S10	RDL	QC Batch
F2-F4 Hydrocarbons							
F4G-sg (Grav. Heavy Hydrocarbons)	ug/g	820	5700	510	2400	100	9962192
RDL = Reportable Detection Limit QC Batch = Quality Control Batch							



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: ASLF63 Sample ID: S1

Matrix: Soil

Collected: 2025/06/24

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF63 Dup Sample ID: S1

Matrix: Soil

Collected: 2025/06/24

Shipped: Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea

Bureau Veritas ID: ASLF64

Sample ID: S2

Matrix: Soil

Collected: 2025/06/24

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/02	Mitesh Raj

Bureau Veritas ID: ASLF64 Dup Sample ID: S2

Matrix: Soil

Collected: 2025/06/24

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/02	Mitesh Raj

Bureau Veritas ID: ASLF65

Sample ID: S3

Matrix: Soil

Collected: 2025/06/25

Shipped:

Instrumentation	Batch	Extracted	Date Analyzed	Analyst
CALC	9959980	N/A	2025/07/03	Automated Statchk
ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
	CALC ICP	CALC 9959980 ICP 9962324	CALC 9959980 N/A ICP 9962324 2025/07/03	CALC 9959980 N/A 2025/07/03 ICP 9962324 2025/07/03 2025/07/03



St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: ASLF65 Sample ID: S3 Matrix: Soil

Collected: 2025/06/25

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF66

Collected: 2025/06/25

Sample ID: S4 Matrix: Soil

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
F4G (CCME Hydrocarbons Gravimetric)	BAL	9962192	2025/07/03	2025/07/03	Rashmi Dubey
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF67 Sample ID: S5

Matrix: Soil

Collected: 2025/06/25

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Rai

Bureau Veritas ID: ASLF68 Sample ID: S6

Matrix: Soil

Collected: 2025/06/25

Shipped:

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb



St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: ASLF68

Sample ID: S6
Matrix: Soil

Collected: 2025/06/25

Shipped: Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF69 Sample ID: S7

Matrix: Soil

Collected: 2025/06/25

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/06/30	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF69 Dup

Sample ID: S7

Matrix: Soil

Collected: 2025/06/25

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb

Bureau Veritas ID: ASLF70 Sample ID: S8

Matrix: Soil

Collected: 2025/06/25 Shipped:

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/07/01	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
F4G (CCME Hydrocarbons Gravimetric)	BAL	9962192	2025/07/03	2025/07/03	Rashmi Dubey
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj



Bureau Veritas Job #: C577434 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: ASLF71 Sample ID: S9 Matrix: Soil

Collected: 2025/06/25

Shipped: Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/07/01	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
F4G (CCME Hydrocarbons Gravimetric)	BAL	9962192	2025/07/03	2025/07/03	Rashmi Dubey
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF72 Sample ID: S10

Matrix: Soil

Collected: 2025/06/25

Shipped: Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/07/01	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
F4G (CCME Hydrocarbons Gravimetric)	BAL	9962192	2025/07/03	2025/07/03	Rashmi Dubey
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF73 Sample ID: S11

Matrix: Soil

Collected: 2025/06/24

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/07/01	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF74

Matrix: Soil

Collected: 2025/06/24 Sample ID: S12 Shipped:

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk



St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE Site Location: SMITH FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: ASLF74
Sample ID: S12
Matrix: Soil

Collected: 2025/06/24

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	HSGC/MSFD	9960382	N/A	2025/07/01	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF75 Sample ID: S13

Collected: 2025/06/25

Matrix: Soil

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959980	N/A	2025/07/03	Automated Statchk
Hot Water Extractable Boron	ICP	9962324	2025/07/03	2025/07/03	Suban Kanapathippllai
Hexavalent Chromium in Soil by IC	IC/SPEC	9962182	2025/07/03	2025/07/03	Harpuneet Kaur
Petroleum Hydro. CCME F1 & BTEX in Soil	H\$GC/MSFD	9960382	N/A	2025/07/01	Anca Ganea
Petroleum Hydrocarbons F2-F4 in Soil	GC/FID	9960611	2025/06/30	2025/07/01	Mohammed Abdul Nafay Shoeb
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu
Moisture	BAL	9960116	N/A	2025/06/28	Diksha Desawer
PAH Compounds in Soil by GC/MS (SIM)	GC/MS	9961299	2025/07/02	2025/07/03	Mitesh Raj

Bureau Veritas ID: ASLF75 Dup Sample ID: S13 Matrix: Soil

Collected: 2025/06/25

Shipped:

Received: 2025/06/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Acid Extractable Metals by ICPMS	ICP/MS	9961905	2025/07/02	2025/07/02	Daniel Teclu



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS Sampler Initials: GM

GENERAL COMMENTS

Each temperature is the average of up to three cooler temperatures taken at receipt

Package 1 2.0°C

F1 Analysis: Soil weight exceeds the protocol specification of approximately 5g in the field preserved vial. Additional methanol was added to the vial to ensure extraction efficiency.

Sample ASLF70 [S8]: PAH Analysis: Due to the sample matrix, sample required dilution. Detection limits were adjusted accordingly.

Sample ASLF72 [S10]: PAH Analysis: Due to the sample matrix, sample required dilution. Detection limits were adjusted accordingly.

Results relate only to the items tested.



Bureau Veritas Job #: C577434 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITH FALLS

Sampler Initials: GM

QUALITY ASSURANCE REPORT

QA/QC Batch	Init	QC Туре	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
9960116	DDR	RPD	Moisture	2025/06/28	1.2		%	20
9960382	AGA	Matrix Spike [ASLF63-04]	1,4-Difluorobenzene	2025/06/30		99	%	60 - 140
			4-Bromofluorobenzene	2025/06/30		100	%	60 - 140
			D10-o-Xylene	2025/06/30		101	%	60 - 140
			D4-1,2-Dichloroethane	2025/06/30		95	%	60 - 140
			Benzene	2025/06/30		79	%	50 - 140
			Toluene	2025/06/30		80	%	50 - 140
			Ethylbenzene	2025/06/30		92	%	50 - 140
			o-Xylene	2025/06/30		92	%	50 - 1 40
			p+m-Xylene	2025/06/30		89	%	50 - 140
			F1 (C6-C10)	2025/06/30		93	%	60 - 140
9960382	AGA	Spiked Blank	1,4-Difluorobenzene	2025/06/30		94	%	60 - 140
		4-Bromofluorobenzene	2025/06/30		98	%	60 - 140	
			D10-o-Xylene	2025/06/30		100	%	60 - 140
			D4-1,2-Dichloroethane	2025/06/30		99	%	60 - 140
			Benzene	2025/06/30		87	%	50 - 140
			Toluene	2025/06/30		85	%	50 - 140
			Ethylbenzene	2025/06/30		95	%	50 - 140
			o-Xylene	2025/06/30		97	%	50 - 140
			p+m-Xylene	2025/06/30		91	%	50 - 140
			F1 (C6-C10)	2025/06/30		96	%	80 - 120
9960382	9960382 AGA Metho	Method Blank	1,4-Difluorobenzene	2025/06/30		104	%	60 - 140
			4-Bromofluorobenzene	2025/06/30		94	%	60 - 140
			D10-o-Xylene	2025/06/30		99	%	60 - 140
			D4-1,2-Dichloroethane	2025/06/30		99	%	60 - 140
			Benzene	2025/06/30	ND, RDL=0.020	33	ug/g	00 140
			Toluene	2025/06/30	ND, RDL=0.020		ug/g	
			Ethylbenzene	2025/06/30	ND, RDL=0.020		ug/g	
			o-Xylene	2025/06/30	ND, RDL=0.020		ug/g	
			p+m-Xylene	2025/06/30	ND, RDL=0.040		ug/g	
			Total Xylenes	2025/06/30	ND, RDL=0.040		ug/g	
			F1 (C6-C10)	2025/06/30	ND, RDL=10		ug/g	
			F1 (C6-C10) - BTEX	2025/06/30	ND, RDL=10		ug/g	
9960382	AGA	RPD [ASLF63-04]	Benzene	2025/06/30	NC		%	50
			Toluene	2025/06/30	NC		%	50
			Ethylbenzene	2025/06/30	NC		%	50
			o-Xylene	2025/06/30	NC		%	50
			p+m-Xylene	2025/06/30	NC		%	50
			Total Xylenes	2025/06/30	NC		%	50
			F1 (C6-C10)	2025/06/30	NC		%	30
			F1 (C6-C10) - BTEX	2025/06/30	NC		%	30
9960611	MSZ	Matrix Spike [ASLF69-03]	o-Terphenyl	2025/07/01		86	%	60 - 140
			F2 (C10-C16 Hydrocarbons)	2025/07/01		92	%	60 - 140
			F3 (C16-C34 Hydrocarbons)	2025/07/01		92	%	60 - 140
			F4 (C34-C50 Hydrocarbons)	2025/07/01		86	%	60 - 140



Bureau Veritas Job #: C577434 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITH FALLS

Sampler Initials: GM

QA/QC			QUALITY ASSURANCE					
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Doca	LINUTC	0011
9960611	MSZ	Spiked Blank	o-Terphenyl	2025/07/01	Value	Recovery 84	UNITS	QC Limits
		,	F2 (C10-C16 Hydrocarbons)	2025/07/01		87	%	60 - 140
			F3 (C16-C34 Hydrocarbons)	2025/07/01		87 87	% %	80 - 120 80 - 120
			F4 (C34-C50 Hydrocarbons)	2025/07/01		80	% %	80 - 120 80 - 120
9960611	MSZ	Method Blank	o-Terphenyl	2025/06/30		87	% %	
			F2 (C10-C16 Hydrocarbons)	2025/06/30	ND,	0/		60 - 140
			F3 (C16-C34 Hydrocarbons)		RDL=7.0		ug/g	
				2025/06/30	ND, RDL=50		ug/g	
			F4 (C34-C50 Hydrocarbons)	2025/06/30	ND, RDL=50		ug/g	
9960611	MSZ	RPD [ASLF69-03]	F2 (C10-C16 Hydrocarbons)	2025/07/01	NC		%	30
			F3 (C16-C34 Hydrocarbons)	2025/07/01	NC		%	30
			F4 (C34-C50 Hydrocarbons)	2025/07/01	NC		%	30
9961299	RAJ	Matrix Spike [ASLF64-03]	D10-Anthracene	2025/07/02		91	%	50 - 130
			D14-Terphenyl (FS)	2025/07/02		85	%	50 - 130
			D8-Acenaphthylene	2025/07/02		84	%	50 - 130
			Acenaphthene	2025/07/02		88	%	50 - 130
			Acenaphthylene	2025/07/02		83	%	50 - 130
			Anthracene	2025/07/02		103	%	50 - 130
			Benzo(a)anthracene	2025/07/02		98	%	50 - 130
			Benzo(a)pyrene	2025/07/02		95	%	50 - 130
			Benzo(b/j)fluoranthene	2025/07/02		97	%	50 - 130
			Benzo(g,h,i)perylene	2025/07/02		98	%	50 - 130
			Benzo(k)fluoranthene	2025/07/02		95	%	50 - 130
			Chrysene	2025/07/02		92	%	50 - 130
			Dibenzo(a,h)anthracene	2025/07/02		98	%	50 - 130
			Fluoranthene	2025/07/02		97	%	50 - 130
			Fluorene	2025/07/02		90	%	50 - 130
			Indeno(1,2,3-cd)pyrene	2025/07/02		100	%	50 - 130
			1-Methylnaphthalene	2025/07/02		75	%	50 - 130
			2-Methylnaphthalene	2025/07/02		79	%	50 - 130
			Naphthalene	2025/07/02		70	%	50 - 130
			Phenanthrene	2025/07/02		92	%	50 - 130
			Pyrene	2025/07/02		98	%	50 - 130
9961299	RAJ	Spiked Blank	D10-Anthracene	2025/07/02		96	%	50 - 130
		•	D14-Terphenyl (FS)	2025/07/02		86	%	50 - 130
			D8-Acenaphthylene	2025/07/02		93	%	50 - 130
			Acenaphthene	2025/07/02		94	%	50 - 130
			Acenaphthylene	2025/07/02		92		
			Anthracene	2025/07/02		92 104	%	50 - 130
			Benzo(a)anthracene	2025/07/02			%	50 - 130
			Benzo(a)pyrene	2025/07/02		102	%	50 - 130
			Benzo(b/j)fluoranthene	2025/07/02		96	%	50 - 130
			Benzo(g,h,i)perylene	2025/07/02		99 100	%	50 - 130
			Benzo(k)fluoranthene	2025/07/02		100	%	50 - 130
			Chrysene			98	%	50 - 130
			Dibenzo(a,h)anthracene	2025/07/02 2025/07/02		95	%	50 - 130
			Fluoranthene	• •		100	%	50 - 130
				2025/07/02		97	%	50 - 130
			Fluorene 2025,			94	%	50 - 130
			Indeno(1,2,3-cd)pyrene	2025/07/02		104	%	50 - 130
			1-Methylnaphthalene	2025/07/02		90	%	50 - 130
			2-Methylnaphthalene	2025/07/02		96	%	50 - 130



Bureau Veritas Job #: C577434 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITH FALLS

Sampler Initials: GM

QA/QC				<u> </u>				
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Bassyary	LINUTC	001::
		3-1/65	Naphthalene	2025/07/02	value	Recovery 94	UNITS	QC Limits
			Phenanthrene	2025/07/02			%	50 - 130
			Pyrene	2025/07/02		93	%	50 - 130
9961299	RAJ	Method Blank	D10-Anthracene	2025/07/02		99	%	50 - 130
		Metriod Blank	D14-Terphenyl (FS)	· ·		96	%	50 - 130
			D8-Acenaphthylene	2025/07/02		81	%	50 - 130
			Acenaphthene	2025/07/02 2025/07/02	ND	92	%	50 - 130
			·		ND, RDL=0.0050		ug/g	
			Acenaphthylene	2025/07/02	ND, RDL=0.0050		ug/g	
			Anthracene	2025/07/02	ND, RDL=0.0050		ug/g	
			Benzo(a)anthracene	2025/07/02	ND, RDL=0.0050		ug/g	
		Benzo(a)pyrene	2025/07/02	ND, RDL≃0.0050		ug/g		
			Benzo(b/j)fluoranthene	2025/07/02	ND, RDL=0.0050		ug/g	
			Benzo(g,h,i)perylene	2025/07/02	ND, RDL=0.0050		ug/g	
			Benzo(k)fluoranthene	2025/07/02	ND, RDL=0.0050		ug/g	
		Chrysene	2025/07/02	ND, RDL=0.0050		ug/g		
			Dibenzo(a,h)anthracene	2025/07/02	ND, RDL=0.0050		ug/g	
			Fluoranthene	2025/07/02	ND, RDL=0.0050		ug/g	
			Fluorene	2025/07/02	ND, RDL=0.0050		ug/g	
			Indeno(1,2,3-cd)pyrene	2025/07/02	ND, RDL=0.0050		ug/g	
			1-Methylnaphthalene	2025/07/02	ND, RDL=0.0050		ug/g	
			2-Methylnaphthalene	2025/07/02	ND, RDL=0.0050		ug/g	
			Naphthalene	2025/07/02	ND, RDL=0.0050		ug/g	
			Phenanthrene	2025/07/02	ND, RDL=0.0050		ug/g	
			Pyrene	2025/07/02	ND, RDL=0.0050		ug/g	
9961299	RAJ	RPD [ASLF64-03]	Acenaphthene	2025/07/02	NC		%	40
			Acenaphthylene	2025/07/02	NC		%	40
			Anthracene	2025/07/02	NC		%	40
			Benzo(a)anthracene	2025/07/02	NC		%	40
			Benzo(a)pyrene	2025/07/02	NC		%	40
			Benzo(b/j)fluoranthene	2025/07/02	NC		%	40
			Benzo(g,h,i)perylene	2025/07/02	NC		%	40
			Benzo(k)fluoranthene	2025/07/02	NC		%	40
			Chrysene	2025/07/02	NC		%	40
			Dibenzo(a,h)anthracene	2025/07/02	NC		%	40
			Fluoranthene	2025/07/02	NC		%	40
			Fluorene	2025/07/02	NC		% %	40



Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE

Site Location: SMITH FALLS

Sampler Initials: GM

QA/QC Batch	Init	OC Tyne	Parameter	Data 4 1 1	N-1			0.000
Dalti	ITHE	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Indeno(1,2,3-cd)pyrene	2025/07/02	NC		%	40
			1-Methylnaphthalene	2025/07/02	NC		%	40
			2-Methylnaphthalene	2025/07/02	NC		%	40
			Naphthalene	2025/07/02	NC		%	40
			Phenanthrene	2025/07/02	NC		%	40
0064005	D.T.1		Pyrene	2025/07/02	NC		%	40
9961905	DT1	Matrix Spike [ASLF75-01]	Acid Extractable Antimony (Sb)	2025/07/02		115	%	75 - 125
			Acid Extractable Arsenic (As)	2025/07/02		104	%	75 - 125
			Acid Extractable Barium (Ba)	2025/07/02		NC	%	75 - 125
			Acid Extractable Beryllium (Be)	2025/07/02		101	%	75 - 125
			Acid Extractable Boron (B)	2025/07/02		99	%	75 - 125
			Acid Extractable Cadmium (Cd)	2025/07/02		101	%	75 - 125
			Acid Extractable Chromium (Cr)	2025/07/02		101	%	75 - 125
			Acid Extractable Cobalt (Co)	2025/07/02		101	%	75 - 125
			Acid Extractable Copper (Cu)	2025/07/02		99	%	7 5 - 12 5
			Acid Extractable Lead (Pb)	2025/07/02		105	%	75 - 125
			Acid Extractable Molybdenum (Mo)	2025/07/02		96	%	75 - 125
			Acid Extractable Nickel (Ni)	2025/07/02		101	%	75 - 125
			Acid Extractable Selenium (Se)	2025/07/02		107	%	75 - 125
			Acid Extractable Silver (Ag)	2025/07/02		101	%	75 - 125
			Acid Extractable Thallium (TI)	2025/07/02		108	%	75 - 12 5
			Acid Extractable Uranium (U)	2025/07/02		111	%	75 - 125
			Acid Extractable Vanadium (V)	2025/07/02		103	%	75 - 125
			Acid Extractable Zinc (Zn)	2025/07/02		NC	%	75 - 125
			Acid Extractable Mercury (Hg)	2025/07/02		101	%	75 - 125 75 - 125
9961905	DT1	Spiked Blank	Acid Extractable Antimony (Sb)	2025/07/02		113	%	80 - 120
		.,	Acid Extractable Arsenic (As)	2025/07/02		101	% %	
			Acid Extractable Barium (Ba)	2025/07/02		101		80 - 120
			Acid Extractable Beryllium (Be)	2025/07/02		96	% %	80 - 120
			Acid Extractable Boron (B)	2025/07/02				80 - 120
			Acid Extractable Bolon (b) Acid Extractable Cadmium (Cd)			89	%	80 - 120
			Acid Extractable Cadmum (Cd) Acid Extractable Chromium (Cr)	2025/07/02		97	%	80 - 120
			• •	2025/07/02		98	%	80 - 120
			Acid Extractable Cobalt (Co)	2025/07/02		98	%	80 - 120
			Acid Extractable Copper (Cu)	2025/07/02		97	%	80 - 120
			Acid Extractable Lead (Pb)	2025/07/02		103	%	80 - 120
			Acid Extractable Molybdenum (Mo)	2025/07/02		91	%	80 - 120
			Acid Extractable Nickel (Ni)	2025/07/02		102	%	80 - 120
			Acid Extractable Selenium (Se)	2025/07/02		103	%	80 - 120
			Acid Extractable Silver (Ag)	2025/07/02		96	%	80 - 120
			Acid Extractable Thallium (Tl)	2025/07/02		105	%	80 - 120
			Acid Extractable Uranium (U)	2025/07/02		106	%	80 - 120
			Acid Extractable Vanadium (V)	2025/07/02		99	%	80 - 120
			Acid Extractable Zinc (Zn)	2025/07/02		101	%	80 - 120
			Acid Extractable Mercury (Hg)	2025/07/02		97	%	80 - 120
9961905	DT1	Method Blank	Acid Extractable Antimony (Sb)	2025/07/02	ND, RDL=0.20		ug/g	
			Acid Extractable Arsenic (As)	2025/07/02	ND, RDL=1.0		ug/g	
			Acid Extractable Barium (Ba)	2025/07/02	ND, RDL=0.50		ug/g	
			Acid Extractable Beryllium (Be)	2025/07/02	ND, RDL=0.20		ug/g	



St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITH FALLS

Sampler Initials: GM

QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Acid Extractable Boron (B)	2025/07/02	ND,	· · · · · · · · · · · · · · · · · · ·	ug/g	
					RDL=5.0			
			Acid Extractable Cadmium (Cd)	2025/07/02	ND,		ug/g	
					RDL=0.10			
			Acid Extractable Chromium (Cr)	2025/07/02	ND,		ug/g	
					RDL=1.0			
			Acid Extractable Cobalt (Co)	2025/07/02	ND, RDL=0.10		ug/g	
			Acid Extractable Copper (Cu)	2025/07/02	ND, RDL=0.50		ug/g	
			Acid Extractable Lead (Pb)	2025/07/02	ND, RDL=1.0		ug/g	
			Acid Extractable Molybdenum (Mo)	2025/07/02	ND,		uala	
			Acid Extractable Molybuchum (Mo)	2023/07/02	RDL=0.50		ug/g	
			Acid Extractable Nickel (Ni)	2025/07/02	ND, RDL=0.50		ug/g	
			Acid Extractable Selenium (Se)	2025/07/02	ND,		ug/g	
					RDL=0.50			
			Acid Extractable Silver (Ag)	2025/07/02	ND,		ug/g	
			Acid Extractable Thallium (TI)	2025/07/02	RDL=0.20 ND,		/	
			Acid Extractable Trialium (11)	2023/07/02	RDL=0.050		ug/g	
			Acid Extractable Uranium (U)	2025/07/02	ND, RDL=0.050		ug/g	
			Acid Extractable Vanadium (V)	2025/07/02	ND,		ug/g	
			Acid Extractable Zinc (Zn)	2025/07/02	RDL=5.0 ND, RDL=5.0		ug/g	
			Acid Extractable Mercury (Hg)	2025/07/02	ND, RDL=0.050		ug/g	
9961905	DT1	RPD [ASLF75-01]	Acid Extractable Antimony (Sb)	2025/07/02	NC		%	30
		• • • • • • •	Acid Extractable Arsenic (As)	2025/07/02	5.0		%	30
			Acid Extractable Barium (Ba)	2025/07/02	3.7		%	30
			Acid Extractable Beryllium (Be)	2025/07/02	4.5		%	30
			Acid Extractable Boron (B)	2025/07/02	4.3		%	30
			Acid Extractable Cadmium (Cd)	2025/07/02	NC		%	30
			Acid Extractable Chromium (Cr)	2025/07/02	1.1		%	30
			Acid Extractable Cobalt (Co)	2025/07/02	1.5		%	30
			Acid Extractable Copper (Cu)	2025/07/02	0.24		%	30
			Acid Extractable Lead (Pb)	2025/07/02	2.9		%	30
			Acid Extractable Molybdenum (Mo)	2025/07/02	NC		%	30
			Acid Extractable Nickel (Ni)	2025/07/02	3.2		%	30
			Acid Extractable Selenium (Se)	2025/07/02	NC		%	30
			Acid Extractable Silver (Ag)	2025/07/02	NC		%	30
			Acid Extractable Thallium (TI)	2025/07/02	8.8		%	30
			Acid Extractable Uranium (U)	2025/07/02	3.3		%	30
			Acid Extractable Vanadium (V)	2025/07/02	0.38		%	30
			Acid Extractable Zinc (Zn)	2025/07/02	0.36		%	30
			Acid Extractable Mercury (Hg)	2025/07/02	NC		%	30
9962182	HK1	Matrix Spike [ASLF64-01]	Chromium (VI)	2025/07/03		85	%	70 - 130
9962182	HK1	Spiked Blank	Chromium (VI)	2025/07/03		89	%	80 - 120
9962182	HK1	Method Blank	Chromium (VI)	2025/07/03	ND, RDL=0.18		ug/g	
9962182	HK1	RPD [ASLF64-01]	Chromium (VI)	2025/07/03	NC NC		%	35



Site Location: SMITH FALLS

Sampler Initials: GM

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC						····		
Batch	Init	QC Туре	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
9962192	RDU	Matrix Spike	F4G-sg (Grav. Heavy Hydrocarbons)	2025/07/03		82	%	65 - 135
9962192	RDU	Spiked Blank	F4G-sg (Grav. Heavy Hydrocarbons)	2025/07/03		101	%	65 - 135
9962192	RDU	Method Blank	F4G-sg (Grav. Heavy Hydrocarbons)	2025/07/03	ND,		ug/g	
					RDL=100		0, 0	
9962192	RDU	RPD	F4G-sg (Grav. Heavy Hydrocarbons)	2025/07/03	7.7		%	50
9962324	SŲK	Matrix Spike [ASLF69-01]	Hot Water Ext. Boron (B)	2025/07/03		100	%	75 - 125
9962324	SUK	Spiked Blank	Hot Water Ext. Boron (B)	2025/07/03		104	%	75 - 125
9962324	SUK	Method Blank	Hot Water Ext. Boron (B)	2025/07/03	ND,		ug/g	
					RDL=0.050		5/ 5	
9962324	SUK	RPD [ASLF69-01]	Hot Water Ext. Boron (B)	2025/07/03	9.0		%	40

Duplicate: Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate sample matrix interference.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.

Surrogate: A pure or isotopically labeled compound whose behavior mirrors the analytes of interest. Used to evaluate extraction efficiency.

NC (Matrix Spike): The recovery in the matrix spike was not calculated. The relative difference between the concentration in the parent sample and the spike amount was too small to permit a reliable recovery calculation (matrix spike concentration was less than the native sample concentration)

NC (Duplicate RPD): The duplicate RPD was not calculated. The concentration in the sample and/or duplicate was too low to permit a reliable RPD calculation (absolute difference <= 2x RDL).



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITH FALLS Sampler Initials: GM

VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by:

Cistin	Cause	
Cristina Carrie	re, Senior Scientific Specialist	

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.

RLC-HydroG

ATTACHMENT I

Laboratory Certificate of Analysis – Surface Water



Your Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

> Report Date: 2025/04/03 Report #: R8514203

Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C533951 Received: 2025/03/28, 09:05

Sample Matrix: Water # Samples Received: 4

		Date	Date		
Analyses	Quantity	Extracted	Analyzed	Laboratory Method	Analytical Method
Methylnaphthalene Sum	4	N/A	2025/04/02	CAM SOP-00301	EPA 8270D m
Chromium (VI) in Water	4	N/A	2025/04/01	CAM SOP-00436	EPA 7199 m
Petroleum Hydro. CCME F1 & BTEX in Water	4	N/A	2025/04/02	CAM SOP-00315	CCME PHC-CWS m
Petroleum Hydrocarbons F2-F4 in Water (1)	4	2025/04/01	2025/04/01	CAM SOP-00316	CCME PHC-CWS m
Mercury	4	2025/04/02	2025/04/02	CAM SOP-00453	EPA 7470A m
Dissolved Metals by ICPMS	4	N/A	2025/03/31	CAM SOP-00447	EPA 6020B m
PAH Compounds in Water by GC/MS (SIM)	4	2025/04/01	2025/04/01	CAM SOP-00318	EPA 8270E

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, EPA, APHA or the Quebec Ministry of Environment.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

(1) All CCME PHC results met required criteria unless otherwise stated in the report. The CWS PHC methods employed by Bureau Veritas conform to all prescribed elements of the reference method and performance based elements have been validated. All modifications have been validated and proven equivalent following "Alberta Environment's

^{*} RPDs calculated using raw data. The rounding of final results may result in the apparent difference.



Your Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

> Report Date: 2025/04/03 Report #: R8514203

Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C533951

Received: 2025/03/28, 09:05

Interpretation of the Reference Method for the Canada-Wide Standard for Petroleum Hydrocarbons in Soil Validation of Performance-Based Alternative Methods September 2003".

Documentation is available upon request. Modifications from Reference Method for the Canada-wide Standard for Petroleum Hydrocarbons in Soil-Tier 1 Method: F2/F3/F4 data reported using validated cold solvent extraction instead of Soxhlet extraction.

Encryption Key

Jolanta Goralczyk Project Manager 03 Apr 2025 17:53:04

Please direct all questions regarding this Certificate of Analysis to:

Jolanta Goralczyk, Project Manager

Email: Jolanta.Goralczyk@bureauveritas.com

Phone# (905)817-5751

hording

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

O.REG 153 METALS PACKAGE (WATER)

Bureau Veritas ID		APIS12			APIS12			APIS13		
Sampling Date		2025/03/25 13:00			2025/03/25 13:00			2025/03/25 13:30		
COC Number		N/A			N/A			N/A		
	UNITS	S1	RDL	QC Batch	S1 Lab-Dup	RDL	QC Batch	52	RDL	QC Batch
Metals										
Chromium (VI)	ug/L	ND	0.50	9902060	ND	0.50	9902060	ND	0.50	9902060
Mercury (Hg)	ug/L	ND	0.10	9902695				ND	0.10	9902695
Dissolved Antimony (Sb)	ug/L	ND	0.50	9900835	ND	0.50	9900835	ND	0.50	9900835
Dissolved Arsenic (As)	ug/L	ND	1.0	9900835	ND	1.0	9900835	ND	1.0	9900835
Dissolved Barium (Ba)	ug/L	47	2.0	9900835	48	2.0	9900835	51	2.0	9900835
Dissolved Beryllium (Be)	ug/L	ND	0.40	9900835	ND	0.40	9900835	ND	0.40	9900835
Dissolved Boron (B)	ug/L	ND	10	9900835	ND	10	9900835	ND	10	9900835
Dissolved Cadmium (Cd)	ug/L	ND	0.090	9900835	ND	0.090	9900835	ND	0.090	9900835
Dissolved Chromium (Cr)	ug/L	ND	5.0	9900835	ND	5.0	9900835	ND	5.0	9900835
Dissolved Cobalt (Co)	ug/L	ND	0.50	9900835	NĐ	0.50	9900835	ND	0.50	9900835
Dissolved Copper (Cu)	ug/L	1.0	0.90	9900835	1.0	0.90	9900835	1.1	0.90	9900835
Dissolved Lead (Pb)	ug/L	ND	0.50	9900835	ND	0.50	9900835	ND	0.50	9900835
Dissolved Molybdenum (Mo)	ug/L	ND	0.50	9900835	ND	0.50	9900835	ND	0.50	9900835
Dissolved Nickel (Ni)	ug/L	ND	1.0	9900835	ND	1.0	9900835	ND	1.0	9900835
Dissolved Selenium (Se)	ug/L	ND	2.0	9900835	ND	2.0	9900835	ND	2.0	9900835
Dissolved Silver (Ag)	ug/L	ND	0.090	9900835	ND	0.090	9900835	ND	0.090	9900835
Dissolved Sodium (Na)	ug/L	8100	100	9900835	8000	100	9900835	7300	100	9900835
Dissolved Thallium (TI)	ug/L	ND	0.050	9900835	ND .	0.050	9900835	ND	0.050	9900835
Dissolved Uranium (U)	ug/L	0.14	0.10	9900835	0.14	0.10	9900835	0.17	0.10	9900835
Dissolved Vanadium (V)	ug/L	ND	0.50	9900835	ND	0.50	9900835	ND	0.50	9900835
Dissolved Zinc (Zn)	ug/L	8.8	5.0	9900835	13	5.0	9900835	8.2	5.0	9900835

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



Site Location: SMITHS FALLS

Sampler Initials: GM

O.REG 153 METALS PACKAGE (WATER)

Bureau Veritas ID		APIS14	APIS15		
Sampling Date		2025/03/25	2025/03/25		
Sampling Date		14:00	14:30		
COC Number		N/A	N/A		
	UNITS	S3	S4	RDL	QC Batch
Metals					
Chromium (VI)	ug/L	ND	ND	0.50	9902060
Mercury (Hg)	ug/L	ND	ND	0.10	9902695
Dissolved Antimony (Sb)	ug/L	ND	ND	0.50	9900832
Dissolved Arsenic (As)	ug/L	ND	ND	1.0	9900832
Dissolved Barium (Ba)	ug/L	55	41	2.0	9900832
Dissolved Beryllium (Be)	ug/L	ND	ND	0.40	9900832
Dissolved Boron (B)	ug/L	ND	ND	10	9900832
Dissolved Cadmium (Cd)	ug/L	ND	ND	0.090	9900832
Dissolved Chromium (Cr)	ug/L	ND	ND	5.0	9900832
Dissolved Cobalt (Co)	ug/L	ND	ND	0.50	9900832
Dissolved Copper (Cu)	ug/L	ND	ND	0.90	9900832
Dissolved Lead (Pb)	ug/L	ND	ND	0.50	9900832
Dissolved Molybdenum (Mo)	ug/L	ND	ND	0.50	9900832
Dissolved Nickel (Ni)	ug/L	ND	ND	1.0	9900832
Dissolved Selenium (Se)	ug/L	ND	ND	2.0	9900832
Dissolved Silver (Ag)	ug/L	ND	ND	0.090	9900832
Dissolved Sodium (Na)	ug/L	7500	23000	100	9900832
Dissolved Thallium (TI)	ug/L	ND	ND	0.050	9900832
Dissolved Uranium (U)	ug/L	0.16	0.16	0.10	9900832
Dissolved Vanadium (V)	ug/L	ND	ND	0.50	9900832
Dissolved Zinc (Zn)	ug/L	6.3	5.5	5.0	9900832

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



Site Location: SMITHS FALLS

Sampler Initials: GM

O.REG 153 PAHS (WATER)

	APIS12		APIS13	APIS14	APIS15		
	2025/03/25		2025/03/25	2025/03/25	2025/03/25		
	13:00		13:30	14:00	14:30		
	N/A		N/A	N/A	N/A		
UNITS	S1	QC Batch	S2	S3	S4	RDL	QC Batch
				·····			
ug/L	ND	9900077	ND	ND	ND	0.071	9900575
•							
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.0090	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
ug/L	ND	9901823	ND	ND	ND	0.030	9901823
ug/L	ND	9901823	ND	ND	ND	0.050	9901823
%	106	9901823	104	101	104		9901823
%	105	9901823	106	104	108		9901823
%	95	9901823	94	92	93		9901823
	ug/L ug/L ug/L ug/L ug/L ug/L ug/L ug/L	13:00 N/A	N/A UNITS S1 QC Batch	13:00	13:00	13:00	13:00

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



Site Location: SMITHS FALLS

Sampler Initials: GM

O.REG 153 PHCS, BTEX/F1-F4 (WATER)

Bureau Veritas ID		APIS12	APIS13	APIS14	APIS15		
Sampling Date		2025/03/25	2025/03/25	2025/03/25	2025/03/25		
Sampling Date		13:00	13:30	14:00	14:30		
COC Number		N/A	N/A	N/A	N/A		
	UNITS	S1	S2	\$3	54	RDL	QC Batch
BTEX & F1 Hydrocarbons							
Benzene	ug/L	ND	ND	ND	ND	0.20	9902637
Toluene	ug/L	ND	ND	ND	ND	0.20	9902637
Ethylbenzene	ug/L	ND	ND	ND	ND	0.20	9902637
o-Xylene	ug/L	ND	ND	ND	ND	0.20	9902637
p+m-Xylene	ug/L	ND	ND	ND	ND	0.40	9902637
Total Xylenes	ug/L	ND	ND	ND	ND	0.40	9902637
F1 (C6-C10)	ug/L	ND	ND	ND	ND	25	9902637
F1 (C6-C10) - BTEX	ug/L	ND	ND	ND	ND	25	9902637
F2-F4 Hydrocarbons							
F2 (C10-C16 Hydrocarbons)	ug/L	ND	ND	ND	ND	90	9901826
F3 (C16-C34 Hydrocarbons)	ug/L	ND	ND	ND	ND	200	9901826
F4 (C34-C50 Hydrocarbons)	ug/L	ND	ND	ND	ND	200	9901826
Reached Baseline at C50	ug/L	Yes	Yes	Yes	Yes		9901826
Surrogate Recovery (%)							·
1,4-Difluorobenzene	%	99	95 .	98	97		9902637
4-Bromofluorobenzene	%	100	97	97	97		9902637
D10-o-Xylene	%	97	95	95	95		9902637
D4-1,2-Dichloroethane	%	97	95	93	93		9902637
o-Terphenyl	%	89	91	89	87		9901826

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: APIS12 Sample ID: 51 Matrix: Water

Collected:

2025/03/25

Shipped: Received: 2025/03/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9900077	N/A	2025/04/02	Automated Statchk
Chromium (VI) in Water	IC	9902060	N/A	2025/04/01	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9902637	N/A	2025/04/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9901826	2025/04/01	2025/04/01	Anna Stuglik-Rolland
Mercury	CV/AA	9902695	2025/04/02	2025/04/02	Maitri PATIL
Dissolved Metals by iCPMS	ICP/MS	9900835	N/A	2025/03/31	Nan Raykha
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9901823	2025/04/01	2025/04/01	Margaret Kulczyk-Stanko

Bureau Veritas ID: APIS12 Dup

Collected: 2025/03/25

Sample ID: 51

Matrix: Water

Shipped:

Received: 2025/03/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Chromium (VI) in Water	IC	9902060	N/A	2025/04/01	Rupinder Sihota
Dissolved Metals by ICPMS	ICP/MS	9900835	N/A	2025/03/31	Nan Raykha

Bureau Veritas ID: APIS13

Sample ID: S2

Matrix: Water

Collected: 2025/03/25

Shipped: Received: 2025/03/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9900575	N/A	2025/04/02	Automated Statchk
Chromium (VI) in Water	IC	9902060	N/A	2025/04/01	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9902637	N/A	2025/04/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9901826	2025/04/01	2025/04/01	Anna Stuglik-Rolland
Mercury	CV/AA	9902695	2025/04/02	2025/04/02	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9900835	N/A	2025/03/31	Nan Raykha
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9901823	2025/04/01	2025/04/01	Margaret Kulczyk-Stanko

Bureau Veritas ID: APIS14 Sample ID: 53 Matrix: Water

Collected: 2025/03/25

Shipped:

Received: 2025/03/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9900575	N/A	2025/04/02	Automated Statchk
Chromium (VI) in Water	IC	9902060	N/A	2025/04/01	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9902637	N/A	2025/04/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9901826	2025/04/01	2025/04/01	Anna Stuglik-Rolland
Mercury	CV/AA	9902695	2025/04/02	2025/04/02	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9900832	N/A	2025/03/31	Indira HarryPaul
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9901823	2025/04/01	2025/04/01	Margaret Kulczyk-Stanko



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

TEST SUMMARY

Bureau Veritas ID: APIS15 Sample ID: S4 Matrix: Water

Collected: 2025/03/25

Shipped: Received: 2025/03/28

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9900575	N/A	2025/04/02	Automated Statchk
Chromium (VI) in Water	IC	9902060	N/A	2025/04/01	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9902637	N/A	2025/04/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9901826	2025/04/01	2025/04/01	Anna Stuglik-Rolland
Mercury	CV/AA	9902695	2025/04/02	2025/04/02	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9900832	N/A	2025/03/31	Indira HarryPaul
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9901823	2025/04/01	2025/04/01	Margaret Kulczyk-Stanko



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

GENERAL COMMENTS

Each temperature is the	average of up t	o three cooler to	nperatures	taken at rece	eipt	 	
Package 1	3.3°C						
Results relate only to the	e items tested.						



Report Date: 2025/04/03

St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

QUALITY ASSURANCE REPORT

QA/QC							•	
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
9900832	IHP	Matrix Spike	Dissolved Antimony (Sb)	2025/03/31		102	%	80 - 120
			Dissolved Arsenic (As)	2025/03/31		99	%	80 - 120
			Dissolved Barium (Ba)	2025/03/31		101	%	80 - 120
			Dissolved Beryllium (Be)	2025/03/31		98	%	80 - 120
			Dissolved Boron (B)	2025/03/31		91	%	80 - 120
			Dissolved Cadmium (Cd)	2025/03/31		99	%	80 - 120
			Dissolved Chromium (Cr)	2025/03/31		97	%	80 - 120
			Dissolved Cobalt (Co)	2025/03/31		93	%	80 - 120
			Dissolved Copper (Cu)	2025/03/31		97	%	80 - 120
			Dissolved Lead (Pb)	2025/03/31		96	%	80 - 120
			Dissolved Molybdenum (Mo)	2025/03/31		100	%	80 - 120
			Dissolved Nickel (Ni)	2025/03/31		94	%	80 - 120
			Dissolved Selenium (Se)	2025/03/31		99	%	80 - 120
			Dissolved Silver (Ag)	2025/03/31		93	%	80 - 120
			Dissolved Sodium (Na)	2025/03/31		93	%	80 - 120
			Dissolved Thallium (Tl)	2025/03/31		99	%	80 - 120
			Dissolved Uranium (U)	2025/03/31		103	%	80 - 120
			Dissolved Vanadium (V)	2025/03/31		97	%	80 - 120
			Dissolved Zinc (Zn)	2025/03/31		97	%	80 - 120
9900832	IHP	Spiked Blank	Dissolved Antimony (Sb)	2025/03/31		96	%	80 - 120
		Dissolved Arsenic (As)	2025/03/31		97	%	80 - 120	
		Dissolved Barium (Ba)	2025/03/31		97	%	80 - 120	
		Dissolved Beryllium (Be)	2025/03/31		94	%	80 - 120	
			Dissolved Boron (B)	2025/03/31		89	%	80 - 120
			Dissolved Cadmium (Cd)	2025/03/31		95	%	80 - 120
			Dissolved Chromium (Cr)	2025/03/31		95	%	80 - 120
			Dissolved Cobalt (Co)	2025/03/31		91	%	80 - 120
			Dissolved Copper (Cu)	2025/03/31		94	%	80 - 120
			Dissolved Lead (Pb)	2025/03/31		94	%	80 - 120
			Dissolved Molybdenum (Mo)	2025/03/31		96	%	80 - 120
			Dissolved Nickel (Ni)	2025/03/31		92	%	80 - 120
			Dissolved Selenium (Se)	2025/03/31		95	%	80 - 120
			Dissolved Silver (Ag)	2025/03/31		91	%	80 - 120
			Dissolved Sodium (Na)	2025/03/31		94	%	80 - 120
			Dissolved Thallium (TI)	2025/03/31		99	%	80 - 120
			Dissolved Uranium (U)	2025/03/31		98	%	80 - 120
			Dissolved Vanadium (V)	2025/03/31		95	%	80 - 120
			Dissolved Variation (V) Dissolved Zinc (Zn)	2025/03/31		95	%	80 - 120
9900832	IHP	Method Blank	Dissolved Antimony (Sb)	2025/03/31	ND,	23	ug/L	00 120
			,,,,,	, ,	RDL=0.50		<i>5.</i>	
			Dissolved Arsenic (As)	2025/03/31	ND, RDL=1.0		ug/L	
			Dissolved Barium (Ba)	2025/03/31	ND, RDL=2.0		ug/L	
			Dissolved Beryllium (Be)	2025/03/31	ND, RDL=0.40		ug/L	
			Dissolved Boron (B)	2025/03/31	ND, RDL=10		ug/L	
			Dissolved Cadmium (Cd)	2025/03/31	ND, RDL=0.090		ug/L	



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

QA/QC		007				_		
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Chromium (Cr)	2025/03/31	ND, RDL=5.0		ug/L	
			Dissolved Cobalt (Co)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Copper (Cu)	2025/03/31	ND, RDL=0.90		ug/L	
			Dissolved Lead (Pb)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Molybdenum (Mo)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Nickel (Ni)	2025/03/31	ND, RDL=1.0		ug/L	
			Dissolved Selenium (Se)	2025/03/31	ND, RDL=2.0		ug/L	
			Dissolved Silver (Ag)	2025/03/31	ND, RDL=0.090		ug/L	
			Dissolved Sodium (Na)	2025/03/31	ND, RDL=100		ug/L	
			Dissolved Thallium (TI)	2025/03/31	ND, RDL=0.050		ug/L	
			Dissolved Uranium (U)	2025/03/31	ND, RDL=0.10		ug/L	
			Dissolved Vanadium (V)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Zinc (Zn)	2025/03/31	ND, RDL=5.0		ug/L	
9900832	IHP	RPD	Dissolved Lead (Pb)	2025/03/31	NC		%	20
9900835	NR	Matrix Spike [APIS12-03]	Dissolved Antimony (Sb)	2025/03/31		101	%	80 - 120
	-	, - ,	Dissolved Arsenic (As)	2025/03/31		99	%	80 - 120
			Dissolved Barium (Ba)	2025/03/31		97	%	80 - 120
			Dissolved Beryllium (Be)	2025/03/31		93	%	80 - 120
			Dissolved Boron (B)	2025/03/31		89	%	80 - 120
			Dissolved Cadmium (Cd)	2025/03/31		100	%	80 - 120
			Dissolved Chromium (Cr)	2025/03/31		95	%	80 - 120
			Dissolved Cobalt (Co)	2025/03/31		96	%	80 - 120
			Dissolved Copper (Cu)	2025/03/31		99	%	80 - 120
			Dissolved Lead (Pb)	2025/03/31		95	%	80 - 120
			Dissolved Molybdenum (Mo)	2025/03/31		98	%	80 - 120
			Dissolved Nickel (Ni)	2025/03/31		95	%	80 - 120
			Dissolved Selenium (Se)	2025/03/31		100	%	80 - 120
			Dissolved Silver (Ag)	2025/03/31		89	%	80 - 120
			Dissolved Sodium (Na)	2025/03/31		94	%	80 - 120
			Dissolved Thallium (TI)	2025/03/31		98	%	80 - 120
			Dissolved Uranium (U)	2025/03/31		99	%	80 - 120
			Dissolved Vanadium (V)	2025/03/31		95	%	80 - 120
			Dissolved Zinc (Zn)	2025/03/31		98	%	80 - 120
900835	N_R	Spiked Blank	Dissolved Antimony (Sb)	2025/03/31		98	%	80 - 120
.500055		op.new oronn	Dissolved Artimony (35)	2025/03/31		98	%	80 - 120
			Dissolved Arsenic (As)	2025/03/31		96	%	
			Dissolved Beryllium (Be)					80 - 120
				2025/03/31		92	%	80 - 120
			Dissolved Boron (B)	2025/03/31		89	%	80 - 120
			Dissolved Cadmium (Cd)	2025/03/31		99	%	80 - 120



Site Location: SMITHS FALLS

Sampler Initials: GM

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Chromium (Cr)	2025/03/31		96	%	80 - 120
			Dissolved Cobalt (Co)	2025/03/31		98	%	80 - 120
			Dissolved Copper (Cu)	2025/03/31		98	%	80 - 120
			Dissolved Lead (Pb)	2025/03/31		96	%	80 - 120
			Dissolved Molybdenum (Mo)	2025/03/31		97	%	80 - 120
			Dissolved Nickel (Ni)	2025/03/31		97	%	80 - 120
			Dissolved Selenium (Se)	2025/03/31		98	%	80 - 120
			Dissolved Silver (Ag)	2025/03/31		92	%	80 - 120
			Dissolved Sodium (Na)	2025/03/31		99	%	80 - 120
			Dissolved Thallium (TI)	2025/03/31		98	%	80 - 120
			Dissolved Uranium (U)	2025/03/31		99	%	80 - 120
			Dissolved Vanadium (V)	2025/03/31		96	%	80 - 120
			Dissolved Zinc (Zn)	2025/03/31		98	%	80 - 120
9900835	900835 N_R Method Blank	Dissolved Antimony (Sb)	2025/03/31	ND, RDL=0.50		ug/L		
			Dissolved Arsenic (As)	2025/03/31	ND, RDL=1.0		ug/L	
		Dissolved Barium (Ba)	2025/03/31	ND, RDL=2.0		ug/L		
		Dissolved Beryllium (Be)	2025/03/31	ND, RDL=0.40		ug/L		
			Dissolved Boron (B)	2025/03/31	ND, RDL=10		ug/L	
			Dissolved Cadmium (Cd)	2025/03/31	ND, RDL=0.090		ug/L	
			Dissolved Chromium (Cr)	2025/03/31	ND, RDL=5.0		ug/L	
			Dissolved Cobalt (Co)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Copper (Cu)	2025/03/31	ND, RDL=0.90		ug/L	
			Dissolved Lead (Pb)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Molybdenum (Mo)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Nickel (Ni)	2025/03/31	ND, RDL=1.0		ug/L	
			Dissolved Selenium (Se)	2025/03/31	ND, RDL=2.0		ug/L	
			Dissolved Silver (Ag)	2025/03/31	ND, RDL=0.090		ug/L	
			Dissolved Sodium (Na)	2025/03/31	ND, RDL=100		ug/L	
			Dissolved Thallium (TI)	2025/03/31	NÐ, RDL=0.050		ug/L	
			Dissolved Uranium (U)	2025/03/31	ND, RDL=0.10		ug/L	
			Dissolved Vanadium (V)	2025/03/31	ND, RDL=0.50		ug/L	
			Dissolved Zinc (Zn)	2025/03/31	ND, RDL=5.0		ug/L	
9900835	N_R	RPD [API\$12-03]	Dissolved Antimony (Sb)	2025/03/31	NC		%	20



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

QA/QC		007						
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Arsenic (As)	2025/03/31	NC		%	20
			Dissolved Barium (Ba)	2025/03/31	2.1		%	20
			Dissolved Beryllium (Be)	2025/03/31	NC		%	20
			Dissolved Boron (B)	2025/03/31	NC		%	20
			Dissolved Cadmium (Cd)	2025/03/31	NC		%	20
			Dissolved Chromium (Cr)	2025/03/31	NC		%	20
			Dissolved Cobalt (Co)	2025/03/31	NC		%	20
			Dissolved Copper (Cu)	2025/03/31	0.86		%	20
			Dissolved Lead (Pb)	2025/03/31	NC		%	20
			Dissolved Molybdenum (Mo)	2025/03/31	NC		%	20
			Dissolved Nickel (Ni)	2025/03/31	NC		%	20
			Dissolved Selenium (Se)	2025/03/31	NC		%	20
			Dissolved Silver (Ag)	2025/03/31	NC		%	20
			Dissolved Sodium (Na)	2025/03/31	0.76		%	20
			Dissolved Thallium (TI)	2025/03/31	NC		%	20
			Dissolved Uranium (U)	2025/03/31	2.1		%	20
			Dissolved Vanadium (V)	2025/03/31	NC		%	20
			Dissolved Zinc (Zn)	2025/03/31	NC		%	20
9901823	MKS	Matrix Spike	D10-Anthracene	2025/04/01		101	%	50 - 130
			D14-Terphenyl (FS)	2025/04/01		102	%	50 - 130
			D8-Acenaphthylene	2025/04/01		94	%	50 - 130
			Acenaphthene	2025/04/01		94	%	50 - 130
			Acenaphthylene	2025/04/01		92	%	50 - 130
			Anthracene	2025/04/01		106	%	50 - 130
			Benzo(a) anthracene	2025/04/01		103	%	50 - 130
			Benzo(a)pyrene	2025/04/01		97	%	50 - 130
			Benzo(b/j)fluoranthene	2025/04/01		100	%	50 - 130
			Benzo(g,h,i)perylene	2025/04/01		98	%	50 - 1 30
			Benzo(k)fluoranthene	2025/04/01		102	%	50 - 130
			Chrysene	2025/04/01		99	%	50 - 130
			Dibenzo (a,h) anthracene	2025/04/01		89	%	50 - 130
			Fluoranthene	2025/04/01		112	%	50 - 130
			Fluorene	2025/04/01		100	%	50 - 130
			Indeno(1,2,3-cd)pyrene	2025/04/01		105	%	50 - 1 30
			1-Methylnaphthalene	2025/04/01		92	%	50 - 130
			2-Methylnaphthalene	2025/04/01		90	%	50 - 130
			Naphthalene	2025/04/01		91	%	50 - 130
			Phenanthrene	2025/04/01		101	%	50 - 130
			Pyrene	2025/04/01		112	%	50 - 130
9901823	MKS	Spiked Blank	D10-Anthracene	2025/04/01		104	%	50 - 130
			D14-Terphenyl (FS)	2025/04/01		106	%	50 - 130
			D8-Acenaphthylene	2025/04/01		95	%	50 - 130
			Acenaphthene	2025/04/01		92	%	50 - 130
			Acenaphthylene	2025/04/01		90	%	50 - 130
			Anthracene	2025/04/01		103	%	50 - 130
			Benzo(a)anthracene	2025/04/01		101	%	50 - 130
			Benzo(a)pyrene	2025/04/01		96	%	50 - 130
			Benzo(b/j)fluoranthene	2025/04/01		99	%	50 - 130
			Benzo(g,h,i)perylene	2025/04/01		98	%	50 - 1 30
			Benzo(k)fluoranthene	2025/04/01		102	%	50 - 130
			Chrysene	2025/04/01		99	%	50 - 130



Site Location: SMITHS FALLS

Sampler Initials: GM

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limit
			Dibenzo(a,h)anthracene	2025/04/01		90	%	50 - 130
			Fluoranthene	2025/04/01		107	%	50 - 130
			Fluorene	2025/04/01		96	%	50 - 13
			Indeno(1,2,3-cd)pyrene	2025/04/01		107	%	50 - 130
			1-Methylnaphthalene	2025/04/01		88	%	50 - 130
			2-Methylnaphthalene	2025/04/01		86	%	50 - 130
			Naphthalene	2025/04/01		87	%	50 - 13
			Phenanthrene	2025/04/01		98	%	50 - 13
			Pyrene	2025/04/01		108	%	50 - 130
9901823	MKS	Method Blank	D10-Anthracene	2025/04/01		102	%	50 - 130
			D14-Terphenyl (FS)	2025/04/01		106	%	50 - 13
			D8-Acenaphthylene	2025/04/01		93	%	50 - 130
			Acenaphthene	2025/04/01	ND, RDL=0.050		ug/L	
			Acenaphthylene	2025/04/01	ND, RDL=0.050		ug/L	
			Anthracene	2025/04/01	ND, RDL=0.050		ug/L	
			Benzo(a)anthracene	2025/04/01	ND, RDL=0.050		ug/L	
			Benzo(a)pyrene	2025/04/01	ND, RDL=0.0090		ug/L	
			Benzo(b/j)fluoranthene	2025/04/01	ND, RDL=0.050		ug/L	
			Benzo(g,h,i)perylene	2025/04/01	ND, RDL=0.050		ug/L	
			Benzo(k)fluoranthene	2025/04/01	ND, RDL=0.050		ug/L	
			Chrysene	2025/04/01	ND, RDL=0.050		ug/L	
			Dibenzo(a,h)anthracene	2025/04/01	ND, RDL=0.050		ug/L	
			Fluoranthene	2025/04/01	ND, RDL=0.050		ug/L	
			Fluorene	2025/04/01	ND, RDL=0.050		ug/L	
			Indeno(1,2,3-cd)pyrene	2025/04/01	ND, RDL=0.050		ug/L	
			1-Methylnaphthalene	2025/04/01	ND, RDL=0.050		ug/L	
			2-Methylnaphthalene	2025/04/01	ND, RDL=0.050		ug/L	
			Naphthalene	2025/04/01	ND, RDL=0.050		ug/L	
			Phenanthrene	2025/04/01	ND, RDL=0.030		ug/L	
			Pyrene	2025/04/01	ND, RDL=0.050		ug/L	
901823	MKS	RPD	Acenaphthene	2025/04/01	NC		%	30
			Acenaphthylene	2025/04/01	NC		%	30
			Anthracene	2025/04/01	NC		%	30
			Benzo(a)anthracene	2025/04/01	NC		%	30



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limit
-		цотре	Benzo(a)pyrene	2025/04/01	NC	Necovery	%	30
			Benzo(b/j)fluoranthene	2025/04/01	NC		%	30
			Benzo(g,h,i)perylene	2025/04/01	NC		%	30
			Benzo(k)fluoranthene	2025/04/01	NC		%	30
			Chrysene	2025/04/01	NC		%	30
			Dibenzo(a,h)anthracene	2025/04/01	NC		%	30
			Fluoranthene	2025/04/01	NC		%	30
			Fluorene	2025/04/01	NC		%	30
			Indeno(1,2,3-cd)pyrene	2025/04/01	NC		%	30
			1-Methylnaphthalene	2025/04/01	NC.		%	30
			2-Methylnaphthalene	2025/04/01	NC		%	30
			Naphthalene	2025/04/01	NC		%	30
			Phenanthrene	2025/04/01	NC		%	30
			Pyrene	2025/04/01	NC		%	30
9901826	AS2	Matrix Spike	o-Terphenyl	2025/04/01	140	87	%	60 - 140
5501020	1112	matrix opino	F2 (C10-C16 Hydrocarbons)	2025/04/01		88	%	60 - 140
			F3 (C16-C34 Hydrocarbons)	2025/04/01		91	%	60 - 140
			F4 (C34-C50 Hydrocarbons)	2025/04/01		83	%	60 - 140
9901826	AS2	Spiked Blank	o-Terphenyl	2025/04/01		90	% %	60 - 140
3301020	732	Spined Dialin	FZ (C10-C16 Hydrocarbons)	2025/04/01		91	%	60 - 140
			F3 (C16-C34 Hydrocarbons)	2025/04/01		95	% ·	60 - 140
			F4 (C34-C50 Hydrocarbons)	2025/04/01		93 83	%	60 - 140
9901826	AS2	Method Blank	o-Terphenyl	2025/04/01		87	%	60 - 140
9901020	AJZ	WELIDO DIATIK	F2 (C10-C16 Hydrocarbons)	2025/04/01	ND	67		00 - 140
			, ,		ND, RDL=90		ug/L	
			F3 (C16-C34 Hydrocarbons)	2025/04/01	ND, RDL=200		ug/L	
			F4 (C34-C50 Hydrocarbons)	2025/04/01	ND, RDL=200		ug/L	
9901826	AS2	RPD	F2 (C10-C16 Hydrocarbons)	2025/04/01	NC		%	30
			F3 (C16-C34 Hydrocarbons)	2025/04/01	NC		%	30
			F4 (C34-C50 Hydrocarbons)	2025/04/01	NC		%	30
9902060	RSU	Matrix Spike [APIS12-04]	Chromium (VI)	2025/04/01		99	%	80 - 120
9902060	RSU	Spiked Blank	Chromium (VI)	2025/04/01		99	%	80 - 120
9902060	RSU	Method Blank	Chromium (VI)	2025/04/01	ND, RDL=0.50		ug/L	
9902060	RSU	RPD [APIS12-04]	Chromium (VI)	2025/04/01	NC		%	20
9902637	RGA	Matrix Spike	1,4-Difluorobenzene	2025/04/02		97	%	70 - 130
			4-Bromofluorobenzene	2025/04/02		102	%	70 - 130
			D10-o-Xylene	2025/04/02		98	%	70 - 130
			D4-1,2-Dichloroethane	2025/04/02		94	%	70 - 130
			Benzene	2025/04/02		87	%	50 - 1 40
			Toluene	2025/04/02		87	%	50 - 140
			Ethylbenzene	2025/04/02		102	%	50 - 140
			o-Xylene	2025/04/02		100	%	50 - 140
			p+m-Xylene	2025/04/02		95	%	50 - 140
			F1 (C6-C10)	2025/04/02		98	%	60 - 1 40
9902637	RGA	Spiked Blank	1,4-Diffuorobenzene	2025/04/02		95	%	70 - 130
		•	4-Bromofluorobenzene	2025/04/02		97	%	70 - 1 30
			D10-o-Xylene	2025/04/02		95	%	70 - 130
			D4-1,2-Dichloroethane	2025/04/02		91	%	70 - 1 30



St Lawrence Testing & Inspection Co Ltd Client Project #: SMITHS FALLS COMPOST SITE

Site Location: SMITHS FALLS

Sampler Initials: GM

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limit
			Benzene	2025/04/02		83	%	50 - 140
			Toluene	2025/04/02		84	%	50 - 140
			Ethylbenzene	2025/04/02		104	%	50 - 140
			o-Xylene	2025/04/02		96	%	50 - 140
			p+m-Xylene	2025/04/02		96	%	50 - 140
			F1 (C6-C10)	2025/04/02		97	%	60 - 140
9902637	RGA	Method Blank	1,4-Difluorobenzene	2025/04/02		96	%	70 - 130
			4-Bromofluorobenzene	2025/04/02		95	%	70 - 130
			D10-o-Xylene	2025/04/02		94	%	70 - 130
			D4-1,2-Dichloroethane	2025/04/02		95	%	70 - 130
			Benzene	2025/04/02	ND, RDL=0.20		ug/L	
			Toluene	2025/04/02	ND, RDL=0.20		ug/L	
			Ethylbenzene	2025/04/02	ND, RDL=0.20		ug/L	
			o-Xylene	2025/04/02	ND, RDL=0.20		ug/L	
			p+m-Xylene	2025/04/02	ND, RDL=0.40		ug/L	
			Total Xylenes	2025/04/02	ND, RDL=0.40		ug/L	
			F1 (C6-C10)	2025/04/02	ND, RDL=25		ug/L	
			F1 (C6-C10) - BTEX	2025/04/02	ND, RDL≃25		ug/L	
9902637	RGA	RPD	Benzene	2025/04/02	NC		%	30
			Toluene	2025/04/02	NC		%	30
			Ethylbenzene	2025/04/02	NC		%	30
			o-Xylene	2025/04/02	NC		%	30
			p+m-Xylene	2025/04/02	NC		%	30
			Total Xylenes	2025/04/02	NC		%	30
			F1 (C6-C10)	2025/04/02	NC		%	30
			F1 (C6-C10) - BTEX	2025/04/02	NC		%	30
9902695	MPJ	Matrix Spike	Mercury (Hg)	2025/04/02		94	%	75 - 125
9902695	MPJ	Spiked Blank	Mercury (Hg)	2025/04/02		98	%	80 - 120
9902695	MPJ	Method Blank	Mercury (Hg)	2025/04/02	ND, RDL=0.10		ug/L	
9902695	MPJ	RPD	Mercury (Hg)	2025/04/02	NC		%	20

 $\label{eq:Duplicate:Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.$

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate sample matrix interference.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.

Surrogate: A pure or isotopically labeled compound whose behavior mirrors the analytes of interest. Used to evaluate extraction efficiency.

NC (Duplicate RPD): The duplicate RPD was not calculated. The concentration in the sample and/or duplicate was too low to permit a reliable RPD calculation (absolute difference <= 2x RDL).



Site Location: SMITHS FALLS

Sampler Initials: GM

VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by:

Louise Harding, Scientific Specialist

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.

RLC-HydroG

ATTACHMENT J

Laboratory Certificate of Analysis – Groundwater



Your Project #: COMPOST SITE Site Location: SMITHS FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

Report Date: 2025/07/03

Report #: R8569237 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C577436 Received: 2025/06/27, 11:30

Sample Matrix: Water # Samples Received: 6

Analyses	Quantity	Date Extracted	Date Analyzed	Laboratory Method	Analytical Method
Methylnaphthalene Sum (1)	6	N/A	2025/07/02	CAM SOP-00301	EPA 8270D m
Chromium (VI) in Water (1)	6	N/A		CAM SOP-00436	EPA 7199 m
Petroleum Hydro. CCME F1 & BTEX in Water (1)	4	N/A		CAM SOP-00315	CCME PHC-CWS m
Petroleum Hydro. CCME F1 & BTEX in Water (1)	2	N/A		CAM SOP-00315	CCME PHC-CWS m
Petroleum Hydrocarbons F2-F4 in Water (1, 2)	6	2025/06/29		CAM SOP-00316	CCME PHC-CWS m
Mercury (1)	6	2025/06/30	2025/06/30	CAM SOP-00453	EPA 7470A m
Dissolved Metals by ICPMS (1)	6	N/A		CAM SOP-00447	EPA 6020B m
PAH Compounds in Water by GC/MS (SIM) (1)	6	2025/06/29	2025/06/30	CAM SOP-00318	EPA 8270E

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, EPA, APHA or the Quebec Ministry of Environment.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

- * RPDs calculated using raw data. The rounding of final results may result in the apparent difference.
- (1) This test was performed by Bureau Veritas Mississauga, 6740 Campobello Rd , Mississauga, ON, L5N 2L8
- (2) All CCME PHC results met required criteria unless otherwise stated in the report. The CWS PHC methods employed by Bureau Veritas conform to all prescribed elements of the



Your Project #: COMPOST SITE Site Location: SMITHS FALLS

Your C.O.C. #: N/A

Attention: Gib McIntee

St Lawrence Testing & Inspection Co Ltd

814 Second St W PO Box 997 Cornwall, ON CANADA K6H 5V1

Report Date: 2025/07/03

Report #: R8569237 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C577436

Received: 2025/06/27, 11:30

reference method and performance based elements have been validated. All modifications have been validated and proven equivalent following "Alberta Environment's Interpretation of the Reference Method for the Canada-Wide Standard for Petroleum Hydrocarbons in Soil Validation of Performance-Based Alternative Methods September 2003". Documentation is available upon request. Modifications from Reference Method for the Canada-wide Standard for Petroleum Hydrocarbons in Soil-Tier 1 Method: F2/F3/F4 data reported using validated cold solvent extraction instead of Soxhlet extraction.

Encryption Key

Jolanta Goralczyk Project Manager 03 Jul 2025 17:26:58

Please direct all questions regarding this Certificate of Analysis to:

Jolanta Goralczyk, Project Manager

Email: Jolanta.Goralczyk@bureauveritas.com

Phone# (905)817-5751

- thorough

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE
Site Location: SMITHS FALLS

O.REG 153 METALS PACKAGE (WATER)

Bureau Veritas ID		ASLF87			ASLF87			ASLF88	ASLF89		
Sampling Date		2025/06/26			2025/06/26			2025/06/26	2025/06/26		
	ļ	10:30			10:30			11:00	10:15		
COC Number		N/A			N/A			N/A	N/A		
	UNITS	MW 1	RDL	QC Batch	MW 1 Lab-Dup	RDL	QC Batch	MW 2	MW 3	RDL	QC Batch
Metals							-				
Chromium (VI)	ug/L	ND	0.50	9960659	ND	0.50	9960659	ND	ND	0.50	9960659
Mercury (Hg)	ug/L	ND	0.10	9960669				ND	ND	0.10	9960669
Dissolved Antimony (Sb)	ug/L	ND	0.50	9960077				ND	ND	0.50	9960077
Dissolved Arsenic (As)	ug/L	ND	1.0	9960077				1.9	ND	1.0	9960077
Dissolved Barium (Ba)	ug/L	150	2.0	9960077				350	190	2.0	9960077
Dissolved Beryllium (Be)	ug/L	ND	0.40	9960077				ND	ND	0.40	9960077
Dissolved Boron (B)	ug/L	21	10	9960077				56	51	10	9960077
Dissolved Cadmium (Cd)	ug/L	ND	0.090	9960077				ND	ND	0.090	9960077
Dissolved Chromium (Cr)	ug/L	ND	5.0	9960077				ND	ND	5.0	9960077
Dissolved Cobalt (Co)	ug/L	2.4	0.50	9960077				2.2	ND	0.50	9960077
Dissolved Copper (Cu)	ug/L	ND	0.90	9960077				3.4	0.97	0.90	9960077
Dissolved Lead (Pb)	ug/L	ND	0.50	9960077				ND	ND	0.50	9960077
Dissolved Molybdenum (Mo)	ug/L	2.6	0.50	9960077				13	4.9	0.50	9960077
Dissolved Nickel (Ni)	ug/L	2.4	1.0	9960077				3.2	2.1	1.0	9960077
Dissolved Selenium (Se)	ug/L	ND	2.0	9960077				ND	ND	2.0	9960077
Dissolved Silver (Ag)	ug/L	ND	0.090	9960077				ND	ND	0.090	9960077
Dissolved Sodium (Na)	ug/L	17000	100	9960077				300000	38000	100	9960077
Dissolved Thallium (TI)	ug/L	ND	0.050	9960077				ND	ND	0.050	9960077
Dissolved Uranium (U)	ug/L	0.70	0.10	9960077				2.6	1.3	0.10	9960077
Dissolved Vanadium (V)	ug/L	ND	0.50	9960077				4.2	ND	0.50	9960077
Dissolved Zinc (Zn)	ug/L	ND	5.0	9960077				ND	ND	5.0	9960077

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

Lab-Dup = Laboratory Initiated Duplicate



Site Location: SMITHS FALLS

O.REG 153 METALS PACKAGE (WATER)

Bureau Veritas ID		ASLF90	ASLF91	ASLF92		
Sampling Date		2025/06/26	2025/06/26	2025/06/26		
		10:00	09:40	10:45		
COC Number		N/A	N/A	N/A		
	UNITS	MW 4	MW 6	MW 7	RDL	QC Batch
Metals						
Chromium (VI)	ug/L	ND	1.9	ND	0.50	9960659
Mercury (Hg)	ug/L	ND	ND	ND	0.10	9960669
Dissolved Antimony (Sb)	ug/L	ND	ND	ND	0.50	9960077
Dissolved Arsenic (As)	ug/L	ND	ND	ND	1.0	9960077
Dissolved Barium (Ba)	ug/L	120	120	340	2.0	9960077
Dissolved Beryllium (Be)	ug/L	ND	ND	ND	0.40	9960077
Dissolved Boron (B)	ug/L	59	25	40	10	9960077
Dissolved Cadmium (Cd)	ug/L	ND	ND	ND	0.090	9960077
Dissolved Chromium (Cr)	ug/L	ND	ND	ND	5.0	9960077
Dissolved Cobalt (Co)	ug/L	0.86	ND	ND	0.50	9960077
Dissolved Copper (Cu)	ug/L	5.0	7.2	3.3	0.90	9960077
Dissolved Lead (Pb)	ug/L	ND	ND	ND	0.50	9960077
Dissolved Molybdenum (Mo)	ug/L	4.3	3.0	2.0	0.50	9960077
Dissolved Nickel (Ni)	ug/L	2.4	1.2	ND	1.0	9960077
Dissolved Selenium (Se)	ug/L	ND	ND	ND	2.0	9960077
Dissolved Silver (Ag)	ug/L	ND	ND	ND	0.090	9960077
Dissolved Sodium (Na)	ug/L	170000	210000	7800	100	9960077
Dissolved Thallium (TI)	ug/L	ND	ND	ND	0.050	9960077
Dissolved Uranium (U)	ug/L	10	1.0	2.8	0.10	9960077
Dissolved Vanadium (V)	ug/L	ND	1.3	0.59	0.50	9960077
Dissolved Zinc (Zn)	ug/L	ND	7.2	6.1	5.0	9960077

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



Site Location: SMITHS FALLS

O.REG 153 PAHS (WATER)

Bureau Veritas ID		ASLF87	ASLF88	ASLF89	ASLF90	ASLF91	ASLF92		
Sampling Date		2025/06/26	2025/06/26	2025/06/26	2025/06/26	2025/06/26	2025/06/26		
		10:30	11:00	10:15	10:00	09:40	10:45	ĺ	
COC Number	ļ	N/A	N/A	N/A	N/A	N/A	N/A		
	UNITS	MW 1	MW 2	MW 3	MW 4	MW 6	MW 7	RDL	QC Batch
Calculated Parameters		· · · · · · · · · · · · · · · · · · ·							'
Methylnaphthalene, 2-(1-)	ug/L	ND	ND	ND	ND	ND	ND	0.071	9959971
Polyaromatic Hydrocarbons									0000071
Acenaphthene	ug/L	ND	ND	0.098	ND	ND	ND	0.050	9960196
Acenaphthylene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Anthracene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Benzo(a) anthracene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Benzo(a)pyrene	ug/L	ND	ND	ND	ND	ND	ND	0.0090	9960196
Benzo(b/j)fluoranthene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Benzo(g,h,i)perylene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Benzo(k) fluoranthene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Chrysene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Dibenzo (a,h) anthracene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Fluoranthene	ug/L	0.052	ND	0.098	ND	ND	ND	0.050	9960196
Fluorene	ug/L	ND	ND	0.078	ND	ND	ND	0.050	9960196
Indeno(1,2,3-cd)pyrene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
1-Methylnaphthalene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
2-Methylnaphthalene	ug/L	ND	ND	ND	ND	ND	ND	0.050	9960196
Naphthalene	ug/L	ND	ND	0.12	ND	ND	ND	0.050	9960196
Phenanthrene	ug/L	0.18	ND	0.33	0.031	0.083	0.064	0.030	9960196
Pyrene	ug/L	0.073	ND	0.080	ND	ND	ND	0.050	9960196
Surrogate Recovery (%)					<u>.</u>				
D10-Anthracene	%	101	98	94	99	99	86	· · · · · · · · · · · · · · · · · · ·	9960196
D14-Terphenyl (FS)	%	96	92	88	93	95	79		9960196
D8-Acenaphthylene	%	95	89	88	89	91	78		9960196
DI - Papartable Detection Li	••								

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch

ND = Not Detected at a concentration equal or greater than the indicated Detection Limit.



Site Location: SMITHS FALLS

O.REG 153 PHCS, BTEX/F1-F4 (WATER)

JNITS	ASLF87 2025/06/26 10:30 N/A MW 1	ASLF88 2025/06/26 11:00 N/A	ASLF89 2025/06/26 10:15 N/A	ASLF90 2025/06/26 10:00	ASLF91 2025/06/26 09:40	ASLF92 2025/06/26 10:45		
JNITS	10:30 N/A	11:00	10:15	10:00	, ,			
JNITS	N/A				09:40	10:45		
JNITS		N/A	N/A					İ
INITS	MW 1			N/A	N/A	N/A		
		MW 2	MW 3	MW 4	MW 6	MW 7	RDL	QC Batch
ug/L	ND	0.40	0.28	ND	ND	ND	0.20	9961684
ug/L	ND	0.33	0.46	ND	26	ND	0.20	9961684
ug/L	ND	ND	ND	ND	ND	ND	0.20	9961684
ug/L	ND	ND	ND	ND	ND	ND	0.20	9961684
ug/L	ND	ND	ND	ND	ND	ND	0.40	9961684
ug/L	ND	ND	ND	ND	ND	ND	0.40	9961684
ug/L	ND	ND	ND	ND	34	ND	25	9961684
ug/L	ND	ND	ND	ND	ND	ND	25	9961684
				1				
ug/L	ND	ND	ND	ND	ND	ND	90	9960197
ug/L	ND	ND	ND	ND	ND	ND	200	9960197
ug/L	ND	ND	ND	ND	ND	ND	200	9960197
ug/L	Yes	Yes	Yes	Yes	Yes	Yes		9960197
							1	
%	99	99	100	99	97	99		9961684
%	96	90	95	87	92	92		9961684
%	97	97	91	93	93	92		9961684
%	104	102	104	105	106	106		9961684
%	98	98	98	98	97	100		9960197
	ng/L ng/L ng/L ng/L ng/L ng/L ng/L ng/L	Ig/L ND Ig/L Yes	Ig/L ND 0.33 Ig/L ND ND Ig/L Yes Yes % 99 99 % 96 90 % 97 97 % 104 102	ag/L ND 0.33 0.46 ag/L ND ND ND ag/L Yes Yes Yes % 99 99 100 % 96 90 95 % 97 97 91 % 104 102 104	Ig/L ND 0.33 0.46 ND Ig/L ND ND ND ND Ig/L Yes Yes Yes Yes Yes Yes Yes % 99 99 100 99 % 96 90 95 87 % 97 97 91 93 % 104 102 104 105	Ig/L ND 0.33 0.46 ND 26 Ig/L ND ND ND ND ND Ig/L ND ND<	Ig/L ND 0.33 0.46 ND 26 ND Ig/L ND ND ND ND ND ND ND Ig/L ND ND	Ig/L ND 0.33 0.46 ND 26 ND 0.20 Ig/L ND ND ND ND ND ND 0.20 Ig/L ND ND ND ND ND ND ND 0.40 Ig/L ND ND ND ND ND ND ND 0.40 Ig/L ND ND ND ND ND ND ND 0.40 Ig/L ND ND ND ND ND ND ND 25 Ig/L ND ND ND ND ND ND ND 90 Ig/L ND ND ND ND ND ND ND ND 200 Ig/L ND ND <t< td=""></t<>

RDL = Reportable Detection Limit

QC Batch = Quality Control Batch



Bureau Veritas Job #: C577436 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITHS FALLS

TEST SUMMARY

Bureau Veritas ID: ASLF87 Sample ID: MW 1 Matrix: Water

Collected: 2025/06/26

Shipped: Received: 2025/06/27

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959971	N/A	2025/07/02	Automated Statchk
Chromium (VI) in Water	IC	9960659	N/A	2025/06/30	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9961684	N/A	2025/07/03	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9960197	2025/06/29	2025/06/30	Jeevaraj Jeevaratrnam
Mercury	CV/AA	9960669	2025/06/30	2025/06/30	Maitri PATIL
Dissolved Metals by ICPMS	1CP/MS	9960077	N/A	2025/06/30	Prempal Bhatti
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9960196	2025/06/29	2025/06/30	Biljana Lazovic

Bureau Veritas ID: ASLF87 Dup Sample ID: MW 1

Matrix: Water

Matrix: Water

Collected: 2025/06/26

Shipped: Received: 2025/06/27

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Chromium (VI) in Water	IC	9960659	N/A	2025/06/30	Rupinder Sihota

Bureau Veritas ID: ASLF88 Sample ID: MW 2

Collected: 2025/06/26

Shipped:

Received: 2025/06/27

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959971	N/A	2025/07/02	Automated Statchk
Chromium (VI) in Water	IC	9960659	N/A	2025/06/30	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9961684	N/A	2025/07/03	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9960197	2025/06/29	2025/06/30	Jeevarai Jeevaratrnam
Mercury	CV/AA	9960669	2025/06/30	2025/06/30	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9960077	N/A	2025/06/30	Prempal Bhatti
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9960196	2025/06/29	2025/06/30	Biliana Lazovic

Bureau Veritas ID: ASLF89 Sample ID: MW 3

Collected: 2025/06/26

Shipped:

ipped:

Matrix: Water

Received: 2025/06/27

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959971	N/A	2025/07/02	Automated Statchk
Chromium (VI) in Water	IC	9960659	N/A	2025/06/30	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9961684	N/A	2025/07/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9960197	2025/06/29	2025/06/30	Jeevaraj Jeevaratrnam
Mercury	CV/AA	9960669	2025/06/30	2025/06/30	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9960077	N/A	2025/06/30	Prempal Bhatti
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9960196	2025/06/29	2025/06/30	Biljana Lazovic



Site Location: SMITHS FALLS

TEST SUMMARY

Bureau Veritas ID: ASLF90 Sample ID: MW 4 Matrix: Water

Collected: 2025/06/26

Shipped:

Received: 2025/06/27

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959971	N/A	2025/07/02	Automated Statchk
Chromium (VI) in Water	IC	9960659	N/A	2025/06/30	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9961684	N/A	2025/07/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9960197	2025/06/29	2025/06/30	Jeevaraj Jeevaratrnam
Mercury	CV/AA	9960669	2025/06/30	2025/06/30	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9960077	N/A	2025/06/30	Prempal Bhatti
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9960196	2025/06/29	2025/06/30	Biljana Lazovic

Bureau Veritas ID: ASLF91 Sample ID: MW 6 Matrix: Water

Collected: 2025/06/26

Shipped: Received: 2025/06/27

Test Description Instrumentation Batch Extracted Date Analyzed Analyst Methylnaphthalene Sum CALC 9959971 N/A 2025/07/02 Automated Statchk Chromium (VI) in Water IC 9960659 N/A 2025/06/30 Rupinder Sihota Petroleum Hydro. CCME F1 & BTEX in Water HSGC/MSFD 9961684 N/A 2025/07/02 Ravinder Gaidhu Petroleum Hydrocarbons F2-F4 in Water GC/FID 9960197 2025/06/29 2025/06/30 Jeevaraj Jeevaratrnam Mercury CV/AA 9960669 2025/06/30 2025/06/30 Maitri PATIL Dissolved Metals by ICPMS ICP/MS 9960077 N/A 2025/06/30 Prempal Bhatti PAH Compounds in Water by GC/MS (SIM) GC/MS 9960196 2025/06/29 2025/06/30 Biljana Lazovic

Bureau Veritas ID: ASLF92 Sample ID: MW 7 Matrix: Water

Collected: 2025/06/26

Shipped:

Received: 2025/06/27

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
Methylnaphthalene Sum	CALC	9959971	N/A	2025/07/02	Automated Statchk
Chromium (VI) in Water	IC	9960659	N/A	2025/06/30	Rupinder Sihota
Petroleum Hydro. CCME F1 & BTEX in Water	HSGC/MSFD	9961684	N/A	2025/07/02	Ravinder Gaidhu
Petroleum Hydrocarbons F2-F4 in Water	GC/FID	9960197	2025/06/29	2025/06/30	Jeevaraj Jeevaratrnam
Mercury	CV/AA	9960669	2025/06/30	2025/06/30	Maitri PATIL
Dissolved Metals by ICPMS	ICP/MS	9960077	N/A	2025/06/30	Prempal Bhatti
PAH Compounds in Water by GC/MS (SIM)	GC/MS	9960196	2025/06/29	2025/06/30	Biljana Lazovic



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE Site Location: SMITHS FALLS

GENERAL COMMENTS

Each temperature is the	average of up t	three cooler temperatures tal	ken at receipt	
Package 1	8.7°C			
		_		
Results relate only to the	e items tested.			



Bureau Veritas Job #: C577436 Report Date: 2025/07/03 St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITHS FALLS

QUALITY ASSURANCE REPORT

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
9960077	PBA	Matrix Spike	Dissolved Antimony (Sb)	2025/06/30		104	%	80 - 120
			Dissolved Arsenic (As)	2025/06/30		102	%	80 - 120
			Dissolved Barium (Ba)	2025/06/30		103	%	80 - 120
			Dissolved Beryllium (Be)	2025/06/30		103	%	80 - 120
			Dissolved Boron (B)	2025/06/30		102	%	80 - 120
			Dissolved Cadmium (Cd)	2025/06/30		102	%	80 - 120
			Dissolved Chromium (Cr)	2025/06/30		104	%	80 - 120
			Dissolved Cobalt (Co)	2025/06/30		100	%	80 - 120
			Dissolved Copper (Cu)	2025/06/30		104	%	80 - 120
			Dissolved Lead (Pb)	2025/06/30		97	%	80 - 120
			Dissolved Molybdenum (Mo)	2025/06/30		103	%	80 - 120
			Dissolved Nickel (Ni)	2025/06/30		99	%	80 - 120
			Dissolved Selenium (Se)	2025/06/30		102	%	80 - 120
			Dissolved Silver (Ag)	2025/06/30		99	%	80 - 120
			Dissolved Sodium (Na)	2025/06/30		NC	%	80 - 120
			Dissolved Thallium (TI)	2025/06/30		99	%	80 - 120
			Dissolved Uranium (U)	2025/06/30		98	%	80 - 120
			Dissolved Vanadium (V)	2025/06/30		104	%	80 - 120
			Dissolved Zinc (Zn)	2025/06/30		99	%	80 - 120
9960077	PBA	Spiked Blank	Dissolved Antimony (Sb)	2025/06/30		102	%	80 - 120
			Dissolved Arsenic (As)	2025/06/30		101	%	80 - 120
			Dissolved Barium (Ba)	2025/06/30		101	%	80 - 120
			Dissolved Beryllium (Be)	2025/06/30		101	%	80 - 120
			Dissolved Boron (B)	2025/06/30		99	%	80 - 120
			Dissolved Cadmium (Cd)	2025/06/30		100	%	80 - 120
			Dissolved Chromium (Cr)	2025/06/30		101	%	80 - 120
			Dissolved Cobalt (Co)	2025/06/30		99	%	80 - 120
			Dissolved Copper (Cu)	2025/06/30		102	%	80 - 120
			Dissolved Lead (Pb)	2025/06/30		98	%	80 - 120
			Dissolved Molybdenum (Mo)	2025/06/30		101	%	80 - 120
			Dissolved Nickel (Ni)	2025/06/30		99	%	80 - 120
			Dissolved Selenium (Se)	2025/06/30		100	%	80 - 120
			Dissolved Silver (Ag)	2025/06/30		97	%	80 - 120
			Dissolved Sodium (Na)	2025/06/30		97	%	80 - 120
			Dissolved Thallium (TI)	2025/06/30		99	%	80 - 120
			Dissolved Uranium (U)	2025/06/30		97	%	80 - 120
			Dissolved Vanadium (V)	2025/06/30		101	%	80 - 120
			Dissolved Zinc (Zn)	2025/06/30		98	%	80 - 120
9960077	PBA	Method Blank	Dissolved Antimony (Sb)	2025/06/30	ND, RDL=0.50		ug/L	
			Dissolved Arsenic (As)	2025/06/30	ND, RDL=1.0		ug/L	
			Dissolved Barium (Ba)	2025/06/30	ND, RDL=2.0		ug/L	
			Dissolved Beryllium (Be)	2025/06/30	ND, RDL=0.40		ug/L	
			Dissolved Boron (B)	2025/06/30	ND, RDL=10		ug/L	
			Dissolved Cadmium (Cd)	2025/06/30	ND, RDL=0.090		ug/L	
			Dissolved Chromium (Cr)	2025/06/30	ND, RDL=5.0		ug/L	
			Dissolved Cobalt (Co)	2025/06/30	ND, RDL=0.50		ug/L	



Site Location: SMITHS FALLS

QA/QC			QUALITY ASSURANCE	•		 -		
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Copper (Cu)	2025/06/30	ND,	Necovery	ug/L	QC Ellines
				, ,	RDL=0.90			
			Dissolved Lead (Pb)	2025/06/30	ND,		ug/L	
					RDL=0.50		O,	
			Dissolved Molybdenum (Mo)	2025/06/30	ND,		ug/L	
					RDL=0.50			
			Dissolved Nickel (Ni)	2025/06/30	ND,		ug/L	
			Discolus d Col. 1 (C.)		RDL=1.0			
			Dissolved Selenium (Se)	2025/06/30	ND,		ug/L	
			Dissolved Silver (Ag)	2025/06/30	RDL=2.0		<i>(</i> 1	
			Dissolved Silver (AB)	2023/00/30	ND, RDL=0.090		ug/L	
			Dissolved Sodium (Na)	2025/06/30	ND,		/	
			(144)	2023/00/30	RDL=100		ug/L	
			Dissolved Thallium (TI)	2025/06/30	ND,		ug/L	
			• •	,,	RDL=0.050		u ₈ / L	
			Dissolved Uranium (U)	2025/06/30	ND,		ug/L	
					RDL=0.10		J,	
			Dissolved Vanadium (V)	2025/06/30	ND,		ug/L	
					RDL=0.50			
			Dissolved Zinc (Zn)	2025/06/30	ND,		ug/L	
9960077	DD 4	000	D: 1 14 11 (01)		RDL=5.0			
3300077	PBA	RPD	Dissolved Antimony (Sb)	2025/06/30	NC		%	20
			Dissolved Arsenic (As)	2025/06/30	1.4		%	20
			Dissolved Barium (Ba)	2025/06/30	1.7		%	20
			Dissolved Beryllium (Be) Dissolved Boron (B)	2025/06/30	NC		%	20
			Dissolved Boron (B) Dissolved Cadmium (Cd)	2025/06/30	1.9		%	20
			Dissolved Carmum (Ca)	2025/06/30 2025/06/30	NC		%	20
			Dissolved Cobalt (Co)	2025/06/30	NC NC		%	20
			Dissolved Copper (Cu)	2025/06/30	NC		% %	20
			Dissolved Lead (Pb)	2025/06/30	NC		% %	20 20
			Dissolved Molybdenum (Mo)	2025/06/30	0.94		%	20
			Dissolved Nickel (Ni)	2025/06/30	NC		%	20
			Dissolved Selenium (Se)	2025/06/30	NC		%	20
			Dissolved Silver (Ag)	2025/06/30	NC		%	20
			Dissolved Sodium (Na)	2025/06/30	0.31		%	20
			Dissolved Thallium (TI)	2025/06/30	NC		%	20
			Dissolved Uranium (U)	2025/06/30	8.0		%	20
			Dissolved Vanadium (V)	2025/06/30	3.1		%	20
			Dissolved Zinc (Zn)	2025/06/30	NC		%	20
9960196	BLZ	Matrix Spike	D10-Anthracene	2025/06/30		98	%	50 - 130
			D14-Terphenyl (FS)	2025/06/30		94	%	50 - 130
			D8-Acenaphthylene	2025/06/30		89	%	50 - 130
			Acenaphthene	2025/06/30		100	%	50 - 130
			Acenaphthylene	2025/06/30		100	%	50 - 130
			Anthracene	2025/06/30		102	%	50 - 130
			Benzo(a)anthracene	2025/06/30		100	%	50 - 130
			Benzo(a)pyrene	2025/06/30		97	%	50 - 130
			Benzo(b/j)fluoranthene	2025/06/30		97	%	50 - 130
			Benzo(g,h,i)perylene	2025/06/30		98	%	50 - 130
			Benzo(k)fluoranthene	2025/06/30		94	%	50 - 130
			Chrysene	2025/06/30		97	%	50 - 130
			Dibenzo(a,h)anthracene	2025/06/30		101	%	50 - 130



St Lawrence Testing & Inspection Co Ltd

Client Project #: COMPOST SITE
Site Location: SMITHS FALLS

QA/QC			QUALITY ASSURANCE					
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Danassans	LINUTE	001: 11
			Fluoranthene	2025/06/30	value	Recovery 101	UNITS %	QC Limits 50 - 130
			Fluorene	2025/06/30		100	% %	50 - 130
			Indeno(1,2,3-cd)pyrene	2025/06/30		100	% %	50 - 130
			1-Methylnaphthalene	2025/06/30		103	% %	50 - 130
			2-Methylnaphthalene	2025/06/30		103	% %	50 - 130 50 - 130
			Naphthalene	2025/06/30		124	% %	50 - 130 50 - 130
			Phenanthrene	2025/06/30		98	% %	50 - 130 50 - 130
			Pyrene	2025/06/30		100	% %	50 - 130
9960196	BLZ	Spiked Blank	D10-Anthracene	2025/06/30		99	% %	50 - 130
		•	D14-Terphenyl (FS)	2025/06/30		100	%	50 - 130
			D8-Acenaphthylene	2025/06/30		91	%	50 - 130
			Acenaphthene	2025/06/30		98	%	50 - 130
			Acenaphthylene	2025/06/30		99	%	50 - 130
			Anthracene	2025/06/30		100	%	50 - 130
			Benzo(a)anthracene	2025/06/30		98	%	50 - 130
			Benzo(a)pyrene	2025/06/30		96	%	50 - 130
			Benzo(b/j)fluoranthene	2025/06/30		96	%	50 - 130 50 - 130
			Benzo(g,h,i)perylene	2025/06/30		91	%	50 - 130
			Benzo(k)fluoranthene	2025/06/30		96	% %	50 - 130
			Chrysene	2025/06/30		96	% %	50 - 130
		•	Dibenzo(a,h)anthracene	2025/06/30		96	% %	50 - 130
			Fluoranthene	2025/06/30		101	% %	
			Fluorene	2025/06/30		98	% %	50 - 130 50 - 130
			Indeno(1,2,3-cd)pyrene	2025/06/30		94	% %	
			1-Methylnaphthalene	2025/06/30		102	% %	50 - 130 50 - 130
			2-Methylnaphthalene	2025/06/30		102	%	50 - 130
			Naphthalene	2025/06/30		120	%	50 - 130
			Phenanthrene	2025/06/30		96	%	50 - 130
			Pyrene	2025/06/30		100	% %	50 - 130
9960196	BLZ	Method Blank	D10-Anthracene	2025/06/30		101	% %	50 - 130
			D14-Terphenyl (FS)	2025/06/30		98	%	50 - 130
			D8-Acenaphthylene	2025/06/30		92	%	50 - 130
			Acenaphthene	2025/06/30	ND, RDL=0.050	32	ug/L	30 - 130
			Acenaphthylene	2025/06/30	ND, RDL=0.050		ug/L	
			Anthracene	2025/06/30	ND, RDL=0.050		ug/L	
			Benzo(a)anthracene	2025/06/30	ND, RDL=0.050		ug/L	
			Benzo(a)pyrene	2025/06/30	ND, RDL=0.0090		ug/L	
			Benzo(b/j)fluoranthene	2025/06/30	ND, RDL=0.050		ug/L	
			Benzo(g,h,i)perylene	2025/06/30	ND, RDL=0.050		ug/L	
			Benzo(k)fluoranthene	2025/06/30	ND, RDL=0.050		ug/L	
			Chrysene	2025/06/30	ND, RDL=0.050		ug/L	
			Dibenzo(a,h)anthracene	2025/06/30	ND, RDL=0.050		ug/L	
			Fluoranthene	2025/06/30	ND, RDL=0.050		ug/L	



Site Location: SMITHS FALLS

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Fluorene	2025/06/30	ND, RDL=0.050	Haddieny	ug/L	QO ENTITES
			Indeno(1,2,3-cd)pyrene	2025/06/30	ND, RDL=0.050		ug/L	
			1-Methylnaphthalene	2025/06/30	ND,		ug/L	
			2-Methylnaphthalene	2025/06/30	RDL=0.050 ND,		ug/L	
			Naphthalene	2025/06/30	RDL=0.050 ND,		ug/L	
			Phenanthrene	2025/06/30	RDL=0.050 ND,		ug/L	
			Pyrene	2025/06/30	RDL=0.030 ND,		ug/L	
					RDL=0.050		.	
9960196	BLZ	RPD	Acenaphthene	2025/06/30	NC		%	30
			Acenaphthylene	2025/06/30	NC		%	30
			Anthracene	2025/06/30	NC		%	30
			Benzo(a) anthracene	2025/06/30	NC		%	30
			Benzo(a)pyrene	2025/06/30	NC		%	30
			Benzo(b/j)fluoranthene	2025/06/30	NC		%	30
			Benzo(g,h,i)perylene	2025/06/30	NC		%	30
			Benzo(k)fluoranthene	2025/06/30	NC		%	30
			Chrysene	2025/06/30	NC		%	30
			Dibenzo(a,h)anthracene	2025/06/30	NC		%	30
			Fluoranthene	2025/06/30	NC		%	30
			Fluorene	2025/06/30	NC		%	30
			Indeno(1,2,3-cd)pyrene	2025/06/30	NC		%	30
			1-Methylnaphthalene	2025/06/30	NC		%	30
			2-Methylnaphthalene	2025/06/30	NC		%	30
			Naphthalene	2025/06/30	NC		%	30
			Phenanthrene	2025/06/30	NC		%	30
			Pyrene	2025/06/30	NC		%	30
9960197	IJΕ	Matrix Spike	o-Terphenyl	2025/06/30		100	%	60 - 140
			F2 (C10-C16 Hydrocarbons)	2025/06/30		94	%	60 - 140
			F3 (C16-C34 Hydrocarbons)	2025/06/30		97	%	60 - 140
			F4 (C34-C50 Hydrocarbons)	2025/06/30		83	%	60 - 140
9960197	JJE	Spiked Blank	o-Terphenyl	2025/06/30		98	%	60 - 140
			F2 (C10-C16 Hydrocarbons)	2025/06/30		94	%	60 - 140
			F3 (C16-C34 Hydrocarbons)	2025/06/30		99	%	60 - 140
			F4 (C34-C50 Hydrocarbons)	2025/06/30		87	%	60 - 140
9960197	JJE	Method Blank	o-Terphenyl	2025/06/30		96	%	60 - 140
			F2 (C10-C16 Hydrocarbons)	2025/06/30	ND, RDL=90		ug/L	
			F3 (C16-C34 Hydrocarbons)	2025/06/30	ND, RDL=200		ug/L	
			F4 (C34-C50 Hydrocarbons)	2025/06/30	ND, RDL=200		ug/L	
9960197	JJE	RPD	F2 (C10-C16 Hydrocarbons)	2025/06/30	NC NC		%	30
			F3 (C16-C34 Hydrocarbons)	2025/06/30	NC		%	30
			F4 (C34-C50 Hydrocarbons)	2025/06/30	NC		% %	30
9960659	RSU	Matrix Spike [ASLF87-01]	Chromium (VI)	2025/06/30	110	101	%	80 - 120
9960659	RSU	Spiked Blank	Chromium (VI)	2025/06/30		101	%	80 - 120
9960659	RSU	Method Blank	Chromium (VI)	2025/06/30	ND,	100	ug/L	00.120
				_5_5,00,50	RDL=0.50		46/ L	



Bureau Veritas Job #: C577436 Report Date: 2025/07/03

St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE

Site Location: SMITHS FALLS

Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limit
9960659	RSU	RPD [ASLF87-01]	Chromium (VI)	2025/06/30	NC		%	20
9960669	MPJ	Matrix Spike	Mercury (Hg)	2025/06/30		89	%	75 - 125
9960669	MPJ	Spiked Blank	Mercury (Hg)	2025/06/30		91	%	80 - 120
9960669	MPJ	Method Blank	Mercury (Hg)	2025/06/30	ND, RDL=0.10		ug/L	
9960669	MPJ	RPD	Mercury (Hg)	2025/06/30	NC		%	20
9961684	RGA	Matrix Spike	1,4-Difluorobenzene	2025/07/02		97	%	70 - 130
			4-Bromofluorobenzene	2025/07/02		103	%	70 - 130
			D10-o-Xylene	2025/07/02		88	%	70 - 130
			D4-1,2-Dichloroethane	2025/07/02		99	%	70 - 130
			Benzene	2025/07/02		87	%	50 - 140
			Toluene	2025/07/02		86	%	50 - 140
			Ethylbenzene	2025/07/02		94	%	50 - 140
			o-Xylene	2025/07/02		92	%	50 - 140
			p+m-Xylene	2025/07/02		93	%	50 - 140
			F1 (C6-C10)	2025/07/02		100	%	60 - 140
9961684	RGA	Spiked Blank	1,4-Difluorobenzene	2025/07/02		96	%	70 - 130
			4-Bromofluorobenzene	2025/07/02		103	%	70 - 130
			D10-o-Xylene	2025/07/02		87	%	70 - 130
			D4-1,2-Dichloroethane	2025/07/02		98	%	70 - 130
			Benzene	2025/07/02		88	%	50 - 140
			Toluene	2025/07/02		88	%	50 - 140
			Ethylbenzene	2025/07/02		96	%	50 - 140
			o-Xylene	2025/07/02		94	%	50 - 140
			p+m-Xylene	2025/07/02		96	%	50 - 140
			F1 (C6-C10)	2025/07/02		100	%	60 - 140
9961684	RGA	Method Blank	1,4-Difluorobenzene	2025/07/02		100	%	70 - 130
			4-Bromofluorobenzene	2025/07/02		98	%	70 - 130
			D10-o-Xylene	2025/07/02		92	%	70 - 130
			D4-1,2-Dichloroethane	2025/07/02		102	%	70 - 130
			Benzene	2025/07/02	ND, RDL=0.20		ug/L	, 5 250
			Toluene	2025/07/02	ND, RDL=0.20		ug/L	
			Ethylbenzene	2025/07/02	ND, RDL=0.20		ug/L	
			o-Xylene	2025/07/02	ND, RDL=0.20		ug/L	
			p+m-Xylene	2025/07/02	ND, RDL=0.40		ug/L	
			Total Xylenes	2025/07/02	ND, RDL=0.40		ug/L	
			F1 (C6-C10)	2025/07/02	ND, RDL=25		ug/L	
			F1 (C6-C10) - BTEX	2025/07/02	ND, RDL=25		ug/L	
961684	RGA	RPD	Benzene	2025/07/02	NC		%	30
			Toluene	2025/07/02	NC		%	30
			Ethylbenzene	2025/07/02	NC		%	30
			o-Xylene	2025/07/02	NC		%	30
			p+m-Xylene	2025/07/02	NC		%	30
			Total Xylenes	2025/07/02	NC		%	30
			F1 (C6-C10)	2025/07/02	NC		%	30



Site Location: SMITHS FALLS

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC					_			
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			F1 (C6-C10) - BTEX	2025/07/02	NC		%	30

Duplicate: Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate sample matrix interference.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.

Surrogate: A pure or isotopically labeled compound whose behavior mirrors the analytes of interest. Used to evaluate extraction efficiency.

NC (Matrix Spike): The recovery in the matrix spike was not calculated. The relative difference between the concentration in the parent sample and the spike amount was too small to permit a reliable recovery calculation (matrix spike concentration was less than the native sample concentration)

NC (Duplicate RPD): The duplicate RPD was not calculated. The concentration in the sample and/or duplicate was too low to permit a reliable RPD calculation (absolute difference <= 2x RDL).



St Lawrence Testing & Inspection Co Ltd Client Project #: COMPOST SITE
Site Location: SMITHS FALLS

VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by:

Cristia	Carriere	
Cristina Carrie	re, Senior Scientific Specialist	

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.

RLC-HydroG

ATTACHMENT K
Spill Response Plan

Spill Response Plan

Town of Smiths Falls Compost Site

The Town of Smiths Falls addresses spill response within the broader framework of its Municipal Emergency Management Program, which focuses on hazard identification, planning, training, exercises, and public education to ensure community preparedness and resilience against various emergencies, including potential spills. Spill response is integrated into the municipality's comprehensive emergency management efforts and its commitment to protecting the environment and drinking water.

1. Purpose

This plan outlines procedures for responding to accidental spills at the Smiths Falls Compost Site, where potential sources of contamination include petroleum hydrocarbons (PHCs) and BTEX compounds associated with vehicular traffic and mobile machinery (e.g., loader and contractor screening equipment). All vehicles and machinery are stored, refueled, and serviced offsite.

2. Scope

This plan applies to all site personnel and contractors operating at the compost facility.

3. Potential Spill Sources

- Leaks or minor spills from mobile equipment during operation (e.g., hydraulic fluid, diesel, motor oil).
- Accidental rupture of fuel or oil lines on vehicles in use.

4. Spill Prevention Measures

- All equipment is stored, refueled, and serviced offsite.
- Routine visual inspections of equipment before operation.
- Operators trained in spill recognition and response.
- Spill response kits maintained onsite near operational areas.

5. Spill Response Procedure

In the event of a spill:

Step 1: Ensure safety.

Stop work and secure the area. Avoid contact with spilled material.

• Step 2: Contain the spill.

Use absorbent socks, pads, or booms to prevent spread, especially near stormwater conveyances or permeable ground.

• Step 3: Notify supervisor and Town representative.

Report all spills immediately, regardless of size.

Phone: 613.283.4124 Email: info@smithsfalls.ca

Step 4: Clean up the spill.

Use absorbents and dispose of contaminated material in accordance with provincial guidelines.

• Step 5: Record and report.

Complete an incident report including date, time, material spilled, estimated volume, cause, response actions, and disposal method.

• Step 6: Notify authorities if required.

If the spill exceeds reportable quantities under **Ontario Regulation 675/98 (Spills)**, contact the **Spills Action Centre (1-800-268-6060)**.

6. Equipment and Materials

- Onsite spill response kit to include:
 - Absorbent pads and booms
 - Disposal bags
 - Nitrile gloves and safety goggles
 - Dustpan and broom
 - o Instructions and contact list

7. Training and Review

- All site personnel and contractors shall be trained in this plan annually.
- This plan shall be reviewed and updated annually or after any spill incident.